

## DENSOTHERM TAPE

### Hot Applied Pipeline Tape

#### Description

Densotherm Tape is a hot applied bituminous tape. It is comprised of a non-woven synthetic fabric fully impregnated and coated with a flexible, high melting point bitumen compound.

#### Uses

Densotherm is suitable for use above or below ground for protecting pipes, fittings, welds and bends. The tape is applied with the aid of a propane gas torch.

#### Features

- Excellent adhesion to pipe and self
- Excellent resistance to cathodic disbonding
- Good impact resistance
- Good conformability
- Hot applied
- Compatible with common pipe coatings

#### Application

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Surface must be clean, dry and free of grease. Apply a thin film of Denso Primer D to all surfaces to be wrapped and allow to dry. Begin wrapping using a reverse spiral wrap, at the same time, apply a flame torch to side of tape that is in contact with the surface. Then, apply heat to form a gloss-like texture to the outside of tape upon completion of wrapping. A minimum 1" overlap should be used. For severe environments, a 55% overlap is recommended.



# Densotherm Tape

## Property Specifications

PROPERTIES	ENGLISH	METRIC
Thickness (ASTM D1000)	79 mils	2.0 mm
Weight	.41 lbs/ft <sup>2</sup>	2.0 kg/m <sup>2</sup>
Breaking Strength (ASTM 1000)	51.4 lbf/in.	9 N/mm
Tear Strength (ASTM 1004)	11.2 lbf	50 N
Elongation @ Break	12%	12%
Adhesion Peel Strength (ASTM D1000)		
To Primed Steel	13.7 lbf/in.	2.4 N/mm
To Self	13.7 lbf/in.	2.4 N/mm
Impact Strength (ASTM G-14)	5.9 ft lb	8.0 Nm
Dielectric Strength	20 kV	20 kV
Maximum Service Temperature	176°F	80°C
Recommended Holiday Test Voltage		
Single Layer	10 kV	10 kV
Double Layer	14 kV	14 kV
Roll Widths	2" to 12"	50 to 300 mm
Roll Length	50 ft	15.24 m
Recommended Primer	Denso Primer D	

## Quantity Estimates

Tape Width	Rolls*/Case	Coverage with 1" Overlap	Coverage with 55% Overlap
2"	12	45 ft <sup>2</sup> /case	45 ft <sup>2</sup> /case
4"	6	75 ft <sup>2</sup> /case	45 ft <sup>2</sup> /case
6"	4	82 ft <sup>2</sup> /case	45 ft <sup>2</sup> /case
12"	2	90 ft <sup>2</sup> /case	45 ft <sup>2</sup> /case

\* All rolls are 50 feet in length.



**DENSO NORTH AMERICA**



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS  
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS  
FURSE EARTHING  
www.cablejoints.co.uk  
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371  
Tel 0044 117 977 4647 Fax 0044 117 9775582

**A Member of Winn & Coales International**

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.