




Bare Aluminium Tapes

Wallis bare aluminium tapes are used on lightning protection system applications. The aluminium is annealed for ease of use and has radiused edges.



Size W x H mm	C.S.A. mm ²	Weight per Metre kg	Standard Coil Size m	Part Number
12.5 x 1.5	18.75	0.05	50	TA 121
20 x 3	60	0.15		TA 203
25 x 3	75	0.21		TA 253
30 x 3	90	0.25		TA 303
25 x 6	150	0.42		TA 256
40 x 6	240	0.67		TA 406
50 x 6	300	0.85		TA 506


Material: Aluminium to BS2898.



PVC Covered Aluminium Tapes

Wallis PVC covered aluminium tapes are available in a choice of six standard colours to match the most common building materials and provide an aesthetic finish to the external lightning protection system. All PVC coverings are UV stabilised although some discolouration may occur over time.



Other PVC colours are also available to order. These may be subject to minimum order quantities and lead times. Please contact our sales office for further information.



Size W x H mm	Colour	C.S.A. mm ²	Weight per Metre kg	Standard Coil Size m	Part Number
12.5 x 1.5	Black	18.75	0.09	50	TAP 121 BL
20 x 3	Black	60	0.25	50	TAP 203 BL
25 x 3	Brown	75	0.30	50	TAP 253 B
	Black				TAP 253 BL
	Grey				TAP 253 G
	Green				TAP 253 GR
	Stone				TAP 253 S
	White				TAP 253 W

Material: Aluminium to BS 2898.

PVC colours to BS 5252 except green to BS 6746C.



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS



11KV 33KV CABLE JOINTS & CABLE TERMINATIONS

FURSE EARTHING

www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371

Tel 0044 117 977 4647 Fax 0044 117 9775582