



Stainless Steel Roll Springs



Roll springs provide a reliable method of solderless earthing in low and medium voltage heatshrink joint and termination systems.

The springs listed below are all standard stock items. We are happy to quote you for any alternative if full details are provided.

PART NUMBER	INNER DIA (mm)	WIDTH (mm)	LENGTH (mm)	APPLICATION RANGE (mm)
CF1	7.39	9.50	200	9-12
CF2	9.22	12.70	250	12-16
CF3	15.5	15.90	216	16-23
CF4	18.47	15.90	400	22-30
CF5	22.17	19.00	400	28-38
CF6	25.91	25.40	711	36-42
CF7	35.05	25.40	610	42-56
CF8	44.00	20.00	935	54-80

Earthing Components

A wide range of copper earth straps/socks are available from stock and can be cut to the required length. Solder blocks can be applied and braids can be insulated with heatshrink sleeving if desired.

PART NUMBER	DESCRIPTION	MAX LENGTH
FLTB 7.5	FLAT TINNED COPPER EARTH STRAP 7.5mm ² CSA	250 mtr
FLTB 16	FLAT TINNED COPPER EARTH STRAP 16mm ² CSA	250 mtr
FLTB 25	FLAT TINNED COPPER EARTH STRAP 25mm ² CSA	100 mtr
TCB 12.5	TUBULAR TINNED COPPER EARTH SOCK 7.5mm ² CSA	100 mtr
TCB 25	TUBULAR COPPER EARTH SOCK 25mm ID BY 16mm ² CSA	25 mtr
TCB 50	TUBULAR COPPER EARTH SOCK 50mm ID BY 25mm ² CSA	20 mtr
KM 50	TINNED COPPER SCREENING BANDAGE 50mm WIDTH	5 mtr

