

PRODUCT DATASHEET

Prolab® Thermal Wrap-around Cable Labels



One Software
One Printer
One Ribbon

This is a multipage document, all pages must be read in conjunction with each other



Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk



The Silver Fox Prolab® thermal wrap-around cable labels are self-laminating and printed in conjunction with our DTP-1/300 thermal printer.

The labels incorporate a highly opaque printable area ensuring excellent levels of clarity for your message whatever the colour of the cable.

The clear 'tail' on the label wraps around the cable and the printable area giving additional protection to the message printed.

Print up to 100 labels in 30 seconds!

TECHNICAL DATA

Printing Method	Silver Fox DTP-1 Thermal Printer
Thermal Ribbon	Silver Fox TSR3/300/110
Material	Self-adhesive Polyethylene
Thickness	105 microns
Standard Colours	White
RoHS (EU 2002/95/EC)	RoHS Compliant

PRODUCT TESTING

Test	Method
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4
High Temperature 2000 hours @ 70°C to 100°C*	MIL-STD-202G Method 108A
Hydrogen Sulphide	H ₂ S Sour Gas Exposure (2% H ₂ S)
UV Weathering 500 hours**	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

* Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C

** Limited external applications generally away from direct sunlight. Labels generally for internal use such as, data centres, banks, hotels, airports etc.

FEATURES & BENEFITS

- Pre-cut for rapid removal from roll
- Wide choice of sizes, fit cable
OD Ø 5mm - 8mm
- Self-laminating for additional protection

Print using our DTP – 1/300 Thermal Printer.



PRODUCT DATASHEET

Prolab® Thermal Wrap-around Cable Labels



One Software
One Printer
One Ribbon

This is a multipage document, all pages must be read in conjunction with each other



Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk

STORAGE INSTRUCTIONS

Storage Instructions	Store between 50° F (10° C) and 77° F (25° C)
Shelf Life	2 Years
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH


HOW TO APPLY LABELS

STEP 1



After printing, place the printed area on the cable

STEP 2



Wrap the clear tail over the printed area

STEP 3




Continue to wrap the tail around the cable

ORDER INFORMATION


Product Code	Cable OD Ø (mm)	Printable Area (mm)	Labels / Roll	Rolls / Pack	Labels / Pack	Colour Options
PSA1/07/2512T	5 - 7	25 x 12	7000	1 Roll	7000	<input type="checkbox"/>
PSA1/08/2519T	5 - 8	25 x 19	5000	1 Roll	5000	<input type="checkbox"/>
PSA1/08/2524T	5 - 8	25 x 24	5000	1 Roll	5000	<input type="checkbox"/>

Use with Silver Fox Labacus Innovator Advanced or Professional software.
Print in conjunction with our Fox-in-a-Box Plug'N'Play thermal printer using the same ribbon as all our other thermal labels.

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE



Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.