## fortress single door



Tel: +44 (0)191 490 1547 Fax: +44 (0)191 477 5371

Email: northernsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneanderrick.co.uk

The Fortress Single Door pillars are available in 6 sizes in both mild and stainless steel. Mild steel variants can be obtained in two panel thicknesses with a choice of a hot dip galvanised finish or hot dip galvanising followed by paint.



When ordering stainless steel versions, the customer is free to specify the grade and finish required. Further options can be selected from the list overleaf and should be specified at the time of order.

#### **Specification**

Long life solid stainless steel hinge blocks on all versions Vandal resistant fully flush hinges

Two tri-head locks fitted as standard

Backboard made from 18mm treated exterior grade plywood

Detachable roof

'Danger' warning label fitted in door recess Detachable root section finished in bitumen enriched paint

Earth lead between pillar body and door

High quality UV resistant paint to an average thickness of 60 microns

Door seal to IP65

### **Options**

Customer specification pre-wired solutions available

Other colours / labels available to special order

Optional G2A Highways Agency paint specification

www.lucyzodion.com



Tel: +44 (0)191 490 1547 Fax: +44 (0)191 477 5371

Email: northernsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneanderrick.co.uk

# fortress single door

selection chart

### Dimensions (mm)

Pillar size code	05	06	08	09	10	12
Height (H) above ground	791	636	836	1088	1194	1294
Root Section (R)	350	300	300	350	350	350
Width (W)	310	400	600	661	800	1100
Depth (D)	220	180	250	281	350	400
Door Opening Height (DH)	585	410	610	860	907	1007
Door Opening Width (DW)	200	300	500	550	700	1000
Working Depth (WD)	170	155	225	225	325	375
Backboard Size (WxH)	650x300	390x475	590x675	640x930	790x975	1080x1075
Weight (Kg) (3mm thickness)	36	42.5	71.5	84	108	142

4

### The ordering code consists of 4 sections



