

General Purpose - power (not ENATS compliant)

General purpose ducting

General Purpose PVCu duct and fittings are a cost-effective alternative to higher specification systems for use in light and medium duty applications. The products are manufactured to traditionally accepted dimensions but do not meet the requirements of BS EN 61386-24: 2010. General Purpose Ducting is not suitable for Highways Agency applications and will require a better standard of installation than more robust systems for successful performance. All ducts include an integral socket and accessories include bends, junctions and end caps.



General Purpose Ducting					
Dia. inches	Dia. mm	Wall Thickness mm	Length m	Code	Pack Qty
2	54	1.5-1.7	6	GP2X6B	400
3	88.9	1.8-2.2	6	GP3X6B	144
4	114	1.8-2.1	6	GP4X6B	86
6	168	2.2-2.9	6	GP6X6B	36
8	200	3.2-3.6	6	GP8X6B	25

General purpose ducting lengths include integral socket.
Please note this product comes in colour grey to black for both pipe and fittings.

General Purpose Bends				
Dia. inches	Dia. mm	Bend Radius	Code	Pack Qty
2	54	225	GPB2X11 ▲	60
2	54	225	GPB2X22 ▲	60
2	54	225	GPB2X45	60
2	54	225	GPB2X90	50
3	89	350	GPB3X11 ▲	25
3	89	350	GPB3X22 ▲	25
3	89	350	GPB3X45	15
3	89	350	GPB3X90	10
4	114	460	GPB4X11 ▲	10
4	114	460	GPB4X22 ▲	10
4	114	460	GPB4X45	10
4	114	460	GPB4X90	7
6	168	610	GPB6X11 ▲	3
6	168	610	GPB6X22 ▲	3
6	168	610	GPB6X45	3
6	168	610	GPB6X90	3
8	200	900	GPB8X11 ▲	1
8	200	900	GPB8X22 ▲	1
8	200	900	GPB8X45	1
8	200	900	GPB8X90	1

▲ Made to order and subject to lead times.
Please note this product comes in colour grey to black for both pipe and fittings.

General Purpose Hockey Sticks, Junctions, End Caps			
Dia (inches)	Dia (mm)	Code	Pack Qty
Hockey Sticks			
2"	54	GPHS2 ▲	25
Connectors			
2"	54	GPC2	10
3"	89	GPC3	60
4"	114	GPC4	40
6"	168	GPC6	15
8"	206	GPC8	1
90° Junctions			
2"	54	GPJY2X90 ▲	1
3"	89	GPJY3X90 ▲	1
4"	114	GPJY4X90 ▲	1
6"	168	GPJY6X90 ▲	1
8"	206	GPJY8X90 ▲	1
45° Junctions			
2"	54	GPJY2X45 ▲	1
3"	89	GPJY3X45 ▲	1
4"	114	GPJY4X45 ▲	1
6"	168	GPJY6X45 ▲	1
8"	206	GPJY8X45 ▲	1
End Caps			
2"	54	GPEC2	10
3"	89	GPEC3	10
4"	114	GPEC4	10
6"	168	GPEC6	10
8"	206	GPEC8	10

▲ Made to order and subject to lead times.

Suretwin

Suretwin is a non-certified twin wall system which provides a cost-effective alternative to conventional systems where a BBA or ENATS duct is not required. The Suretwin system is currently available in 150mm diameter and meets the stiffness and normal duty impact requirements of BS EN 61386-24:Type 450 only.

Suretwin				
ID mm	OD mm	Length m	Code	Pack Qty
150	178	6	GPT150X6B	36

