



Heat Shrink Terminations for use on XLPE and Paper Cables 1.9/3.6kV

In conditions of high humidity, chemical and dust contamination, it is recommended that red anti-track materials are used for extra reliability and long term service.



Single Core PILC / XLPE Indoor / Outdoor Type		
Part Number	Cable Range	Tail Length
1TIS-3.6A	25-70mm ²	300mm
1TIS-3.6B	95-300mm ²	300mm
1TIS-3.6C	400-630mm ²	300mm

3 Core PILC / XLPE Indoor / Outdoor Type		
Part Number	Cable Range	Tail Length
3TIS-3.6A	25-70mm ²	600mm
3TIS-3.6B	95-185mm ²	600mm
3TIS-3.6C	240-400mm ²	600mm



Heat Shrink Terminations for LV PILC Cables 0.6/1kV

3/4 Core PILC Termination		
Part Number	Cable Range	Tail Length
SPS 4-35-600-3	4-35mm ²	600mm
SPS 4-35-1000-3	4-35mm ²	1000mm
SPS 50-150-600-3	50-150mm ²	600mm
SPS 50-150-1000-3	50-150mm ²	1000mm
SPS 185-300-600-3	185-300mm ²	600mm
SPS 185-300-1000-3	185-300mm ²	1000mm

Table above lists part number for 3 core kits, if 4 core, last digit should read - 4

Example: SPS 50-150-600-4

Note: Picture shows outdoor earthing components. If indoor type, the gland kit selected normally takes care of the earthing requirements.

