

CONDUCTORS

Conductors - Bare Aluminium Tape

CODE	CONDUCTOR SIZE (mm)	COIL SIZE (m)	MATERIAL	WEIGHT (Kg/m)
ATBA12515	12.5 x 1.5	50	ALUMINIUM	0.05
ATBA2030	20 x 3	50	ALUMINIUM	0.17
ATBA2530	25 x 3	50	ALUMINIUM	0.21
ATBA3030	30 x 3	50	ALUMINIUM	0.25
ATBA2560	25 x 6	50	ALUMINIUM	0.42
ATBA4060	40 x 6	50	ALUMINIUM	0.67
ATBA5060	50 x 6	50	ALUMINIUM	0.85



☐ BS 2898-1350.

Conductors - PVC Sheathed Aluminium

CODE	CONDUCTOR SIZE (mm)	COIL SIZE (m)	COLOUR	WEIGHT (Kg/m)
TABL12515	12.5 x 1.5	50	BLACK	0.09
TABL2030	20 x 3	50	BLACK	0.25
TABL253	25 x 3	50	BLACK	0.31
TABN253	25 x 3	50	BROWN	0.31
TAGN253	25 x 3	50	GREEN	0.31
TAGY253	25 x 3	50	GREY	0.31
TAST253	25 x 3	50	STONE	0.31
TAWH253	25 x 3	50	WHITE	0.31



- ☐ Kingsmill Aluminium is manufactured to British Standard BS2898 - Grade 1350.
- ☐ Kingsmill PVC Sheathing is manufactured to BS 5252 except Green PVC which is manufactured to BS6746.

**FOR TECHNICAL ADVICE, RECOMMENDATIONS, ADDITIONAL
SPECIFICATIONS AND CUSTOM PRODUCTS, CALL OUR TECHNICAL
SALES TEAM ON**

T&D
down to earth service

WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK