



LFHU system galvanised steel LFH coated



FPU system galvanised steel polyurethane coated



Conduit

LFHU

Construction: Galvanised steel, helically wound, flexible steel conduit with Low Fire Hazard (LFH) coating. Colour black.

Typical Applications: Public and commercial buildings and tunnels.

FPU

Construction: Galvanised steel, helically wound, flexible steel conduit with low temperature, high abrasion, high fatigue life halogen free polyurethane coating. Colour black and metallic blue.

Typical Applications: Where low temperature and mechanical strength are important.

Fittings

M

fixed external thread nickel plated brass

Two part fitting comprising shell and body with external thread. This fitting can be inserted into a knockout and secured with a locknut.

IP54

S

swivel external thread nickel plated brass

Two part fitting comprising shell and body. The external thread swivels about the main body. Can be used with threaded entries, or knockout secured with a locknut.

IP54

P

plain hole connector nickel plated brass

Two part fitting comprising shell and body without thread. The body is fitted through the opposite side of the entry to the conduit and acts as a locking device also providing a smooth entry bush.

IP54



Tel: +44 (0)191 490 1547
 Fax: +44 (0)191 477 5371
 Email: northernsales@thorneandderrick.co.uk
 Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk



nominal size (mm)	LFHU part number	reel length (m)	FPU part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)
12	LFHU12B*	25	FPU12B*	25	14.0	10.2	30
16	LFHU16B	25, 50	FPU16B	25	17.0	13.0	40
16							
20	LFHU20B	10, 25, 50	FPU20B	25, 50	21.5	16.9	45
25	LFHU25B	10, 25, 50	FPU25B	25, 50	26.0	21.1	55
32	LFHU32B	10, 25	FPU32B	25	34.0	28.1	80
40	LFHU40B	10, 25	FPU40B*	10	44.5	37.6	90
50	LFHU50B	10, 25	FPU50B*	10	55.0	48.4	100
63	LFHU63B	10	FPU63B*	10	64.5	57.5	115
75	LFHU75B	10	FPU75B*	10	79.0	70.0	150

metric thread part number	PG thread part number	metric thread part number	PG thread part number	hole size (mm)	part number
FSU12-M16-M	FSU12-PG9-M	FSU12-M16-S	FSU12-PG9-S	12	FSU12-P
FSU16-M16-M	FSU16-PG11-M	FSU16-M16-S	FSU16-PG11-S	16	FSU16-P
FSU16-M20-M		FSU16-M20-S	FSU16-PG13-S		
FSU20-M20-M	FSU20-PG16-M	FSU20-M20-S	FSU20-PG16-S	20	FSU20-P
FSU25-M25-M	FSU25-PG21-M	FSU25-M25-S	FSU25-PG21-S	25	FSU25-P
FSU32-M32-M	FSU32-PG29-M	FSU32-M32-S	FSU32-PG29-S	32	FSU32-P
FSU40-M40-M	FSU40-PG36-M	FSU40-M40-S	FSU40-PG36-S	40	FSU40-P
FSU50-M50-M	FSU50-PG48-M	FSU50-M50-S	FSU50-PG42-S	51	FSU50-P
FSU63-M63-M		FSU63-M63-S		61	FSU63-P
FSU75-M75-M				75	FSU75-P

Ordering Notes

Important Note

- For LFH performance see page 102

- Add reel length eg: LFHU20B-25M for 25m reel
- FSU fittings used on LFHU conduit
- For metallic blue change B to BU eg FPU20BU-25M
- * Indicates parts made to order on request and may be subject to MOQ and lead time



- Available on request:**
 - longer lengths and bulk packaging
 - cut lengths and assemblies additional sizes
 - stainless steel fittings (grade 316)
 - alternative threads
 - 45° C type elbows 16 to 32mm

How to read the fittings code

