

**FSB system** galvanised steel core, pvc coated, galvanised steel overbraid



**LFHUBRD system** galvanised steel core, extra LFH coated, stainless steel overbraid



Conduit

Fittings

**FSB**

**Construction:** Galvanised steel, helically wound, flexible conduit with pvc coating and galvanised steel overbraid. Colour zinc, self colour.

**Typical Applications:** Industrial environments where higher abrasion resistance or screening are required.

**LFHUBRD**

**Construction:** Galvanised steel, helically wound, flexible conduit with extra LFH coating and stainless steel (316) overbraid.

**Typical Applications:** Metro rail stations where LFH, EMC screening and anti-vandal properties are required. Compliant to LUL std 1-085 (Cert No.297).

**M**

**fixed external thread nickel plated brass**

Two part fitting comprising of shell and body with external thread. This fitting can be inserted into a knockout and secured with a locknut.

IP54

**S**

**swivel external thread nickel plated brass**

Two part fitting comprising of shell and body. The external thread swivels about the main body. Can be used with threaded entries, or knockout secured with a locknut.

IP54



Tel: +44 (0)191 490 1547  
 Fax: +44 (0)191 477 5371  
 Email: [northersales@thorneandderrick.co.uk](mailto:northersales@thorneandderrick.co.uk)  
 Website: [www.cablejoints.co.uk](http://www.cablejoints.co.uk)  
[www.thorneandderrick.co.uk](http://www.thorneandderrick.co.uk)




nominal size (mm)	FSB part number		real length (m)	outside dia (mm)	inside dia (mm)	min. inside bend radius (mm)	metric thread part number		PG thread part number	
	FSB	LFHUBRD					metric thread part number	PG thread part number	metric thread part number	PG thread part number
12	FSB12		25	15.2	10.2	30	FSB12-M16-M	FSB12-PG9-M	FSB12-M16-S	FSB12-PG9-S
16	FSB16		25	18.2	13.0	40	FSB16-M16-M	FSB16-PG11-M	FSB16-M16-S	FSB16-PG11-S
16							FSB16-M20-M		FSB16-M20-S	
20	FSB20	LFHUBRD20	25	22.7	16.9	45	FSB20-M20-M	FSB20-PG16-M	FSB20-M20-S	FSB20-PG16-S
25	FSB25	LFHUBRD25	25	27.2	21.1	55	FSB25-M25-M	FSB25-PG21-M	FSB25-M25-S	FSB25-PG21-S
32	FSB32	LFHUBRD32	25	35.2	28.1	70	FSB32-M32-M	FSB32-PG29-M	FSB32-M32-S	FSB32-PG29-S
40	FSB40	LFHUBRD40	10	45.7	37.6	80	FSB40-M40-M	FSB40-PG36-M	FSB40-M40-S	FSB40-PG36-S
50	FSB50		10	57.7	48.4	90	FSB50-M50-M	FSB50-PG48-M	FSB50-M50-S	FSB50-PG42-S

Ordering Notes

- Add reel length eg: FSB20-25M for 25m reel
- Available on request:
  - longer lengths, cut lengths and assemblies
  - additional sizes, stainless steel overbraided
  - PG threads, female threaded fittings
  - full copies of independent test report confirming screening effectiveness

How to read the fittings code



Standards



BS EN IEC 61386



Note: refer to conduit properties for applicable standards