

D Type - Double Eye

Ideal for pulling medium to heavy loads; the main advantage over the single eye cablegrip is, since the cable being pulled can be passed through the grip, several cables can be used to support over a calculated distance.

SLINGCO PART NO.	CABLE DIA	TYPE	LATTICE WEAVE	LATTICE LENGTH	OVERALL LENGTH	APPROX BREAKING STRENGTH (lb)
ZCS0305	ins mm	0.38-0.50" 10-13	D1	Single 9" 230	12" 305	1,680
ZCS0306	ins mm	0.50-0.75" 13-19	D2	Single 14" 355	17" 430	2,240
ZCS0307	ins mm	0.75-1.0" 19-25	D3	Single 16" 405	20" 510	5,600
ZCS0308	ins mm	1.0-1.5" 25-38	D4	Single 18" 455	24" 610	7,840
ZCS0309	ins mm	1.5-2.0" 38-50	D5	Double 21" 535	29" 735	11,200
ZCS0310	ins mm	2.0-2.5" 50-63	D6	Double 24" 610	34" 865	11,200
ZCS0311	ins mm	2.5-3.5" 63-89	D7	Double 27" 685	39" 990	13,440
ZCS0312	ins mm	3.5-4.5" 89-115	D8	Double 27" 685	39" 990	15,680



L Type - Lace Up

Ideal for pulling medium to heavy loads; the L-type is fitted to the cable being pulled by stitching it together, like a football. Mainly used where a 'typical' cablegrip cannot be fitted over a connector at the end of a cable.

SLINGCO PART NO.	CABLE DIA	TYPE	LATTICE WEAVE	LATTICE LENGTH	OVERALL LENGTH	APPROX BREAKING STRENGTH (lb)
ZCS1157	ins mm	0.38-0.50" 10-13	L1	Single 9" 230	12" 305	1,680
ZCS0872	ins mm	0.50-0.75" 13-19	L2	Single 14" 355	17" 430	2,240
ZCS0871	ins mm	0.75-1.0" 19-25	L3	Single 16" 405	20" 510	5,600
ZCS0328	ins mm	1.0-1.5" 25-38	L4	Single 18" 455	24" 610	7,840
ZCS0329	ins mm	1.5-2.0" 38-50	L5	Double 21" 535	29" 735	11,200
ZCS0330	ins mm	2.0-2.5" 50-63	L6	Double 24" 610	34" 865	11,200
ZCS0331	ins mm	2.5-3.5" 63-89	L7	Double 27" 685	39" 990	13,440
ZCS0853	ins mm	3.5-4.5" 89-115	L8	Double 27" 685	39" 990	15,680



O Type - Open Ended

Ideal for joining two cables to form a continuous loop. Typical application: replacement of elevator cables, where the old cable would be attached to the new one, and the cable then fed round with ease.

SLINGCO PART NO.	CABLE DIA	TYPE	LATTICE WEAVE	LATTICE LENGTH	APPROX BREAKING STRENGTH (lb)
ZCS0313	ins mm	0.38-0.50" 10-13	O1	Single 15" 380	1,680
ZCS0314	ins mm	0.50-0.75" 13-19	O2	Single 24" 610	2,240
ZCS0315	ins mm	0.75-1.0" 19-25	O3	Single 28" 710	5,600
ZCS0316	ins mm	1.0-1.5" 25-38	O4	Single 32" 815	7,840
ZCS0317	ins mm	1.5-2.0" 38-50	O5	Double 36" 915	11,200
ZCS0318	ins mm	2.0-2.5" 50-63	O6	Double 42" 1065	11,200
ZCS1158	ins mm	2.5-3.5" 63-89	O7	Double 48" 1220	13,440
ZCS1159	ins mm	3.5-4.5" 89-115	O8	Double 54" 1370	15,680

