

**LOW VOLTAGE MINIATURE FUSE-LINKS**

**TYPE MIN**

**200/240 Volt miniature Fuse-Links generally to IEC127**

Rated voltage: 250V a.c. Rated breaking capacity: Various.

**Current ratings and principal dimensions**

DIMENSION MM	OPERATING CHARACTERISTIC	BODY MATERIAL	TYPE REF	RATING		FUSE- HOLDER TYPE	CARTON QUANTITY
				mA	AMPS		
5 X 20	FAST	GLASS	PDC	32, 40, 50, 63, 80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10, 15	KP	100 (10x10)
		CERAMIC	PCC	32, 40, 50, 63, 80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
	SLOW	GLASS	PDC-S	32, 40, 50, 63, 80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		CERAMIC	PCC-S	125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
	ULTRAFAST		PCC-UR		1.6, 2, 3, 15, 4, 5, 8, 10		
6.3 X 32	FAST	GLASS	KDC	10, 32, 40, 63, 100, 125, 150, 175, 187, 200, 250, 300, 375, 500, 600, 750	1, 1.25, 1.5, 1.6, 2, 2.5, 3, 4, 5, 6, 7, 8, 10	K	100 (10x10)
		CERAMIC	KCC	125, 250, 375, 500, 750	1, 2, 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30		
	SLOW	GLASS	KDC-S	10, 32, 40, 63, 100, 125, 150, 175, 187, 200, 250, 300, 375, 400, 500, 600, 700, 750, 800	5, 6, 7, 8, 20, 25, 30		
		CERAMIC	KCC-S	10, 32, 63, 100, 125, 150, 175, 187, 200, 250, 300, 375, 400, 500, 600, 700, 750, 800	1, 1.25, 1.5, 1.6, 2, 2.5, 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30		
			KCC-UR		1, 1.25, 2, 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30		
5 X 25	FAST	GLASS	TDC	80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		CERAMIC C/W INDICATOR	TCC		1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		GLASS	TDC-M	80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		CERAMIC C/W INDICATOR	TCC-M	80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10,		



Lawson Type "MIN" fuse-links are available to meet a wide variety of applications. Miniature and other small dimensioned fuse-links are grouped into several different application categories and comply with different specifications. Many different types are available with current ratings from 10mA to 30 Amps.



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS  
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS  
FURSE EARTHING  
www.cablejoints.co.uk  
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371  
Tel 0044 117 977 4647 Fax 0044 117 9775582