



Designed, manufactured and tested in accordance with BS7654:1997.

The latest Single Pole Street Lighting Cut-out from Lucy Lighting has been redesigned in a high grade, high performance thermoplastic. Its new low body line split increases cable access. By incorporating retained fixing screws, this allows for reduced installation time. It also has a redesigned cam operated lever mechanism with zero extraction force. Operating cam lever ensures electrical disconnection prior to removal of fuse carrier, thus giving additional safety features.

There are two versions available, separate, neutral and earth (SNE) and combined neutral/earth (CNE) for PME applications.



Order Details
Max rating 25A
Dimensions

Height 150mm Width 76mm Depth 61mm

Order Code	Description
MC040SLF 25A SLCO TYPE 1 (SNE)	Fuseway separate, neutral and earth
MC040SLF 25A SLCO TYPE 2 (CNE)	Combined, neutral and earth
LST Fuse	State rating

Specification

- Designed, manufactured and tested in accordance with BS7654:1997
- Accepts fuse links to BS 88 Part 1,
 AC16 Tag Type
- Single Pole isolation
 - Single fuse
 - All terminals are formed from solid brass, serrated and electroplated
- Maximum cable of 16mm² stranded copper or 25mm² solid aluminium conductors
- Cable entry via PVC grommets as standard
- Outgoing cables exit below horizontal to form drip loop
- Sealing wire facility



WWW.CABLEJOINTS.CO.UK THORNE & DERRICK UK TEL 0044 191 490 1547 FAX 0044 477 5371 TEL 0044 117 977 4647 FAX 0044 977 5582 WWW.THORNEANDDERRICK.CO.UK