

## Indoor LV Distribution Board



### Fully Shielded Low Voltage 415 Volts Distribution Board

#### Design Features

- Designed for indoor floor or wall-mounting conforming to ENATS 37.2.
- Up to 12 outgoing ways.
- 800 amp or 1600 amp main busbar rating.
- 800 amp or 1600 amp 3 phase 4 wire pole operated incoming 'off-load' isolator.
- 630 amp rated triple pole outgoing circuits with provision for BS88 JS type 92mm fuse links as per ENATS 37.2.
- 800 amp or 1600 amp 3 phase 'off-load' outgoing isolator circuit.
- Metering available to suit customer's specification.
- Fully shielded internally to IPXXB.
- Tested in accordance with ENATS 37.2.



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS  
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS  
FURSE EARTHING  
www.cablejoints.co.uk  
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371  
Tel 0044 117 977 4647 Fax 0044 117 9775582