

**MULTI**

DXN37C METAL MULTI-CONTACT CONNECTORS

**10 A
IP66/IP67****TYPICAL CONFIGURATION**

MAIN FEATURES

Rated current (with wiring according to standard)	10 A	Ambient temperature	-40 °C to +55 °C
Maximum voltage	230 V	Flexible wiring (min-max)	1 - 2,5 mm ²
Number of contacts	36P+E	Wiring	crimping
IP protection lid closed	IP66/IP67	Protection mode	e + i
IP protection connected plug	IP66/IP67	ATEX zones	1 & 2, 21 & 22
Shock resistance	IK09	Keying positions	3

LOCKING POSITION CONNECTED OR DISCONNECTED BY LOCKABLE SHAFT.

WALL MOUNTING SOCKET female DNX37c (10 A)



PLUG male DNX37c (10 A)



Ex cable gland	Part no.		Ex cable gland	Part no.
M32	36C000332M	12-21 mm	M32	36C100332M 12-21 mm
M40	36C0003	16-27 mm	M40	36C1003 16-27 mm

With padlocking shaft (padlock not included)

INCLINED SOCKET female DNX37c (10 A)



INCLINED APPLIANCE INLET male DNX37c (10 A)



Part no.	Part no.
36C7003	36C9003

With padlocking shaft (padlock not included)

ACCESSORIES & OPTIONS

Crimping tool	61CA500
Helavia sleeve expansion tool	61CA400

COUPLER SOCKET female DNX37c (10 A)



WALL MOUNTING APPLIANCE INLET male DNX37c (10 A)



Ex cable gland	Part no.		Ex cable gland	Part no.
M32	36C300332M	12-21 mm	M32	36C600332M 12-21 mm
M40	36C3003	16-27 mm	M40	36C6003 16-27 mm

With padlocking shaft (padlock not included)

Each product is supplied with 3 bags of 13 contacts depending on the maximum configuration. This allows you to set up the product to suit your needs.

BAG OF 13 CONTACTS (SUPPLIED WITH INSULATION SLEEVES AND FERRULES)

Female socket-outlet Part Number	01AA213
Male inlet Part Number	61CA113

MARECHAL ELECTRIC MAROMME

I12 G D Ex e IIC Gbtb IIIC Db
 -40 °C ≤ Ta ≤ +40 °C T6 T56 °C
 -40 °C ≤ Ta ≤ +55 °C T5 T76 °C
 Ex ia und ib IIC T6 Gb

T&D THORNE & DERRICK UK

Tel: +44 (0)191 490 1547
 Fax: +44 (0)191 477 5371
 Email: northersales@thorneandderrick.co.uk
 Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk