



11KV 33KVCABLE JOINTS & CABLETERMINATIONS FURSE EARTHING www.cablejoints.co.uk Thorne and Derrick UK

## Cable Clamp - Metro LSF216-MR-V1 series With single channelled connector base & locking zip-strap




## The Metro LSF216-MR-V1 Cable Clamp

specifically designed to exceed the critical safetv requirements of London Underground Ltd and to provide a secure, reliable fixing cable method in the most demanding, hostile and hazardous environments.



- London Underground 'Fire Safety Performance of Materials' compliant - Standard Ref. Number 1-085 (formerly Ref. 2-01001-002)
- Fast, efficient & simple 'Push-On' installation when used with the LUL 'J' Hanger cable support system
- Serviceable -40 to +323°C
- Strong durable construction
- No 'burrs' to snag or damage cables
- 40 Year effective life
- Less than 0.1% water absorption
- Suitable for use with LS0H cable (Low Smoke Zero Halogen)
- Enables the unrestricted path of radio signal (RF) cable propagation signalling systems
- Standard size product accepts cable diameters of between 13 - 50mm



## Material:

- High Strength smooth surface thermoplastic resin
- Excellent electrical and thermal insulator with high dielectric strength and arc quenching
- Corrosion free stable not subject to attack by weather, chemical or biological agents
- Dimensionally stable material with no directional 'grain' weakness

## **Product:**

- Manufactured to tight tolerances
- Standard product colouring in Grey / Black other colours available to special order