



MELCROFT



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS

FURSE EARTHING

www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 480 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4547 Fax 0044 117 977 5582

Cable Clamp - 'Twist & Lock' Metro Self-Locking LSF 50/55 S series For use with GRP / metal framing channel systems (Strut), slotted cable tray or for direct fixing to substrate surface



Supplied with optional 'slot' adaptors to enable mounting directly to 'strut' type GRP / metal framing systems & slotted cable tray; or direct fixing to the substrate surface by expansion bolt or chemical anchor bolt fixings

- ◆ London Underground Compliant
- ◆ New York City Transit approved
- ◆ Easy to use
- ◆ Simple 'Twist & Lock' installation on GRP / metal framing channel systems and slotted cable tray **or** Bolt-on / 'Chemical Anchor Bolt' installation
- ◆ Serviceable -40 to +323°C
- ◆ Strong, durable construction
- ◆ Standard size product accepts cable diameters of between 7.5 - 24.0mm
- ◆ No 'burrs' to snag or damage cables
- ◆ 40 Year effective life
- ◆ Suitable for use with LSOH cable (Low Smoke Zero Halogen)
- ◆ Enables the unrestricted path of radio signal (RF) cable propagation signalling systems



Heathrow Express
London - UK

Material:

- High Strength smooth surface LSOH thermoplastic resin
- Excellent electrical and thermal insulator with high dielectric strength and arc quenching
- Corrosion free stable - not subject to attack by weather, chemical or biological agents
- Dimensionally stable material with no directional 'grain' weakness

Product:

- Manufactured to tight tolerances
- Complies with The London Underground Limited Engineering Standard **"Fire safety performance of materials"** standard - Document Reference No. 1-085

Please 'Contact Us' for details of our LSOH range of GRP 'strut' framing channel & Cable trays