## **Multiple Lockout Device**



Only one device needed to perform a variety of lockout functions:

- Rugged stainless steel/nylon construction offers great durability, strength, added security and corrosion resistance
- · Compact and easy to install
- One six foot vinyl coated galvanized steel cable with loophole included with every lockout!

Part Number	Description	Std. Pkg.*
PSL-MLD	Multiple Lockout Device; includes lockout hasp and cable	1
PSL-MLDC	6 ft. (1.8 m) vinyl coated galvanized steel cable with loophole, 0.19" (4.8 mm) diameter. Combine several cables to extend cable length.	1
PSL-MLDC200	200 ft. (61.0 m) vinyl coated galvanized steel cable on roll, no loophole, 0.19" (4.8 mm) diameter	1
PSL-MLDH-X	PSL-MLD Lockout Hasps without cable	10

Lockout Single or Multiple Disconnects



**Lockout Gate Valve Device** 



Immobilize Large or Cumbersome Devices




## **Plug Lockout**




Prevents a plug from being plugged in.

- Lockout device for a wide range of plug connector applications (see page 8 for other plug types)
- Requires a hole in a blade of the plug
- Should be used with locks that have a minimum shackle length of 1.5" (38 mm)

Part Number	Description	Std. Pkg.*
PSL-P	Plug Lockout	1



Place PSL-P Lockout through the hole in blade of plug.



Insert padlock shackle through both holes in the lockout and lock padlock.



Verify that lockout cannot be removed from plug and that plug blades cannot be inserted into a receptacle. Add safety tag.

