



Section

MV Outer sheath

Application

Field
Laboratory
Production



PRODUCT BENEFITS

Quick, light and easy to use

TOOL CAPACITY

Diameter 21 - 35 mm
0,827 - 1,378 inch

Circular cutting thickness capacity 2,8 mm / 0,110 in

Longitudinal cutting thickness capacity 2,8 mm / 0,110 in

TOOL DIMENSIONS

Length 240 mm

Width 85 mm

Height 80 mm

Weight without box 0,5 Kg

Packaging None

Pliers for MV cable outer sheath

TO DO WHAT

The PG2HTA/2828 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

All cutting depth ranging from 0,5 mm / 0,019 in to 5 mm / 0,196 in are available on demand
How to built your customized pliers : PG3HTA/yyzz
yy = Circular cutting depth e.g : 28 = 2,8 mm / 0,110 in
zz = Longitudinal cutting depth e.g : 33 = 3,3 mm / 0,129 in

Options

PG3MB/2833 - Locking lever
SGM - Large size pouch

Spare part

MTL2/28 - Sapre blade for longitudinal cutting
MTC2/28 - Sapre blade for circular cutting

Associated tool

MF1+/25 - Multifunction tool for bonded semiconductor
MF2/40 - Multifonction tool for outer sheath and insulation



MV cables Tools

PG2HTA/2828



| Part Number | Diameter | Tool capacity | | Dimensions | | | Packaging |
|--------------------|--------------------------------|-------------------------------------|---|---------------------|--------------------|--------------------|-----------|
| | | Circular cutting thickness capacity | Longitudinal cutting thickness capacity | Length | Width | Height | |
| PG2HTA/2828 | 21 - 35 mm 0,827 - 1,378 in | 2,8 mm / 0,110 in | 2,8 mm / 0,110 in | 240 mm 9,449 in | 85 mm 3,346 in | 80 mm 3,150 in | none |
| PG3HTA/2530 | 26 - 52 mm 1,024 - 2,047 in | 2,5 mm / 0,098 in | 3,0 mm / 0,118 in | 265 mm 10,433 in | 95 mm 3,740 in | 80 mm 3,150 in | none |
| PG3HTA/2828 | 21 - 35 mm 0,827 - 1,378 in | 2,8 mm / 0,110 in | 2,8 mm / 0,110 in | 240 mm 9,449 in | 85 mm 3,346 in | 80 mm 3,150 in | none |
| PG3HTA/2833 | 26 - 52 mm 1,024 - 2,047 in | 2,8 mm / 0,110 in | 3,3 mm / 0,139 in | 265 mm 10,433 in | 95 mm 3,740 in | 80 mm 3,150 in | none |
| PG4HTA/3033 | 47 - 75 mm 1,850 - 2,953 in | 3,0 mm / 0,118 in | 3,3 mm / 0,129 in | 300 mm 11,811 in | 110 mm 4,331 in | 105 mm 4,134 in | none |