

Ridgiduct Power HV Trefoil Accessories			
Description	Diameter mm	Colour	Product Code
Trefoil Clip	100	Black	RBTC100
	125	Black	RBTC125
	150	Black	RBTC150

Trefoil clip



Key Features

- Suitable for use with both Ridgiduct and bends
- Supports duct arrangement during installation and burial
- Ensures consistent spacing of duct lengths and bends

PVCu Duct

PVCu Duct				
Nominal wall thickness mm	ID mm	Length m	Colour	Code
UNSEALED				
4.1	100	6	Black	SD7110X6BNS ▲
4.4	117	6	Black	SD7125X6BNS ▲
5.2	150	6	Black	SD7160X6BNS ▲
4.1	100	6	Red	SD7110X6RNS ▲
4.4	117	6	Red	SD7125X6RNS ▲
5.2	150	6	Red	SD7160X6RNS ▲
SEALED				
4.1	100	6	Black	SD7110X6BSPE UG402B ▲
5.2	150	6	Black	SD7160X6BSPE UG402B ▲
4.1	100	6	Red	SD7110X6RSPE UG404B ▲
5.2	150	6	Red	SD7160X6RNS UG402B ▲

All sizes are available in PVCu.

Bend radius information required at quote.
▲ Made to order and subject to lead times.



ENATS
(12-24)

Key Benefits

- Complies with ENATS 12-24 Class 1 specification
- Complies with BS EN 61386-24
- Full range of fittings available
- Used for high voltage applications
- Can also be used in medium and low voltage applications
- 6m lengths as standard (other lengths available on request)
- Standard markings - Electrical Cable Duct (other markings available on request)