





WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK

Automation

Section



CAM-ST MULTI-DIAGRAM CAM SWITCHES



SWITCHES In UP TO 63A - IP65 325

**LINE SELECTOR SWITCHES
In UP TO 63A - IP65** 326

**LINE SELECTOR SWITCHES
In UP TO 25A - IP65** 327

**MOTOR SELECTOR SWITCHES
In UP TO 63A - IP65** 330

**INSTRUMENT SELECTOR SWITCHES
In UP TO 25A - IP65** 331

**ADDER AND MULTI-WAY SELECTOR SWITCHES
In UP TO 25A - IP65** 334

TECHNICAL ACCESSORIES 339

CAM-SZ ISOLATOR SWITCHES



**REAR PANEL ISOLATOR SWITCHES
In UP TO 100A - IP65** 345

**BASE PANEL ISOLATOR SWITCHES
In UP TO 100A - IP65** 346

**WALL-MOUNTED ISOLATOR SWITCHES
In UP TO 100A - IP65** 154

TECHNICAL ACCESSORIES 347

CAM HEAVY DUTY USE CAM CONTROL DEVICES		
	REAR PANEL AND FLUSH-MOUNTING DEVICES WITH SCREW FIXING	348
	BASE PANEL DEVICES WITH DOORLOCK	360
	WALL-MOUNTED DEVICES	153

PROTECTION DEVICES		
	UNITS AND FUSE-HOLDER BASES	167

CONTROL, START, STOP AND EMERGENCY



CAM-SZ page 345



CAM-SZ page 347



CAM-SZ page 345



CAM-ST page 339



CAM-ST page 325



CAM-ST page 308



CONTROL AND LINE SECTIONING



CAM
page 157

CAM page 156















CAM-SZ page 154



CAM-SZ page 154

SWITCHES

Front-plate	Connection layout	In (A)	AC3 400V (Kw)	Prof. (mm)	Black knob/ grey front-plate 48x48 mm	Black knob/ grey front-plate 67x67 mm			
Switch - 1-pole									
			12	4,5	33	210121	layout 0 - no. 1 disk 211121		
			16	6,5	33	210161	211161		
			20	8	33	210201	211201		
			25	10	33	210251	211251		
			32	10,5	42,4		212321		
			40	13	42,4		212401		
			63	22	42,4		212631		
			Switch - 2-poles						
			12	4,5	33	210122	layout 1 - no. 1 disk 211122		
			16	6,5	33	210162	211162		
			20	8	33	210202	211202		
			25	10	33	210252	211252		
			32	10,5	42,4		212322		
			40	13	42,4		212402		
			63	22	42,4		212632		
			Switch - 3-poles						
			12	4,5	46	210123	layout 2 - no. 2 disks 211123		
			16	6,5	46	210163	211163		
			20	8	46	210203	211203		
			25	10	46	210253	211253		
			32	10,5	59,4		212323		
			40	13	59,4		212403		
			63	22	59,4		212633		
			12	4,5	46		214123* emergency		
			16	6,5	46		214163* emergency		
			20	8	46		214203* emergency		
			25	10	46		214253* emergency		
			32	10,5	59,4		214323* emergency		
			40	13	59,4		214403* emergency		
			63	22	59,4		214633* emergency		
			Switch - 4 poles						
						12	4,5	46	210124
16						6,5	46	210164	211164
20	8	46				210204	211204		
25	10	46				210254	211254		
32	10,5	59,4					212324		
40	13	59,4					212404		
63	22	59,4					212634		
12	4,5	46					214124* emergency		
16	6,5	46					214164* emergency		
20	8	46					214204* emergency		
25	10	46					214254* emergency		
32	10,5	59,4					214324* emergency		
40	13	59,4					214404* emergency		
63	22	59,4					214634* emergency		
Switch - 5-poles									
						12	4,5	59	210125
			16			6,5	59	210165	211165
			20	8	59	210205	211205		
			25	10	59	210255	211255		

* red knob / yellow front-plate

* red knob / yellow front-plate

Form for requesting special products on page 381

LINE SELECTOR SWITCHES

Front-plate	Connection layout	In (A)	AC3 400V (Kw)	Prof. (mm)	Black knob/ grey front-plate 48x48 mm	Black knob/ grey front-plate 67x67 mm
Line selector switches - 1 pole						
			12	4,5	33	236121
			16	6,5	33	236161
			20	8	33	236201
			25	10	33	236251
						layout 8 - no. 1 disk
						237121
						237161
						237201
						237251

Line selector switches - 2 poles						
			12	4,5	46	236122
			16	6,5	46	236162
			20	8	46	236202
			25	10	46	236252
						layout 9 - no. 2 disks
						237122
						237162
						237202
						237252

Line selector switches - 3 poles						
			12	4,5	59	236123
			16	6,5	59	236163
			20	8	59	236203
			25	10	59	236253
						layout 10 - no. 3 disks
						237123
						237163
						237203
						237253

MOTOR SELECTOR SWITCHES

Three-phase reversing switches - 3 poles						
			12	4,5	59	221123
			16	6,5	59	221163
			20	8	59	221203
			25	10	59	221253
			32	10,5	76,4	223323
			40	13	76,4	223403
			63	22	76,4	223633
						layout 12 - no. 3 disks
						222123
						222163
						222203
						222253
						223323
						223403
						223633

Single-phase reversing switches - with auxiliary phase and automatic return - 2 poles						
			12	4,5	59	224122
			16	6,5	59	224162
			20	8	59	224202
			25	10	59	224252
						layout 40 - no. 3 disks
						225123
						225163
						225202
						225252

Dahlander pole selector switches - 3 poles						
			12	4,5	72	381123
			16	6,5	72	381163
			20	8	72	381203
			25	10	72	381253
						layout 66 - no. 4 disks
						382123
						382163
						382203
						382253

Form for requesting special products on page 381



MOTOR SELECTOR SWITCHES

Front-plate	Connection layout	In (A)	AC3 400V (Kw)	Prof. (mm)	Black knob/ grey front-plate 48x48 mm	Black knob/ grey front-plate 67x67 mm
Star/triangle starters - 3 poles						
						layout 13 - no. 4 disks
		12	4,5	72	218123	219123
		16	6,5	72	218163	219163
		20	8	72	218203	219203
		25	10	72	218253	219253
		32	10,5	93,4		220323
		40	13	93,4		220403
		63	22	93,4		220633
Star/triangle starters with reverse direction - 3 poles						
						layout 65 - no. 5 disks
		12	4,5	85	377123	378123
		16	6,5	85	377163	378163
		20	8	85	377203	378203
		25	10	85	377253	378253
Star-0-triangle starters - 3 poles						
						layout 71 - no. 4 disks
		12	4,5	72	379123	380123
		16	6,5	72	379163	380163
		20	8	72	379203	380203
		25	10	72	379253	380253
Switch for single-phase motor - with auxiliary phase and return from start pos. - 2 poles						
						layout 68 - no. 2 disks
		12	4,5	46	385122	386122
		16	6,5	46	385162	386162
		20	8	46	385202	386202
		25	10	46	385252	386252
Line selector switches with self-return to 0 - 3 poles						
						layout 67 - no. 3 disks
		12	4,5	59	383123	384123
		16	6,5	59	383163	384163
		20	8	59	383203	384203
		25	10	59	383253	384253
Two-pole reversing switch with condenser - 3 poles						
						layout 70 - no. 3 disks
		12	4,5	59	387122	388122
		16	6,5	59	387162	388162
		20	8	59	387202	388202
		25	10	59	387252	388252
Three-pole pole changing switch - with 0 central						
						layout 15 - no. 4 disks
		12	4,5	72	226123	227123
		16	6,5	72	226163	227163
		20	8	72	226203	227203
		25	10	72	226253	227253
		32	10,5	93,4		228323
		40	13	93,4		228403
		63	22	93,4		228633

Form for requesting special products on page 381

INSTRUMENT SELECTOR SWITCHES

Front-plate	Connection layout	In (A)	Prof. (mm)	Black knob/ grey front-plate 48x48 mm	Black knob/ grey front-plate 67x67 mm
Voltmeter selector switches - 3 line phases					
					layout 18 - no. 2 disks
		12	33	229120	
		16	33	229160	
		25	33	229250	
Voltmeter selector switches - for 3 neutral-phase voltages					
					layout 19 - no. 2 disks
		12	46	230120	
		16	46	230160	
		25	46	230250	
Voltmeter selector switches - 3 line voltages +2 neutral-phase					
					layout 41 - no. 3 disks
		12	59	231120	
		16	59	231160	
Voltmeter selector switches - 3 line voltages +3 neutral-phase					
					layout 35 - no. 3 disks
		12	59	233120	
		16	59	233160	
		25	59	233250	
Voltmeter selector switches - 3 line voltages +1 neutral-phase					
					layout 42 - no. 3 disks
		12	59	234120	
		16	59	234160	
		25	59	234250	
Ammeter selector switches - single-pole for 3 reduction units					
					layout 75 - no. 3 disks
		12	59	235120	
		16	59	235160	
		20	59	235200	
		25		235250	

Form for requesting special products on page 381



INSTRUMENT SELECTOR SWITCHES

Front-plate	Connection layout	In (A)	AC3 400V (Kw)	Prof. (mm)	Black knob/ grey front-plate 48x48 mm	Black knob/ grey front-plate 67x67 mm
Ammeter selector switches - two-pole for 3 reduction units						
		12		85	390120	layout 74 - no. 5 disks
		16		85	390160	
		20		85	390200	
		25		85	390250	

Ammeter selector switches - single-pole for 1 reduction unit

		12		33	391120	layout 73 - no. 1 disk
		16		33	391160	
		20		33	391200	
		25		33	391250	

Ammeter selector switches - single-pole for 4 reduction units

		12		72	392120	layout 72 - no. 4 disks
		16		72	392160	
		20		72	392200	
		25		72	392250	

ADDER AND MULTI-WAY SELECTOR SWITCHES


Adder - 3-poles

		16	6,5	46	376161	layout 64 - no. 2 disks
		25	10	46	376251	

Form for requesting special products on page 381

Multi-way selector switches (3, 4, 5, 6 ways) from page 334

Multi-way selector switches with 0 (2, 3, 4, 5, 6, 7 ways) from page 334



TECHNICAL ACCESSORIES



Wall-mounted enclosure with provision for front panel control of a rear panel device - screw fixing

page 339
















Blind wall-mounted enclosure suitable for fitting a maximum of 2 rear panel devices - screw or $\varnothing$ 22mm hole fixing

page 339



Adaptor for mounting on $\varnothing$ 22mm hole devices for screw fixing


page 339

Switches	CAM 0 - Single-pole	CAM 1 - Two-pole	CAM 2 - Three-pole	CAM 3 - Four-pole
				
Line selector switches	CAM 4 - Single-pole	CAM 5 - Two-pole	CAM 6 - Three-pole	
				
Motor selector switches	CAM 12 - For three-phase motors	CAM 40 - Two-pole running with auxiliary phase and automatic return	CAM 66 - Dahlander three-pole pole selector switches	
				
	CAM 68 - Two-pole	CAM 67 - Three-pole running with return to 0	CAM 70 - Two-pole with condenser	
				


Form for requesting special products on page 381




CAM 43 - Five-pole




CAM 44 - Six-pole




CAM 3.1 - Six-pole




CAM 7 - Four-pole




CAM 45 - Three-pole with ret. to 0




CAM 13 - Star triangle




CAM 65 - Star/triangle with run reversing




CAM 71 - Star/triangle selector switch




CAM 15 - Di poles (0 central)



CAM 64 - Adder



CAM 631 - For three-phase motor with automatic return




Motor
selector
switches


CAM 572 - Polarity reversing switch for magnetic chucks	CAM 575 - Polarity reversing switch for magnetic chucks	CAM 14 - Star/triangle with run reversing
CAM 34 - Two-pole thermal switches	CAM 36 - Button pad handler	CAM 38 - Sin. pole reversing switch to be inserted between 2 two-way switches
CAM 18 - Voltmetric three concatenated voltages	CAM 19 - Voltmetric three phase voltages	CAM 35 - Voltmetric three concatenated voltages -three of phase
CAM 73 - Amperometric single pole for 1 reduction unit	CAM 75 - Amperometric single pole for 3 reduction units	CAM 74 - Amperometric two-pole for 3 reduction units

Form for requesting special products on page 381


CAM 16 - Dipoles



CAM 17 - Dipoles with run reversing




CAM 32 - Two-pole thermal switches




Two-way switches


CAM 8 - Single pole




CAM 9 - Two-pole




CAM 10 - Three-pole




CAM 11 - Four-pole




CAM 42 - Voltmetric three concatenated voltages-one of phase




CAM 41 - Voltmetric three concatenated voltages-two of phase




CAM 22 - Amperometric on 3 TA



CAM 72 - Amperometric single pole for 4 reduction units



CAM 23 - Amperometric on 3 TA + N



Multi-way switches

CAM 47 - Single pole 3-way 1 2 3	CAM 48 - Single pole 4-way 1 2 3 4	CAM 79 - Single pole 4-way 1 2 4 3	CAM 46 - Single pole 5-way 1 2 3 4 5	CAM 51 - Single pole 6-way 1 2 3 4 5 6			
CAM 25 - 1P, 2P, 3P 4-way 2 3 1 4		CAM 26 - 1P, 2P, 3P 5-way 2 3 1 4 5		CAM 27 - 1P, 2P, 3P 6-way 2 3 1 4 5 6			
CAM 63 - Single pole 7-way + 0 7 1 2 3 4		CAM 52 - Two-pole 2-way + 0 1 2		CAM 54 - Two-pole 3-way + 0 1 2 3		CAM 56 - Two-pole 4-way + 0 1 2 3 4	
CAM 55 - Three-pole 3-way + 0 1 2 3		CAM 57 - Three-pole 4-way + 0 1 2 3 4		CAM 60 - Three-pole 5-way + 0 1 2 3 4 5			

Form for requesting special products on page 381



CAM 49 - Two-pole 4-way		CAM 50 - Three-pole 4-way		CAM 24 - 1P, 2P, 3P 3-way	
CAM 39 - Single-pole 2-way + 0	CAM 78 - Single-pole 3-way + 0	CAM 58 - Single-pole 5-way + 0		CAM 31 - Single-pole 6-way + 0	CAM 61 - Single-pole 6-way + 0
CAM 59 - Two-pole 5-way + 0		CAM 62 - Two-pole 6-way + 0		CAM 53 - Three-pole 2-way + 0	
CAM 28 - 1P, 2P, 3P 3-way + 0		CAM 29 - 1P, 2P, 3P 4-way + 0		CAM 30 - 1P, 2P, 3P 5-way + 0	



CAM-ST series

It is recognisable

Rotary control devices for standard applications



Italian
design
award

TECHNIQUE

The CAM-ST series rotary devices comply with European harmonised standards CEI EN 60947-3, concerning sectioning and operation devices, and with CEI EN 60947-5-1 concerning electromechanical control devices. The cam use, optimised in its electrical, dielectric and mechanical features, allows performances suitable for the heaviest duty use categories, such as AC23 for direct motor operation or other highly inductive loads and AC 15 for very heavy electromagnetic loads control. The front panel features, compared to the active parts and the internal sections of the panel, the IP 65 protection rating, ideal for positioning in dusty environments exposed to weather conditions and water jets. Other than the high protection rate, what is added is the enclosure

resistance characteristics to weather and any item outside and inside the devices. The contact holding disk is made of totally self-extinguishing technopolymers, with the Glow-Wire Test at 960°C (UL94 – V0) and resistance to creeping currents higher than 600V. A CAM-ST feature is the front-plate that can be customised, which distinguishes the application.

Trademarks, symbols, awards



THE ADVANTAGES



EXTREMELY QUICK TO ASSEMBLE

The rear panel version with fixture on a hole measuring 22 mm in diameter with a single hole on the panel and snap fitting of all the elements of the control device makes assembly very fast.



WORKS BETTER AND IS RECOGNISABLE

The totally transparent front-plate shows all the positions to which the knob can be turned to the user's advantage for greater awareness of the electrical manoeuvres and to avoid errors. Owing to the lens effect (the only one on the market), the symbol of the selected position is enlarged and is therefore perfectly identifiable and readable.



TOTAL SAFETY

The switch control can be padlocked preventing unauthorised persons from operating it incorrectly. This is extremely useful for maintenance work.




CAM-ST MULTI-LAYOUT CAM SWITCHES

TECHNICAL SPECIFICATIONS

CAM-ST compact switch			CAM-SZ 12	CAM-ST 16	CAM-ST 20	CAM-ST 25	CAM-ST 32	CAM-ST 40	CAM-ST 63
Rated insulation voltage U_i	V		690	690	690	690	690	690	690
Rated impulse seal voltage U_{imp}	kV		4	4	4	4	4	4	4
Rated making capacity I_{cm}	A		1500	1500	1500	1500	320	400	630
Rated breaking capacity	A		96	128	160	200	256	320	504
Protection against short-circuits									
Rated short time current (1 sec.) I_{cw}	A		480	480	480	480	480	600	950
Conditional short-circuit current	kA		10	10	10	10	10	10	15
Max current of protection fuses (gl or aM)	A		12	16	20	25	32	40	63
Thermal and uninterrupted rated current $I_{th} = I_u$	A		12	16	20	25	32	40	63
Rated operating current I_e									
AC21A	400V	A	15	18	23	28	38	45	63
	500V	A	12	16	20	25	32	40	63
	690V	A	12	16	20	25	32	40	63
AC22A	400V	A	15	18	23	28	38	45	63
	500V	A	12	16	20	25	32	40	63
	690V	A	12	16	20	25	32	40	63
AC23A 3F	230V	A	10	14	18	20	38	45	36
	400V	A	10	14	18	20	32	40	36
	600V	A	6	10	12	16	32	40	36
AC23A 3F	230V	kW	3,5	4,5	5,5	6,5	6,5	8,0	12,0
	400V	kW	5,5	8,0	10,0	11,0	10,5	13,0	22,0
	600V	kW	4,5	7,5	9,0	11,0	19,0	24,0	32,0
AC3 3F	230V	kW	2,5	4,0	5,5	6,0	6,5	8,0	12,0
	400V	kW	4,5	6,5	8,0	10,0	10,5	13,0	22,0
	600V	kW	5,0	8,0	10,0	13,0	19,0	24,0	32,0
AC4	400V	kW	1,2	1,7	2,2	2,5	3,0	5,5	7,5
Mechanical duration	N. oper.		10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶
Frequency of the operations at rated current	oper. /hour		120	120	120	120	120	120	120
Rigid wire section	(mm ²)		1,5 - 6	1,5 - 6	1,5 - 6	1,5 - 6	2,5 - 16	2,5 - 16	2,5 - 16
FLEXIBLE CABLE SECTION	(mm ²)		1,5 - 6	1,5 - 6	1,5 - 6	1,5 - 6	2,5 - 16	2,5 - 16	2,5 - 16
Tightening torque	No		1,5	1,5	1,5	1,5	3	3	3
UL ratings									
1 PH	120V	HP	0,5	0,75	1	1	-	-	-
	240V	HP	1	1,5	2	3	-	-	-
3 PH	240V	HP	2	3	5	5	-	-	-
	480V	HP	5	7,5	10	15	-	-	-
	600V	HP	7,5	10	10	15	-	-	-

CAM-ST REAR PANEL 12÷63A SCREW FIXING



CAM-ST REAR PANEL CONTROL DEVICES 12÷25A Ø22MM SCREW FIXING





CAM-ST series

PRODUCT SPECIFICATIONS

Conformity to standards:	CEI EN 60947-3	IEC 60947-3
	CEI EN 60529	IEC 60529
Operation category:	see table on page. 323	
Protection rating:	IP65 finishes	IP20 cores
Impact resistance:	> IK 08	
Glow wire test:	960°C	
Self-Extinguishing:	V0	
Temperature resistance:	Operating:	-25°C - +60°C
	Storage:	-40°C - +80°C
Homologations:	CE, UL, CSA, IMQ, R.I.Na RoHS compliant	

Switches

CAM-ST series
Switches with black knob
and grey plate. Rear panel finish
48x48. Front panel IP65 Terminals
IP20



Rated current (A)	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	1	1	0	210121	1
	2	1	1	210122	1
	3	2	2	210123	1
	4	2	3	210124	1
	5	3	43	210125	1
	6	3	44	210126	1
16	1	1	0	210161	1
	2	1	1	210162	1
	3	2	2	210163	1
	4	2	3	210164	1
	5	3	43	210165	1
	6	3	44	210166	1
20	1	1	0	210201	1
	2	1	1	210202	1
	3	2	2	210203	1
	4	2	3	210204	1
	5	3	43	210205	1
	6	3	44	210206	1
25	1	1	0	210251	1
	2	1	1	210252	1
	3	2	2	210253	1
	4	2	3	210254	1
	5	3	43	210255	1
	6	3	44	210256	1

Complementary items:

wall-mounting enclosures page 339
hole mounting adaptor page 339.

Switches

CAM-ST series
Switches with black knob
and grey plate. Rear panel finish
67x67. Front panel IP65 Terminals
IP20



Rated current (A)	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	1	1	0	211121	1
	2	1	1	211122	1
	3	2	2	211123	1
	4	2	3	211124	1
	5	3	43	211125	1
	6	3	44	211126	1
16	1	1	0	211161	1
	2	1	1	211162	1
	3	2	2	211163	1
	4	2	3	211164	1
	5	3	43	211165	1
	6	3	44	211166	1
20	1	1	0	211201	1
	2	1	1	211202	1
	3	2	2	211203	1
	4	2	3	211204	1
	5	3	43	211205	1
	6	3	44	211206	1
25	1	1	0	211251	1
	2	1	1	211252	1
	3	2	2	211253	1
	4	2	3	211254	1
	5	3	43	211255	1
	6	3	44	211256	1
32	1	1	0	212321	1
	2	1	1	212322	1
	3	2	2	212323	1
	4	2	3	212324	1
40	1	1	0	212401	1
	2	1	1	212402	1
	3	2	2	212403	1
	4	2	3	212404	1
63	1	1	0	212631	1
	2	1	1	212632	1
	3	2	2	212633	1
	4	2	3	212634	1

Complementary items:

wall-mounting enclosures page 339
hole mounting adaptor page 339.

Switches



CAM-ST series
Switches
red **knob** and yellow **plate** rear
panel finish **67x67**
front panel IP65
terminals IP20
lockable in 0



Rated current (A)	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	3	2	2	214123	1
	4	2	3	214124	1
16	3	2	2	214163	1
	4	2	3	214164	1
20	3	2	2	214203	1
	4	2	3	214204	1
25	3	2	2	214253	1
	4	2	3	214254	1
32	3	2	2	214323	1
	4	2	3	214324	1
40	3	2	2	214403	1
	4	2	3	214404	1
63	3	2	2	214633	1
	4	2	3	214634	1

Complementary items:

wall-mounting enclosures page 339

hole mounting adaptor page 339.

Line selector switches



CAM-ST series
Line selector switches
self-return to 0
black **knob** and grey rear panel
finish front panel IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
16	48x48	3	3	45	360163	1
25	48x48	3	3	45	360253	1
16	67x67	3	3	45	361163	1
25	67x67	3	3	45	361253	1

Complementary items:

wall-mounting enclosures page 339

hole mounting adaptor page 339

Line selector switches



CAM-ST series
Line selector switches
black **knob** and grey rear panel
finish front panel IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	1	4	215121	1
	48x48	2	2	5	215122	1
	48x48	3	3	6	215123	1
	48x48	4	4	7	215124	1
16	48x48	1	1	4	215161	1
	48x48	2	2	5	215162	1
	48x48	3	3	6	215163	1
	48x48	4	4	7	215164	1
20	48x48	1	1	4	215201	1
	48x48	2	2	5	215202	1
	48x48	3	3	6	215203	1
	48x48	4	4	7	215204	1
25	48x48	1	1	4	215251	1
	48x48	2	2	5	215252	1
	48x48	3	3	6	215253	1
	48x48	4	4	7	215254	1
12	67x67	1	1	4	216121	1
	67x67	2	2	5	216122	1
	67x67	3	3	6	216123	1
	67x67	4	4	7	216124	1
16	67x67	1	1	4	216161	1
	67x67	2	2	5	216162	1
	67x67	3	3	6	216163	1
	67x67	4	4	7	216164	1
20	67x67	1	1	4	216201	1
	67x67	2	2	5	216202	1
	67x67	3	3	6	216203	1
	67x67	4	4	7	216204	1
25	67x67	1	1	4	216251	1
	67x67	2	2	5	216252	1
	67x67	3	3	6	216253	1
	67x67	4	4	7	216254	1
32	67x67	1	1	4	217321	1
	67x67	2	2	5	217322	1
	67x67	3	3	6	217323	1
	67x67	4	4	7	217324	1
40	67x67	1	1	4	217401	1
	67x67	2	2	5	217402	1
	67x67	3	3	6	217403	1
	67x67	4	4	7	217404	1
63	67x67	1	1	4	217631	1
	67x67	2	2	5	217632	1
	67x67	3	3	6	217633	1
	67x67	4	4	7	217634	1



Two-Way switches



CAM-ST series
Two-Way switches
black **knob** and **grey** rear panel
finish front panel IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	1	8	236121	1
	48x48	2	2	9	236122	1
	48x48	3	3	10	236123	1
16	48x48	1	1	8	236161	1
	48x48	2	2	9	236162	1
	48x48	3	3	10	236163	1
20	48x48	1	1	8	236201	1
	48x48	2	2	9	236202	1
	48x48	3	3	10	236203	1
25	48x48	1	1	8	236251	1
	48x48	2	2	9	236252	1
	48x48	3	3	10	236253	1
12	67x67	1	1	8	237121	1
	67x67	2	2	9	237122	1
	67x67	3	3	10	237123	1
16	67x67	1	1	8	237161	1
	67x67	2	2	9	237162	1
	67x67	3	3	10	237163	1
20	67x67	1	1	8	237201	1
	67x67	2	2	9	237202	1
	67x67	3	3	10	237203	1
25	67x67	1	1	8	237251	1
	67x67	2	2	9	237252	1
	67x67	3	3	10	237253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Motor selector switches



CAM-ST series
Three-pole reversing switches
black **knob** and **grey** rear panel
finish front panel IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	3	12	221123	1
16	48x48	3	3	12	221163	1
20	48x48	3	3	12	221203	1
25	48x48	3	3	12	221253	1
12	67x67	3	3	12	222123	1
16	67x67	3	3	12	222163	1
20	67x67	3	3	12	222203	1
25	67x67	3	3	12	222253	1
32	67x67	3	3	12	223323	1
40	67x67	3	3	12	223403	1
63	67x67	3	3	12	223633	1

Complementary items:

wall-mounting enclosures page 339
hole mounting adaptor page 339

Motor selector switches



CAM-ST series
Single-phase reversing switches
Auxiliary phase
Automatic return
black knob and grey rear panel
finish front panel IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	3	40	224122	1
16	48x48	2	3	40	224162	1
20	48x48	2	3	40	224202	1
25	48x48	2	3	40	224252	1
12	67x67	2	3	40	225123	1
16	67x67	2	3	40	225163	1
20	67x67	2	3	40	225202	1
25	67x67	2	3	40	225252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Dahlander pole selector switches black knob and grey rear front panel finish IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	4	66	381123	1
16	48x48	3	4	66	381163	1
20	48x48	3	4	66	381203	1
25	48x48	3	4	66	381253	1
12	67x67	3	4	66	382123	1
16	67x67	3	4	66	382163	1
20	67x67	3	4	66	382203	1
25	67x67	3	4	66	382253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Motor selector switches



CAM-ST series
Star/triangle starters
black knob and grey rear front panel
finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	4	13	218123	1
16	48x48	3	4	13	218163	1
20	48x48	3	4	13	218203	1
25	48x48	3	4	13	218253	1
12	67x67	3	4	13	219123	1
16	67x67	3	4	13	219163	1
20	67x67	3	4	13	219203	1
25	67x67	3	4	13	219253	1
32	67x67	3	4	13	220323	1
40	67x67	3	4	13	220403	1
63	67x67	3	4	13	220633	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Star/triangle starters
Inversion
black knob and grey rear front panel
finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	5	65	377123	1
16	48x48	3	5	65	377163	1
20	48x48	3	5	65	377203	1
25	48x48	3	5	65	377253	1
12	67x67	3	5	65	378123	1
16	67x67	3	5	65	378163	1
20	67x67	3	5	65	378203	1
25	67x67	3	5	65	378253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



Motor selector switches



CAM-ST series
Star-0-triangle starters
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	4	71	379123	1
16	48x48	3	4	71	379163	1
20	48x48	3	4	71	379203	1
25	48x48	3	4	71	379253	1
12	67x67	3	4	71	380123	1
16	67x67	3	4	71	380163	1
20	67x67	3	4	71	380203	1
25	67x67	3	4	71	380253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Motor selector switches



CAM-ST series
Reversing switch
Self-return to 0
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	3	67	383123	1
16	48x48	3	3	67	383163	1
20	48x48	3	3	67	383203	1
25	48x48	3	3	67	383253	1
12	67x67	3	3	67	384123	1
16	67x67	3	3	67	384163	1
20	67x67	3	3	67	384203	1
25	67x67	3	3	67	384253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Switch for single-phase motor
Auxiliary phase
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	2	68	385122	1
16	48x48	2	2	68	385162	1
20	48x48	2	2	68	385202	1
25	48x48	2	2	68	385252	1
12	67x67	2	2	68	386122	1
16	67x67	2	2	68	386162	1
20	67x67	2	2	68	386202	1
25	67x67	2	2	68	386252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Two-pole reversing switch
Condenser
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finish	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	3	70	387122	1
16	48x48	2	3	70	387162	1
20	48x48	2	3	70	387202	1
25	48x48	2	3	70	387252	1
12	67x67	2	3	70	388122	1
16	67x67	2	3	70	388162	1
20	67x67	2	3	70	388202	1
25	67x67	2	3	70	388252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Motor selector switches



CAM-ST series
Pole changing switch
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	4	15	226123	1
16	48x48	3	4	15	226163	1
20	48x48	3	4	15	226203	1
25	48x48	3	4	15	226253	1
12	67x67	3	4	15	227123	1
16	67x67	3	4	15	227163	1
20	67x67	3	4	15	227203	1
25	67x67	3	4	15	227253	1
32	67x67	3	4	15	228323	1
40	67x67	3	4	15	228403	1
63	67x67	3	4	15	228633	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Instrument selector switches



CAM-ST series
Voltmeter selector switches
3 line voltages
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	18	229120	1
16	18	229160	1
25	18	229250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Voltmeter selector switches
Neutral-phase voltages
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	19	230120	1
16	19	230160	1
25	19	230250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



Instrument selector switches



CAM-ST series
Voltmeter selector switches
3 line voltages + 2 phase voltages
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	41	231120	1
16	41	231160	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Instrument selector switches



CAM-ST series
Voltmeter selector switches
3 line voltages + 1 phase voltages
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	42	234120	1
16	42	234160	1
25	42	234250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Voltmeter selector switches
3 line voltages + 3 phase voltages
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	35	233120	1
16	35	233160	1
25	35	233250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Ammeter selector switches
Single-pole for 3 reduction units
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	75	235120	1
16	75	235160	1
20	75	235200	1
25	75	235250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Instrument selector switches



CAM-ST series
Ammeter selector switches
Two-poles
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	74	390120	1
16	74	390160	1
20	74	390200	1
25	74	390250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Instrument selector switches



CAM-ST series
Ammeter selector switches
Single-pole for 4 reduction unit
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	72	392120	1
16	72	392160	1
20	72	392200	1
25	72	392250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Ammeter selector switches
Single-pole for 1 reduction unit
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
12	73	391120	1
16	73	391160	1
20	73	391200	1
25	73	391250	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



Adder selector switches



CAM-ST series
Adders
black knob and grey rear front
panel **48x48**
finish IP65
terminals IP20



Rated current (A)	Scheme CAM	Palazzoli code	Pack Q.ty
16	64	376161	1
25	64	376251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Adder selector switches



CAM-ST series
Single-pole 4-way selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	2	48	364121	1
16	48x48	1	2	48	364161	1
20	48x48	1	2	48	364201	1
25	48x48	1	2	48	364251	1
12	67x67	1	2	48	365121	1
16	67x67	1	2	48	365161	1
20	67x67	1	2	48	365201	1
25	67x67	1	2	48	365251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Single-pole 3-way selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	2	47	362121	1
16	48x48	1	2	47	362161	1
20	48x48	1	2	47	362201	1
25	48x48	1	2	47	362251	1
12	67x67	1	2	47	363121	1
16	67x67	1	2	47	363161	1
20	67x67	1	2	47	363201	1
25	67x67	1	2	47	363251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Two-pole 4-way selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	4	49	364122	1
16	48x48	2	4	49	364162	1
20	48x48	2	4	49	364202	1
25	48x48	2	4	49	364252	1
12	67x67	2	4	49	365122	1
16	67x67	2	4	49	365162	1
20	67x67	2	4	49	365202	1
25	67x67	2	4	49	365252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches

CAM-ST series
Three-pole 4-way selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	6	50	364123	1
16	48x48	3	6	50	364163	1
20	48x48	3	6	50	364203	1
25	48x48	3	6	50	364253	1
12	67x67	3	6	50	365123	1
16	67x67	3	6	50	365163	1
20	67x67	3	6	50	365203	1
25	67x67	3	6	50	365253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches

CAM-ST series
Single-pole 6-way selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	3	51	368121	1
16	48x48	1	3	51	368161	1
20	48x48	1	3	51	368201	1
25	48x48	1	3	51	368251	1
12	67x67	1	3	51	369121	1
16	67x67	1	3	51	369161	1
20	67x67	1	3	51	369201	1
25	67x67	1	3	51	369251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

CAM-ST series
Single-pole 5-way selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	3	46	366121	1
16	48x48	1	3	46	366161	1
20	48x48	1	3	46	366201	1
25	48x48	1	3	46	366251	1
12	67x67	1	3	46	367121	1
16	67x67	1	3	46	367161	1
20	67x67	1	3	46	367201	1
25	67x67	1	3	46	367251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

CAM-ST series
Single-pole 2-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	1	39	238121	1
16	48x48	1	1	39	238161	1
20	48x48	1	1	39	238201	1
25	48x48	1	1	39	238251	1
12	67x67	1	1	39	240121	1
16	67x67	1	1	39	240161	1
20	67x67	1	1	39	240201	1
25	67x67	1	1	39	240251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



Multi-way selector switches



CAM-ST series
Two-pole 2-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	2	52	238122	1
16	48x48	2	2	52	238162	1
20	48x48	2	2	52	238202	1
25	48x48	2	2	52	238252	1
12	67x67	2	2	52	240122	1
16	67x67	2	2	52	240162	1
20	67x67	2	2	52	240202	1
25	67x67	2	2	52	240252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches



CAM-ST series
Single-pole 3-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	2	78	241121	1
16	48x48	1	2	78	241161	1
20	48x48	1	2	78	241201	1
25	48x48	1	2	78	241251	1
12	67x67	1	2	78	242121	1
16	67x67	1	2	78	242161	1
20	67x67	1	2	78	242201	1
25	67x67	1	2	78	242251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Three-pole 2-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	3	53	238123	1
16	48x48	3	3	53	238163	1
20	48x48	3	3	53	238203	1
25	48x48	3	3	53	238253	1
12	67x67	3	3	53	240123	1
16	67x67	3	3	53	240163	1
20	67x67	3	3	53	240203	1
25	67x67	3	3	53	240253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Two-pole 3-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	3	54	241122	1
16	48x48	2	3	54	241162	1
20	48x48	2	3	54	241202	1
25	48x48	2	3	54	241252	1
12	67x67	2	3	54	242122	1
16	67x67	2	3	54	242162	1
20	67x67	2	3	54	242202	1
25	67x67	2	3	54	242252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches

CAM-ST series
Three-pole 3-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	5	55	241123	1
16	48x48	3	5	55	241163	1
20	48x48	3	5	55	241203	1
25	48x48	3	5	55	241253	1
12	67x67	3	5	55	242123	1
16	67x67	3	5	55	242163	1
20	67x67	3	5	55	242203	1
25	67x67	3	5	55	242253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches

CAM-ST series
Two-pole 4-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	4	56	243122	1
16	48x48	2	4	56	243162	1
20	48x48	2	4	56	243202	1
25	48x48	2	4	56	243252	1
12	67x67	2	4	56	244122	1
16	67x67	2	4	56	244162	1
20	67x67	2	4	56	244202	1
25	67x67	2	4	56	244252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

CAM-ST series
Single-pole 4-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	3	79	243121	1
16	48x48	1	3	79	243161	1
20	48x48	1	3	79	243201	1
25	48x48	1	3	79	243251	1
12	67x67	1	3	79	244121	1
16	67x67	1	3	79	244161	1
20	67x67	1	3	79	244201	1
25	67x67	1	3	79	244251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

CAM-ST series
Three-pole 4-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishings	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	6	57	243123	1
16	48x48	3	6	57	243163	1
20	48x48	3	6	57	243203	1
25	48x48	3	6	57	243253	1
12	67x67	3	6	57	244123	1
16	67x67	3	6	57	244163	1
20	67x67	3	6	57	244203	1
25	67x67	3	6	57	244253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



Multi-way selector switches



CAM-ST series
Single-pole 5-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	3	58	370121	1
16	48x48	1	3	58	370161	1
20	48x48	1	3	58	370201	1
25	48x48	1	3	58	370251	1
12	67x67	1	3	58	371121	1
16	67x67	1	3	58	371161	1
20	67x67	1	3	58	371201	1
25	67x67	1	3	58	371251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches



CAM-ST series
Three-pole 5-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	3	8	60	370123	1
16	48x48	3	8	60	370163	1
20	48x48	3	8	60	370203	1
25	48x48	3	8	60	370253	1
12	67x67	3	8	60	371123	1
16	67x67	3	8	60	371163	1
20	67x67	3	8	60	371203	1
25	67x67	3	8	60	371253	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Two-pole 5-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	5	59	370122	1
16	48x48	2	5	59	370162	1
20	48x48	2	5	59	370202	1
25	48x48	2	5	59	370252	1
12	67x67	2	5	59	371122	1
16	67x67	2	5	59	371162	1
20	67x67	2	5	59	371202	1
25	67x67	2	5	59	371252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339



CAM-ST series
Two-pole 6-way + 0 selector switches
black knob and grey rear front
panel finish IP65
terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	3	61	372121	1
16	48x48	1	3	61	372161	1
20	48x48	1	3	61	372201	1
25	48x48	1	3	61	372251	1
12	67x67	1	3	61	373121	1
16	67x67	1	3	61	373161	1
20	67x67	1	3	61	373201	1
25	67x67	1	3	61	373251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
wall-mounting enclosures page 339
hole mounting adaptor page 339

Multi-way selector switches

CAM-ST series
Two-pole 6-way + 0 selector switches
 black knob and grey rear front
 panel finish IP65
 terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	2	6	62	372122	1
16	48x48	2	6	62	372162	1
20	48x48	2	6	62	372202	1
25	48x48	2	6	62	372252	1
12	67x67	2	6	62	373122	1
16	67x67	2	6	62	373162	1
20	67x67	2	6	62	373202	1
25	67x67	2	6	62	373252	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
 wall-mounting enclosures page 339
 hole mounting adaptor page 339

Multi-way selector switches

CAM-ST series
Single-pole 7-way + 0 selector switches
 black knob and grey rear front
 panel finish IP65
 terminals IP20



Rated current (A)	Finishes	Poles	No. disks	Scheme CAM	Palazzoli code	Pack Q.ty
12	48x48	1	4	63	374121	1
16	48x48	1	4	63	374161	1
20	48x48	1	4	63	374201	1
25	48x48	1	4	63	374251	1
12	67x67	1	4	63	375121	1
16	67x67	1	4	63	375161	1
20	67x67	1	4	63	375201	1
25	67x67	1	4	63	375251	1

Complementary items:

base panel mounting adaptor and DIN rail page 339
 wall-mounting enclosures page 339
 hole mounting adaptor page 339



TECHNICAL ACCESSORIES



CAM-ST series
Base panel mounting adaptor
and DIN rail page

For control devices type	Palazzoli code	Pack Q.ty
CAM-ST rear panel screw fixing 12-25A	270236	1
CAM-ST rear panel screw fixing 32-63A	270243	1

Complementary items:

the adaptor is applied after the wiring on the selector switch device.



CAM-ST series
Extension shaft for rear panel
devices screw fixing

For control devices type	Length (mm)	Manufacture material	Palazzoli code	Pack Q.ty
CAM-ST 12-25A	225	ANTICORODAL	271225	1
	350	ANTICORODAL	271350	1
	500	ANTICORODAL	271500	1
CAM-ST 32-63A	225	ANTICORODAL	274225	1
	350	ANTICORODAL	274350	1
	500	ANTICORODAL	274500	1



CAM-ST series
Wall-mounted enclosure with
provision for front panel control of
a rear panel device screw fixing
IP65

External dimensions (mm)	Max no. of installable disks	Palazzoli code	Pack Q.ty
121x158x107	6 from 12÷25A 3 from 32÷40A	270247	1



CAM-ST series
Blind wall-mounted enclosure
suitable for fitting
a maximum of 2 rear panel devices
screw or hole fixing
IP65

External dimensions (mm)	Max no. of installable disks	Palazzoli code	Pack Q.ty
121x158x107	6 from 12÷25A 3 from 32÷40A	270248	1



CAM-ST series
Adaptor for mounting devices from
12A to 25A with screw fixing on a
22 mm Ø hole

Front-plate dimensions (mm)	Colour	Palazzoli code	Pack Q.ty
48x48	● black	270237	1
67x67	● black	270239	1
	● yellow ● red	270240	1



CAM-SZ Series

Section the System Multiply Safety

Disconnecting control
devices and for
emergencies

Highly
inductive
loads

TECHNIQUE

The CAM-SZ is designed and built for the operator who has to section the industrial electrical systems for safety and functional reasons. CAM-SZ ensures the powering down of the entire or partial system, dividing it safely from any electrical power supply. CAM-SZ is category AC23A – AC3 is suitable even for highly inductive loads. It is the only one applicable to cage motors (best known as rotary motors, widely used for Industrial and Automation systems) for their start or stop during the rotation. CAM-SZ has IP65 watertight front panel, rated current up to 100A and with maximum operating voltage of $U_n=690V_{ca}$. The contact holding disk is made of totally

self-extinguishing technopolymers, with the Glow-Wire Test at $960^{\circ}C$ (UL94 – V0) and resistance to creeping currents higher than 600V.

Trademarks, symbols, awards



THE ADVANTAGES



UNBEATABLE

An AC23A – AC3 utilisation category, conditional short circuit current 10,000A and guaranteed isolation are some of the few superbly performing features of the isolator switches. At the maximum level of what the market offers today. They allow direct control of even highly inductive loads (such as pumps, exhaust fans, mills, compressors, etc.) and eliminate costly machine shutdowns with a subsequent increase in the system's production.



HIGH ELECTRICAL PERFORMANCES

The contacts in silver alloy are double-break. Each "disk" holds two complete contacts with high connecting and disconnecting power. It does not lose any ampere even years later.



DIVIDES THE SYSTEM AND MULTIPLIES SAFETY


CAM-SZ is suitable for highly inductive loads. It is the only one applicable to cage motors (best known as rotary motors, widely used for Industrial and Automation systems) for their start or stop during the rotation.




CAM-ST SERIES ISOLATOR SWITCHES TECHNICAL SPECIFICATIONS

CAM-SZ Isolator-switch			CAM-SZ 16	CAM-SZ 25	CAM-SZ 32	CAM-SZ 40	CAM-SZ 63	CAM-SZ 100
Rated insulation voltage U_i	V		500	500	500	690	690	690
Rated impulse seal voltage U_{imp}	kV		4	4	4	4	4	4
Rated closing capacity	A		160	250	320	880	1380	2200
Rated breaking capacity	A		125	200	256	690	1100	1750
Protection against short-circuits								
Rated short time current (1 sec.)	A		240	375	480	4800	7500	1200
Conditional short-circuit current	kA		10	10	10	10	10	10
Max current of protection fuses (gl or aM)	A		16	25	32	40	63	100
Thermal and uninterrupted rated current $I_{th} = I_u$	A		16	25	32	40	63	100
Rated operating current I_e								
AC20 230V	A		16	25	32	50	80	100
400V	A		16	25	32	40	63	100
500V	A		16	25	32	40	63	100
AC21A 230V	A		16	25	32	50	80	100
400V	A		16	25	32	40	63	100
500V	A		16	25	32	40	63	100
AC22A 230V	A		16	25	32	50	80	100
400V	A		16	25	32	40	63	100
500V	A		16	25	32	40	63	100
AC23A 3F 230V	A		16	25	32	40	50	63
400V	A		16	25	32	40	50	63
500V	A		16	25	32	40	50	63
690V	A		-	-	-	40	50	63
AC23A 3F 230V	kW		4	6,5	8,5	10	12	20
400V	kW		7,5	11,5	15	16	21	34
500V	kW		8,5	13	17	18	28	44
690V	kW		-	-	-	20	32	50
AC3 3F230V	kW		4	6,5	8,5	9	10	16
400V	kW		7,5	11,5	15	16	17	28
500V	kW		8,5	13	17	18	22	36
690V	kW		-	-	-	20	25	40
AC4 230V	kW		3	4,5	6	-	-	-
400V	kW		5	7,5	10	-	-	-
500V	kW		6,5	10	13	-	-	-
Use in direct current								
DC21A Rated operating current I_e	A		16	25	32	40	63	100
Max voltage for each pole in series	V		60	60	60	60	60	60
DC21A Rated operating current I_e	A		16	25	32	32	40	63
Max voltage for each pole in series	V		48	48	48	60	60	60
DC21A Rated operating current I_e	A		16	25	32	32	37	40
Max voltage for each pole in series	V		30	30	30	30	30	30
Mechanical duration	N.oper.		10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶
Frequency of the operations at rated current	oper. /hour		120	120	120	120	120	120
Rigid wire section	(mm ²)		1-6	1-6	1-6	10-35	10-35	10-35
Flexible cable section	(mm ²)		1-10	1-10	1-10	10-35	10-35	10-35
Tightening torque	No		2	2	2	3	3	3

CAM-SZ REAR PANEL ISOLATOR SWITCHES 16÷32A SCREW FIXING




CAM-SZ REAR PANEL ISOLATOR SWITCHES 40÷100A SCREW FIXING







CAM-SZ REAR PANEL ISOLATOR SWITCHES 16÷32A / 40÷100A WITH ROD KIT




CAM-SZ REAR PANEL ISOLATOR SWITCHES 16÷32A / 40÷100A WITH SPACER



CAM-SZ WALL-MOUNTED AND REAR PANEL ISOLATOR SWITCHES 16÷32A MOUNTING AUXILIARIES



Auxiliary contact fixing layout





CAM-SZ series

PRODUCT SPECIFICATIONS

Conformity to standards:	CEI EN 60947-3	IEC 60947-3
	CEI EN 60529	IEC 60529
Operation category:	see table on page. 341	
Protection rating:	IP65 finishes	IP20 cores
Impact resistance:	> IK 08	
Glow wire test:	960°C	
Self-Extinguishing:	V0	
Temperature resistance:	Operating:	-25°C - +60°C
	Storage:	-40°C - +80°C
Homologations:	CE, IMQ, UL	
	RoHS compliant	

CAM-SZ Series
Rear panel emergency isolator switches with red knob and yellow plate. Rear panel finish 67x67 IP65



Rated current (A)	Poles	Scheme CAM	Palazzoli code	Pack Q.ty
16	2	1	267162	1
	3	2	267163	1
	4	3	267164	1
25	3	2	267253	1
	4	3	267254	1
32	2	1	267322	1
	3	2	267323	1
	4	3	267324	1
40	3	2	267403	1
	4	3	267404	1
63	2	1	267632	1
	3	2	267633	1
	4	3	267634	1
100	3	2	267103	1
	4	3	267104	1

Characteristics

IP20 clamps for cable fastening without having to prepare wires in advance or use terminals.

Complementary items

auxiliary contacts on page 347
adapter for mounting auxiliary contacts page 347
extension shafts page 347
terminal cover cap page 347
Spacer kit page 347



CAM-SZ Series
Rear panel isolator switches with black knob and grey plate. Rear panel finish 67x67 IP65



Rated current (A)	Poles	Scheme CAM	Palazzoli code	Pack Q.ty
16	2	1	268162	1
	3	2	268163	1
	4	3	268164	1
25	3	2	268253	1
	4	3	268254	1
32	2	1	268322	1
	3	2	268323	1
	4	3	268324	1
40	3	2	268403	1
	4	3	268404	1
63	2	1	268632	1
	3	2	268633	1
	4	3	268634	1
100	3	2	268103	1
	4	3	268104	1

Characteristics

IP20 clamps for cable fastening without having to prepare wires in advance or use terminals.

Complementary items

auxiliary contacts on page 347
adapter for mounting auxiliary contacts page 347
extension shafts page 347
terminal cover cap page 347
Spacer kit page 347

REAR, BASE PANEL AND WALL-MOUNTED ISOLATOR SWITCHES



CAM-SZ Series
Base panel isolator switches
with emergency doorlock
with red **knob** and yellow **plate**.
Rear panel finish 67x67
IP65



Rated current (A)	Poles	Scheme CAM	Palazzoli code	Pack Q.ty
16	2	1	265162	1
	3	2	265163	1
	4	3	265164	1
25	3	2	265253	1
	4	3	265254	1
32	2	1	265322	1
	3	2	265323	1
	4	3	265324	1
40	3	2	265403	1
	4	3	265404	1
63	2	1	265632	1
	3	2	265633	1
	4	3	265634	1
100	3	2	265103	1
	4	3	265104	1

Characteristics

IP20 clamps for cable fastening without having to prepare wires in advance or use terminals.

Uses

Direct mounting on plate using screws or on EN50022 rail.

Complementary items

auxiliary contacts on page 347

adapter for mounting auxiliary contacts page 347

extension shafts page 347

terminal cover cap page 347

spacer kit page 347



CAM-SZ Series
Base panel isolator switches
with doorlock with black **knob**
and grey **plate**.
Rear panel finish 67x67
IP65



Rated current (A)	Poles	Scheme CAM	Palazzoli code	Pack Q.ty
16	2	1	266162	1
	3	2	266163	1
	4	3	266164	1
32	2	1	266322	1
	3	2	266323	1
	4	3	266324	1
63	2	1	266632	1
	3	2	266633	1
	4	3	266634	1
100	3	2	266103	1
	4	3	266104	1

Characteristics

IP20 clamps for cable fastening without having to prepare wires in advance or use terminals.

Uses

Direct mounting on plate using screws or on EN50022 rail.

Complementary items

auxiliary contacts on page 347

adapter for mounting auxiliary contacts page 347

extension shafts page 347

terminal cover cap page 347

spacer kit page 347



CAM-SZ Series
Auxiliary contacts for base panel
isolator switches with doorlock
and for walls

Rated current (A)	For control devices tipo	Contact type	Palazzoli code	Pack Q.ty
16	isolator switches 16-32A	1 NC retarded	270226	1
	isolator switches 16-32A	1 NA antipitated	270227	1
	isolator switches 16-32A	1 NC	270230	1
	isolator switches 16-32A	1 NA	270231	1
	isolator switches 16-32A	1NA+1NC	270232	1
	isolator switches 40-100A	1NA+1NC	200016	1

Characteristics

adaptor kit code 270235 is needed for mounting auxiliary contacts from 16A to 32A. 270235. The code 200016 can also be used for rear panel applications from 40A to 100A.

Uses

you can reposition the main contacts from a distance.



CAM-SZ Series
Adaptor for mounting auxiliary
contacts to the base panel 16A
and 32A isolator switches with
doorlock and for walls

For control devices type	Palazzoli code	Pack Q.ty
isolator switches 16-32A	270235	1



CAM-SZ Series
Extension shaft for mounting base
panel isolator switches with
doorlock from 16A to 100A

Lenght (mm)	Manufacture material	Palazzoli code	Pack Q.ty
225	ANTICORODAL	270225	1
350	ANTICORODAL	270350	1
500	ANTICORODAL	270500	1



CAM-SZ Series
Terminal cover cap for isolator
switches

For control devices type	Palazzoli code	Pack Q.ty
isolator switches 16-32A	270241	1
isolator switches 40-100A	270242	1



CAM-SZ Series
Adjustable spacer support kit for
fixing base panel control devices
with doorlock in tropicalised
galvanised steel

Min. lenght (mm)	Max. lenght (mm)	Palazzoli code	Pack Q.ty
96,5	168,5	270900	10

Characteristics

it is composed of 4 equal squares in zinc-plated steel with self-threading screws and washers.

Uses

it is used for fixing devices in the right position and height for correct coupling with the control applied to the hatch.

Rear panel and inset devices screw fixing



CAM 351
Switches In up to 1200A - IP65



CAM 351
Line selector switches
In up to 63A - IP65



CAM 352
Motor selector switches
In up to 200A - IP65



CAM 355
Instrument selector switches
In 16A - IP65



CAM 356
Multi-ways with and without pos. 0
In up to 25A IP65



CAM 358
Two-way switches In 16A - IP65



CAM 358
Technical accessories



CAM 359
Knobs for rear panel devices



CAM 359
Knobs for inset devices




CAM SERIES SWITCHES **TECHNICAL SPECIFICATIONS**


CAM heavy duty switch		CAM 16	CAM 25	CAM 40	CAM 63	CAM 100	CAM 125	CAM 200	CAM 400	CAM 600	CAM 800	CAM 1200
Rated insulation voltage U_i	V	500	500	500	500	500	500	500	500	500	500	500
Rated impulse seal voltage U_{imp}	kV	4	4	4	4	4	4	4	4	4	4	4
Rated closing capacity	A	160	250	400	630	1000	1250	1250	1250	1250	1250	1250
Rated breaking capacity	A	128	200	320	504	800	1000	1000	1000	1000	1000	1000
Protection against short-circuits												
Rated short time current (1 sec.)	A	240	380	600	950	1500	2000	3000	3000	3000	3000	3000
Conditional short-circuit current	kA	10	10	10	15	15	15	15	15	15	15	15
Max current of protection fuses (gl or aM)	A	16	25	40	63	100	125	200	400	600	800	1200
Thermal and uninterrupted rated current $I_{th} = I_u$	A	16	25	40	63	100	125	200	400	600	800	1200
Rated operating current I_e												
AC23A 415V	A	16	25	40	63	100	125	200	-	-	-	-
500V	A	16	25	40	63	100	125	200	-	-	-	-
690V	A	16	25	40	63	100	125	200	-	-	-	-
AC22A 415V	A	16	25	40	63	100	125	200	-	-	-	-
500V	A	16	25	40	63	100	125	200	-	-	-	-
690V	A	16	25	40	63	100	125	200	-	-	-	-
AC23A 230V	A	16	25	40	63	100	125	200	-	-	-	-
400V	A	16	25	40	63	100	125	200	-	-	-	-
500V	A	16	25	40	63	100	125	200	-	-	-	-
AC23A 230V	kW	4,5	7	11	20	26	30	30	-	-	-	-
400V	kW	7,5	12	19	34	45	52	52	-	-	-	-
500V	kW	10	14	23	44	56	64	64	-	-	-	-
AC3A 230V	kW	4,5	7	11	18	26	30	30	-	-	-	-
400V	kW	7,5	12	19	31	45	52	52	-	-	-	-
500V	kW	10	14	23	40	56	64	64	-	-	-	-
AC4 230V	kW	3,5	5	8	13	14	14	14	-	-	-	-
400V	kW	6	8	13	21	27	27	27	-	-	-	-
500V	kW	7,5	10	16	24	28	28	28	-	-	-	-
Use in direct current												
DC20 Rated operating current I_e	A	16	25	40	63	100	125	200	-	-	-	-
DC21 Rated operating current I_e	A	16	25	40	50	100	125	200	-	-	-	-
Max voltage for each pole in series	V	60	60	60	50	42	42	42	-	-	-	-
DC22 Rated operating current I_e	A	16	25	40	40	100	125	200	-	-	-	-
Max voltage for each pole in series	V	48	48	42	42	30	30	30	-	-	-	-
DC23 Rated operating current I_e	A	16	25	40	40	100	125	200	-	-	-	-
Max voltage for each pole in series	V	30	30	30	30	30	30	30	-	-	-	-
Mechanical duration	N. oper.	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶	10 ⁶
Frequency of the operations at rated current	oper. /hour	120	120	120	120	120	120	120	60	60	60	60
Rigid wire section	(mm ²)	1-4	2,5-6	6-10	10-25	10-35	-	-	-	-	-	-
Flexible cable section	mm ²	1-4	1,5-6	4-10	6-16	10-25	16-70*	16-70*	-	-	-	-
Cable lug terminal	-	-	-	-	-	-	M10	M10	M12	M16	M16	2xM16
Tightening torque	Nm	1,5	1,5	2	2	3	3	3	-	-	-	-

* With bolted clamp for terminals

CAM REAR PANEL CONTROL DEVICES 16÷63A SCREW FIXING



CAM INSET CONTROL DEVICES 16÷63A SCREW FIXING





CAM series

PRODUCT SPECIFICATIONS

Conformity to standards:	CEI EN 60947-3	IEC 60947-3
	CEI EN 60529	IEC 60529
Operation category:	see table on page. 349	
Protection rating:	IP65 /IP64 finishes	IP00 cores
Impact resistance:	> IK 08	
Glow wire test:	960°C	
Self-Extinguishing:	V0	
Temperature resistance:	Operating:	-25°C - +60°C
	Storage:	-40°C - +80°C



CAM SERIES
High performance
watertight switches
for distribution board
and flush-mounting
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	1	0	52	276600	1
	2	1	52	276601	5
	3	2	67	276602	5
	4	3	67	276603	5
25	2	1	52	276701	1
	3	2	68	276702	5
	4	3	68	276703	5
40	2	1	74	276801	1
	3	2	92	276802	1
	4	3	92	276803	5
63	3	2	108	286902	1
	4	3	108	286903	5

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358
distribution board knobs on page 359
flush-mounted knobs on page 359



CAM SERIES
High performance
watertight switches
for distribution boards with knob
and front-plate front panel
Front panel IP65
Terminals IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
100	4	3	133	276503	1
200	4	3	145	286603	1
400	4	3	221	286703	1
600	3	2	259	286732	1
800	3	2	297	286762	1
1200	3	2	411	286782	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).



CAM SERIES
Line selector switches
watertight switches
for distribution board
and flush-mounting
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	1	4	52	276604	1
	2	5	67	276605	5
	3	6	83	276606	5
	4	7	98	276607	5
25	2	5	68	276705	1
	3	6	84	276706	5
	4	7	100	276707	5
40	2	5	92	276805	1
	3	6	110	276806	1
	4	7	128	276807	5
63	3	6	134	286906	1
	4	7	159	286907	5

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358
distribution board knobs on page 359
flush-mounted knobs on page 359

REAR PANEL INSET DEVICES SCREW FIXING

CAM SERIES

Line selector switches
watertight switches
for distribution board and
flush-mounting with knob,
front-plate front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
100	4	7	197	276507	1
200	4	7	221	286607	1
400	4	7	373	286707	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

CAM SERIES

Reversing switches for three-phase motors
watertight switches
for distribution board
and flush-mounting
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	3	12	83	276612	5
25	3	12	84	276712	5
40	3	12	110	276812	1
63	3	12	134	286912	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358
distribution board knobs on page 359
flush-mounted knobs on page 359

CAM SERIES

Reversing switches for three-phase motors
watertight switches with knob,
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	631	96	276289	1
40	631	110	276389	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358

CAM SERIES

Pole reversing switches
for magnetic watertight planes
with knob, front-plate and front
panel Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	572	95	276185	1
	575	79	276186	1

Characteristics:

art. 276186 supplied without signalling contact.

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358



**CAM SERIES
Star/triangle starters**
watertight planes
for distribution board
and flush-mounting
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	3	13	98	276613	1
25	3	13	100	276713	1
40	3	13	128	276813	1
63	3	13	159	286913	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358
distribution board knobs on page 359
flush-mounted knobs on page 359



**CAM SERIES
Star/triangle starters**
run reversing watertight planes
for distribution boards with knob
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	14	116	276214	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358



**CAM SERIES
Star/triangle starters**
watertight planes
for distribution boards with knob
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
100	13	197	276513	1
200	13	221	286613	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars). Article 286613 supplied with handwheel.



**CAM SERIES
Pole changing switches**
watertight planes
for distribution board
and flush-mounting
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	3	15	98	276615	1
25	3	15	100	276715	1
40	3	15	128	276815	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358
terminal cover caps page 358
distribution board knobs on page 359
flush-mounted knobs on page 359

REAR PANEL AND INSET DEVICES SCREW FIXING



CAM SERIES
Pole changing switches
watertight planes
for distribution boards with front-
plate knob 0-I-II and front plate
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	16	100	276216	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Pole changing switches
run reversing
high performance watertight for
distribution boards with knob and
front-plate 2-1-0-2 front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	17	148	276217	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Heat control high performance
watertight switches with knob,
front-plate 0-1-2-3 front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	2	32	67	276132	1
25	2	34	68	276234	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Watertight
high performance control
for distribution boards with knob
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	36	52	276136	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Voltmeter selector switch
high performance watertight for
distribution boards with knob
and front-plate 0-RS-RT-ST
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	18	67	276118	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Voltmeter selector switch
high performance watertight for
distribution boards with knob and
front-plate RT-ST-RS-0-RN-SN-TN
front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	35	83	276135	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Voltmeter selector switch
high performance watertight for
distribution boards with knob
and front-plate 0-RN-ST-TN
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	19	67	276119	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Ammeter selector switch on 3 watertight high performance
reduction units with knob,
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	22	98	276122	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358

REAR PANEL AND INSET DEVICES SCREW FIXING



CAM SERIES
Ammeter selector switch on 4
watertight high performance
reduction units with knob,
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	23	98	276123	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
3-way selector switch
high performance reduction
units with knob, front-plate
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	24	68	276224	1
	2	24	84	276244	1
	3	24	116	276254	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
4-way selector switch
high performance reduction
units with knob,
front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	25	68	276225	1
	2	25	100	276245	1
	3	25	132	276255	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
5-way watertight high
performance selector switch
with knob, front-plate
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	26	84	276226	1
	2	26	116	276246	1
	3	26	164	276256	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



**CAM SERIES
6-way watertight high
performance selector switch**
with knob, front-plate
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	27	84	276227	1
	2	27	132	276247	1
	3	27	180	276257	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



**CAM SERIES
3-way + 0 watertight high
performance selector switch**
with knob, front-plate
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	28	68	276228	1
	2	28	84	276248	1
	3	28	116	276258	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



**CAM SERIES
4-way + 0 watertight high
performance selector switch**
with knob, front-plate
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	29	68	276229	1
	2	29	100	276249	1
	3	29	132	276259	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



**CAM SERIES
5-way + 0 watertight high
performance selector switch**
with knob, front-plate
and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	30	84	276230	1
	2	30	132	276250	1
	3	30	180	276260	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358

REAR PANEL AND INSET DEVICES SCREW FIXING



CAM SERIES
6-way + 0 watertight high performance selector switch with knob, front-plate and front panel
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
25	1	31	100	276231	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358



CAM SERIES
Two-Way watertight high performance selector switch for distribution board and flush-mounting
Front panel IP65
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	1	8	52	276608	1
	2	9	67	276609	1
	3	10	83	276610	1
	4	11	98	276611	1

Uses:

they can be fixed onto the hatch or in blind compartments (e.g. empty steel pillars).

Complementary items:

protruding terminal blocks page 358

terminal cover caps page 358

distribution board knobs on page 359

flush-mounted knobs on page 359



CAM SERIES
Projecting terminals for control devices

Rated current (A)	Terminal block description	Palazzoli code	Pack Q.ty
16	Right	270810	20
	Left	270811	20
25	Right	270820	20
	Left	270821	20

Uses:

they are used for easily connecting wires to the terminals even if the device is installed in an awkward position.




CAM SERIES
Rear protection caps for distribution boards in transparent thermoplastic material
IP54

For devices with depth (mm)	Palazzoli code	Pack Q.ty
52/67/68	276910	1
74/82/92	276930	1
79/83/84/95/96/98/100	276911	1
108/110/128/134	276931	1
114/116/130/132	276912	1
145/148/160/164	276913	1
159	276932	1

Uses:

they have connections with stepped gland in non-ageing elastomer. They ensure rear protection IP54.



CAM SERIES
Rear protection caps for flush-mounting in transparent thermoplastic material
IP54

For devices with depth (mm)	Palazzoli code	Pack Q.ty
52/67/68	278920	1
74/82/92	278940	1
83/84/96/98/100	278921	1
108/110/128/134	278941	1
159	278942	1

Characteristics:

they have connections with stepped gland in non-ageing elastomer. They ensure rear protection IP54.



CAM SERIES
Black knobs **for distribution boards** with front-plate in anodized aluminium and polycarbonate transparent protection IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 16/25A	67x67	292115	10
Switches 40/63A	99x99	292315	1
Selector switches, reversing switches, pole changing switches 16/25A	67x67	292135	10
Selector switches, reversing switches, pole changing switches 40/63A	99x99	292335	1
Two-way switches 16A	67x67	292145	1
Star/triangle starters 16/25A	67x67	292155	1
Star/triangle starters 40/63A	99x99	292355	1



CAM SERIES
Black knobs **for distribution boards** with front-plate in anodized aluminium and polycarbonate transparent protection IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 16/25A	67x67	292116	1
Switches 40/63A	99x99	292316	1
Switches, selector switches, reversing switches, pole changing switches 16/25A	67x67	292136	1
Switches, selector switches, reversing switches, pole changing switches 40/63A	99x99	292336	1
Two-way switches 16A	67x67	292146	1
Star/triangle starters 16/25A	67x67	292156	1
Star/triangle starters 40/63A	99x99	292356	1



CAM SERIES
Grey lockable knobs **for distribution boards**, with blue thermoplastic flange IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches, selector switches, reversing switches, pole changing switches 16/25A	67x67	292125	10
Switches, selector switches, reversing switches, pole changing switches 40/63A	99x99	292325	1

Characteristics:

for lockable main switches in position "I" or "O".



CAM SERIES
Grey lockable **flush-mounted** knobs, with blue thermoplastic flange IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches, selector switches, reversing switches, pole changing switches 16/25A	67x67	292126	1
Switches, selector switches, reversing switches, pole changing switches 40/63A	99x99	292326	1

Characteristics:

for lockable main switches in position "I" or "O".



CAM SERIES
Red lockable emergency knobs **for distribution boards**, with yellow thermoplastic flange IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches, selector switches, reversing switches, pole changing switches 16/25A	67x67	292105	10
Switches, selector switches, reversing switches, pole changing switches 40/63A	99x99	292305	1

Characteristics:

for lockable main switches in position "I" or "O".



CAM SERIES
Red lockable **flush-mounted** emergency knobs with yellow thermoplastic flange IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches, selector switches, reversing switches, pole changing switches 16/25A	67x67	292106	1
Switches, selector switches, reversing switches, pole changing switches 40/63A	99x99	292306	1

Characteristics:

for lockable main switches in position "I" or "O".



CAM 362

Switches with doorlock
In up to 400A



CAM 363

Technical accessories



CAM 362

Line selector switches with doorlock
In up to 200A




CAM 364-365

Knobs for CAM with doorlock



CAM BASE PANEL CONTROL DEVICES 16÷63A SCREW FIXING



REAR PANEL DEVICES WITH DOORLOCK

CAM series

PRODUCT SPECIFICATIONS

Conformity to standards:	CEI EN 60947-3	IEC 60947-3
	CEI EN 60529	IEC 60529
Operation category:	AC3 - AC23A	
Protection rating:	IP65 /IP64 finishes	IP00 cores
Impact resistance:	> IK 08	
Glow wire test:	960°C	
Self-Extinguishing:	V0	
Temperature resistance:	Operating:	-25°C - +60°C
	Storage:	-40°C - +80°C

CAM SERIES

A32 switches

with doorlock for cabinets,
with protective cap on high
capacity input
Terminal blocks IP00



Rated current (A)	Poles	Depth (mm)	Palazzoli code	Pack Q.ty
32	2	102	275232	1
	3	102	275332	1
	4	102	275432	1

Characteristics:

clamps suitable for locking cables without preparing wires in advance and without using terminals.

Uses:

for snaplocking the device on EN50022 rail or directly fastening it onto the plate using screws.

Complementary items:

cabinet knobs page 364÷365

CAM SERIES

Switches

with doorlock for cabinets,
with protective cap on high
capacity input
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	3	2	96	275112	10
	4	3	96	275113	10
25	3	2	97	275212	10
	4	3	97	275213	10
40	3	2	123	275312	5
	4	3	123	275313	5
63	3	2	140	285412	5
	4	3	140	285413	5

Complementary items:

protruding terminals page 363

Spacer kit page 363

cabinet knobs page 364÷365

CAM SERIES

Switches

with doorlock for cabinets,
with protective cap on high
capacity input
terminals
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
100	3	2	183	270512	1
100	4	3	183	270513	1
200	3	2	195	280612	1
200	4	3	195	280613	1
400	3	2	233	280712	1
400	4	3	271	280713	1

Complementary items:

cabinet knobs page 364÷365



**CAM SERIES
Selector switches**
with doorlock for cabinets,
with protective cap on high
capacity input
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
16	3	6	112	275116	1
	4	7	128	275117	1
25	3	6	113	275216	1
	4	7	129	275217	1
40	3	6	141	275316	1
	4	7	159	275317	1
63	3	6	166	285416	1
	4	7	191	285417	1

Complementary items:

protruding terminals page 363

Spacer kit page 363

cabinet knobs page 364÷365



**CAM SERIES
Selector switches**
with doorlock for cabinets,
with protective cap on high
capacity input
Terminal blocks IP00



Rated current (A)	Poles	Scheme CAM	Depth (mm)	Palazzoli code	Pack Q.ty
100	4	7	247	270517	1
200	4	7	271	280617	1

Complementary items:

cabinet knobs page 364÷365



CAM SERIES
Projecting terminals
for control devices

Rated current (A)	Terminal block description	Palazzoli code	Pack Q.ty
16	Right	270810	20
	Left	270811	20
25	Right	270820	20
	Left	270821	20

Uses:

they are used for easily connecting wires to the terminals even if the device is installed in an awkward position.



CAM SERIES
Adjustable spacer support kit
for attaching control devices for
tropicalized steel cabinet with
doorlock.

Min. lenght (mm)	Max. lenght (mm)	Palazzoli code	Pack Q.ty
96,5	168,5	270900	10

Characteristics

suitable for loads from 16A to 63A Composed of 4 equal brackets in zinc-plated steel with self-threading screws and washers.

Uses

it is used for fixing devices in the right position and height for correct coupling with the control applied to the hatch.

REAR PANEL DEVICES WITH DOORLOCK



CAM SERIES
Black knobs with doorlock for cabinets, with anodised aluminium front-plate and transparent polycarbonate protection IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 16/25/32A	67x67	295117	10
Switches 40/63A	99x99	295157	5
Selector switches 16/25A	67x67	295137	1
Selector switches 40/63A	99x99	295177	1



CAM SERIES
Grey lockable knobs with doorlock for cabinets, with blue thermoplastic flange IP65

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 16/25/32A	83x83	295108	10
Switches 40/63A	105x105	295308	5
Selector switches 16/25A	83x83	295118	1
Selector switches 40/63A	105x105	295318	1

Characteristics:

lockable in any position. Codes 295308 and 295318 have a projecting lever knob.



CAM SERIES
Grey lockable knobs with doorlock for cabinets, with blue thermoplastic flange IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches, selector switches 16/25/32A	67x67	295127	1
Switches, selector switches 40/63A	99x99	295167	1

Characteristics:

lockable in any position.



CAM SERIES
Red lockable emergency knobs with doorlock for cabinets, with yellow thermoplastic flange IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches, selector switches 16/25/32A	67x67	295107	10
Switches, selector switches 40/63A	99x99	295147	5

Characteristics:

lockable in any position.



CAM SERIES
Red lockable emergency knobs with doorlock for cabinets, with yellow thermoplastic flange IP65

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 16/25/32A	83x83	295128	10
Switches 40/63A	105x105	295328	5
Selector switches 16/25A	83x83	295138	1
Selector switches 40/63A	105x105	295338	1

Characteristics:

lockable in any position. Codes 295328 and 295338 have a projecting lever knob.



CAM SERIES
Black knobs with doorlock for cabinets, with anodised aluminium front-plate IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 100A ~	134x134	270528	1
Switches 200A ~	134x134	270628	2
Selector switches 100A	134x134	270538	1
Selector switches 200A	134x134	270638	1



CAM SERIES
Black handwheel with doorlock for cabinets, with anodised aluminium front-plate IP54

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 400A	134x134	270728	1



CAM SERIES
Grey lockable knobs with doorlock for cabinets, with blue thermoplastic flange IP65

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 100/200A	105x105	292508	1
Switches 400A ~	72x83	292708	1
Selector switches 100/200A	105x105	292518	1

Characteristics:

lockable in any position. Code 292708 has a projecting lever knob.



CAM SERIES
Red lockable emergency knobs with doorlock for cabinets, with yellow thermoplastic flange IP65

For control devices type	Flange dimensions (mm)	Palazzoli code	Pack Q.ty
Switches 100/200A	105x105	292528	2
Switches 400A ~	72x83	292728	1
Selector switches 100/200A	105x105	292538	1

Characteristics:

lockable in any position. Code 292728 has a projecting lever knob.