



Cable Ties

DOME-TOP® Barb Ty Cable Ties



- Dome-top head features unique patented design with round, smooth edges
- Stainless steel locking barb provides consistent performance, reliability and infinite adjustability through entire bundle range
- High strength and low thread force



Part Number Nylon 6.6	Part Number Weather Resistant	Length (In.)	Max. Bundle Dia. (In.)	Min. Loop Tensile Strength (Lbs.)	Tool	Pkg. Qty.
BT1M-C	BT1M-C0	4.0	.90	18	GTS, GTSL, GS2B, PTS, PPTS, STS2	100
BT1M-M	BT1M-M0	4.0	.90	18		1000
BT1.5M-C	BT1.5M-C0	6.3	1.50	18		100
BT2M-C	BT2M-C0	7.9	2.00	18		100
BT4M-C	BT4M-C0	14.2	4.00	18		100
BT1.5I-C	BT1.5I-C0	6.1	1.50	40		100
BT1.5I-M	BT1.5I-M0	6.1	1.50	40		1000
BT2I-C	BT2I-C0	8.0	2.00	40		100
BT3I-C	BT3I-C0	11.3	3.00	40		100
BT4I-C	BT4I-C0	14.3	4.00	40		100
BT2S-C	BT2S-C0	8.0	2.00	50	GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2	100
BT2S-M	BT2S-M0	8.0	2.00	50		1000
BT3S-C	BT3S-C0	12.0	3.00	50		100
BT4S-C	BT4S-C0	15.1	4.00	50		100
BT4S-M	BT4S-M0	15.1	4.00	50		1000
BT2LH-L	BT2LH-L0	8.7	2.00	120	GTH, GS4H, GS4EH, PTH, STH2, ST3EH	50
BT3LH-L	BT3LH-L0	11.8	3.00	120		50
BT4LH-L	BT4LH-L0	14.9	4.00	120		50
BT6LH-L	BT6LH-L0	21.2	6.00	120		50
BT7LH-L	BT7LH-L0	24.4	7.00	120		50
BT8LH-L	BT8LH-L0	27.5	8.00	120		50
BT9LH-L	BT9LH-L0	30.7	9.00	120		50

Parts available in other materials and colors.
UL Listing excludes Light-Heavy cross section ties in weather resistant material.



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

Cable Ties

Cable Accessories

Stainless Steel

Wiring Duct

Surface Raceway

Abrasion Protection

Terminals

Power Connectors

Grounding Connectors

Identification & Labeling

Lockout/Tagout & Safety

Network Components