



PAN-TY® Cable Ties – HALAR[▲]



- UL Listed for use in Plenum or Air Handling Spaces per NEC, Section 300-22 (C) and (D)
- Low smoke density and excellent flammability rating of UL94V-0
- Commonly accepted solution for bundling qualified cable without conduit in air handling space applications



Part Number	Length (In.)	Max. Bundle Dia. (In.)	Min. Loop Tensile Strength (Lbs.)	Tool	Std. Pkg. Qty.
PLT1M-C702Y	4.0	.87	18	GTS, GTSL, GS2B, PTS, PPTS, STS2	100
PLT2S-C702Y	7.4	1.88	50	GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2	100
PLT3S-C702Y	11.6	3.00	50		100

[▲]HALAR is the registered trademark of Solvay Solexis, Inc.

NEW! PAN-TY® Cable Ties – Polyetheretherketone (PEEK)



- High temperature material up to 500 °F
- Flammability rating of UL94V-0 with low smoke and toxicity, and resistant to a wide variety of chemicals and gamma radiation
- High loop tensile strength

Part Number	Length (In.)	Max. Bundle Diameter (In.)	Min. Loop Tensile Strength (Lbs.)	Tool	Std. Pkg. Qty.
PLT2S-M71	7.4	1.88	150	GTS, GTSL, GS2B, GTH, GS4H, PTS, PPTS, STS2, STH2	1000



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING

www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371

Tel 0044 117 977 4647 Fax 0044 117 9775582

Cable Ties

Cable Accessories

Stainless Steel

Wireing Duct

Surface Raceway

Abraction Protection

Terminals

Power Connectors

Grounding Connectors

Identification & Labeling

Lockout/Tagout & Safety

Network Components