



PAN-STEEL® Fully Coated Stainless Steel Cable Ties



- Polyester coated 316 grade stainless steel
- Self-locking with low thread force
- Low smoke, halogen free and UV resistant
- Temperature tolerance -40°F (-40°C) to 302°F (150°C)

Part Number	Length (In.)	Width (In.)	Min. Loop Tensile Strength (Lbs.)*	Tool**	Std. Pkg. Qty.
Standard Cross Section					
MLTFC2S-CP316	7.9	.18	100	GS4MT	100
MLTFC4S-CP316	14.3	.18	100		100
MLTFC6S-CP316	20.5	.18	100		100
MLTFC8S-CP316	26.8	.18	100		100
Heavy Cross Section					
MLTFC2H-LP316	7.9	.31	250	GS4MT	50
MLTFC4H-LP316	14.3	.31	250		50
MLTFC6H-LP316	20.5	.31	250		50
MLTFC8H-LP316	26.8	.31	250		50
Extra-Heavy Cross Section					
MLTFC4EH-LP316	17.1	.50	300	RT1HT	50
MLTFC6EH-LP316	23.4	.50	300		50
MLTFC8EH-LP316	29.7	.50	300		50
Super-Heavy Cross Section					
MLTFC4SH-LP316	17.1	.63	450	RT1HT	50
MLTFC6SH-LP316	23.4	.63	450		50
MLTFC8SH-LP316	29.7	.63	450		50

*Per SAE Standard AS23190/3 (formerly MIL).

**For information on other installation tools available, contact PANDUIT Customer Service or visit www.panduit.com.

Cable Ties

Cable Accessories

Stainless Steel

Wiring Duct

Surface Raceway

Abrasion Protection

Terminals

Power Connectors

Grounding Connectors

Identification & Labeling

Lockout/Tagout & Safety

Network Components



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS, FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
 FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
 Tel 0044 117 977 4647 Fax 0044 117 9775582