

PERSONAL TORCHES

Small and mighty! Peli's advanced lighting products are designed to be compact yet incredibly bright and lightweight.

MEDIUM TORCHES

These models offer quality, durability and dependability.

MITYLITE™ 2AAA

Cat No. 1900

- High performance Xenon lamp module
- Twist on/off lens shroud
- Hi-impact Xenoy® resin body
- Shirt clip
- 90° Light Bender (included)
- 2 x AAA batteries (included)



VERSABRITE™

Cat No. 2250

- High performance Xenon lamp module
- Twist on/off lens shroud
- Swivel head directs the beam
- Clip for hands-free use
- Red and green night vision discs included
- Elasticated head-strap included
- 2 x AA batteries (included)



MITYLITE™ 2AA

Cat No. 2300

- High performance Xenon lamp module
- Twist on/off lens shroud
- Xenoy® resin body with polycarbonate lens
- 2 x AA batteries (included)



MITYLITE™ 2AA+

Cat No. 2340

- High performance Xenon lamp module
- Handy tail button on/off switch
- Hi-impact Xenoy® resin body with polycarbonate lens
- 2 x AA batteries (included)





• Pre-focused Xenon lamp module

- Twist on/off lens shroud
- Built for durability
- Waterproof
- 2 x C-cell batteries (not included)



SABRELITE™

Cat No. 2000

- Xenon beam penetrates smoke and fog
- Twist on/off lens shroud
- Rugged body with a hi-impact nylon lens
- Stainless steel split ring
- Adjustable wrist lanyard
- Spring loaded belt clip
- 3 x C cells (not included)



STEALTHLITE™

Cat No. 2400

- One-handed safety switch
- Unbreakable body with a hi-impact polycarbonate lens
- Double shock mounted battery compartment
- Adjustable wrist lanyard
- Helmet mountable
- 4 x AA batteries (included)



STEALTHLITE™ RECHARGEABLE

- High performance Xenon lamp module
- One-handed safety switch
- Tough body with polycarbonate lens
- Water and Corrosion proof
- Smart Charger base with 240v charger and high-capacity industrial NiMh battery pack







LED TORCHES

Designed using the latest LED technology in a variety of models, from compact mini torches to larger hand lamps, this LED series offers a solution for all requirements.

LFD Cat No. 1910

- Ultra compact aluminium design
- LED lights create a clean white beam
- Lightweight pocket torch
- Ideal personal light
- 1 AAA battery (included)



LED Cat No. 1920

- Ultra compact aluminium design
- LED lights create a clean white beam
- Lightweight pocket torch
- Ideal personal light
- 2 x AAA batteries (included)



L1 LED

Cat No. 1930

- LED offers excellent battery efficiency
- End switch for momentary "blink" or constant "on" modes
- Lanvard with breakaway safety feature
- Pocket clip for easy attachment
- Red and green night vision discs included
- 4 x LR 44 1.5 coin cells (included)



SABRELITE[™] LED

Cat No. 2010

- Luxeon Lambertion LED using LED Technology™
- Twist on/off lens shroud
- Rugged ABS body
- Adjustable lanyard
- 3 x C-cell alkaline batteries (not included)



MINI FLASHER™



- Compact emergency light
- Twist on/off shroud
- LED pulses at a frequency of two pulses per second
- LED lamp never needs replacement
- 2 x L1154 1.5v coin-cell (included)

VB3™ LED

Cat No. 2220

- Head flips up to activate LEDs and rotates 180° to aim light where required
- Multiple use built in clip
- Attaches to surface up to 10mm thick
- 2 x CR2032 3v coin cells (included)
- Red LED version available



LED FLEX - NECK

Cat No. 2365

- 1 Watt Luxeon LED beam
- Magnetic base for fixed position
- Push button tail switch
- Flexible cable neck to shine light where required
- 2 x AA batteries (not included)



LED Cat No. 2370

- 3 lights in one
- Bright white, night vision red or blue light options
- Dual mode: High or Low output (white)
- Manufactured in strong but lightweight aluminium
- Steel clip to attach to clothing
- 2 x AA batteries (included)



- STEALTHLITE™ LED
- Uses LED Technology™ . Waterproof, ideal for wide range of applications
- Piercing, white 126 lumen beam
- 4 x AA batteries (included)



STEALTHLITE™ LED RECHARGEABLE

Cat No. 2460

Cat No. 2410

- Uses Peli's LED
- One handed safety switch operation
- Rugged body with polycarbonate lens
- Smart Charger base with 240v charger and high-capacity industrial NiMh battery pack



RECOIL™ LED WITH TRAFFIC WAND

Cat No. 2490

- Uses Peli's Recoil™ LED
- Can be used as a torch (without wand)
- Polymer based, opaque, screw-on traffic wand
- 51 lumens
- Runtime of up to 15 hours
- 4 colour discs included
- 4 x AA batteries (not included)



COMPACT LED HAND LAMP

- Lightweight 1.4kg
- High performance 710 lumen LED
- Ribbed handle prevents slipping
- 90° tilt-adjustable head for use as a lantern
- 3 mode switch high, economy & flashing
- Shoulder strap supplied
- 3-stage battery level indicator
- Duration 1.75 hrs (high mode) 4.75 hours (economy mode)












NEMO™ TORCHES

Submersible Torches designed specifically for divers, in various models to suit all aspects of diving.

NEMO™ Cat No. 1900N

- Bright Xenon beam
- Compact, lightweight hand torch
- Convenient clip
- 2 x AAA batteries (included)



- Xenon beam penetrates murky conditions
- Twist on/off lens shroud
- Rugged body with a hi-impact nylon lens
- Stainless steel split ring
- Adjustable wrist lanyard
- Spring loaded belt clip
- 3 x C-cells (not included)



NEMO[™] Cat No. 2400N

- One-handed on/off switch
- Unbreakable body with a hi-impact polycarbonate lens
- Double shock mounted battery compartment
- Adjustable wrist lanyard
- 4 x AA batteries (included)

mounted artment sist lanyard

NEMO[™] Cat No. 4300N

- Powerful Xenon lamp produces 276 lumens
- Easy on/off magnetic switch
- Spare lamp included
- Rugged body and polycarbonate lens with over-moulded thermoplastic accents
- 8 x C-cells (not included)



TACTICAL TORCHES

Designed for police and security professionals, these tactical torches are compact and lightweight yet ultra bright.

M6



- 1.3 amp Xenon lamp module
- Tail switch provides constant on/off or momentary light
- CNC-machined aluminium with deep knurled grip
- Safety lockout switch prevents inadvertent activation
- Cordura® holster included
- 2 x CR123 lithium cell batteries (included)

PM6

Cat No. 3320

- Super bright focused Xenon beam
- Tactical on/off tail switch
- Sturdy, detachable, magnesium coated clip
- Durable and lightweight polymer body
- Helmet light holder available
- 2 x CR123 lithium cell batteries (included)

M11 RECHARGEABLE

- High performance Xenon lamp
- Push button switch
- Non slip grip for use in all weathers
- Powerful 137 lumen beam





TACTICAL LED TORCHES

These models incorporate the latest LED technology to produce compact, incredibly bright and efficient lights.

Cat No. 2360

M6 LED

Cat No. 2330

- Powerful 1 Watt LED beam
- Convenient tail switch
- High grade aluminium with a non-slip knurled grip
- Cordura® holster included
- 2 x CR123 lithium cell batteries (included)

M5 LED

- Bright, white 110 lumen beam on high mode
- Tough, aluminium body
- Tail button on/off switch
- High and Low power modes
- Lightweight, just 130 grams
- 2 x AA batteries (included)

M6 LED 3W



- Powerful 3 Watt LED beam produces 177 lumens
- Tail switch
- CNC-machined from solid high grade aluminium with a non-slip knurled diamond pattern
- Cordura® holster included
- 2 x CR123 lithium cell batteries (included)

PM6 LED


Cat No. 3330

- Intense 1 Watt LED beam
- Tactical tail switch
- Durable and lightweight polymer body
- Helmet light holder available
- 2 x CR123 lithium cell batteries (included)



7060 LED RECHARGEABLE

Cat No. 7060




- Powerful beam penetrates over 254 metres of darkness
- LED never needs replacing
- Low battery indicator

8060 LED RECHARGEABLE



- 6 hours of light from one charge
- No slip grenade grip
- 4 x C Alkaline batteries can also be used





TORCH SPECIFICATIONS

Product	Model No.	Light Source	Batteries	Key Features	lumens	metres	candelas	hours	Length (mm)	Weight with batteries (g)	Colours
	1900	Xenon	2 x AAA Alkaline	+	11	45	571	1.5	120	50	
Î	2250	Xenon	2 x AA Alkaline	+	7	54	726	5.5	98	90	•
	2300	Xenon	2 x AA Alkaline	+	11	43	478	4.5	143	100	••
The second secon	2340	Xenon	2 x AA Alkaline	+	10	43	461	4.5	159	100	••
	1800	Xenon	2 x C-cell Alkaline	0	21	131	4370	7	152	220	••
	2000	Xenon	3 x C-cell Alkaline	0	53	158	6234	5	198	360	••
	2400	Xenon	4 x AA Alkaline	+	45	125	3934	3.45	165	200	••
	2450	Xenon	4 x AA NiMH Rechargeable	10	35	122	3735	3.5	165	220	••
	1910	LED	1 x AAA Alkaline	+	39	62	967	1	91	40	•
	1920	LED	2 x AAA Alkaline	+	67	81	1648	2.45	135	90	•
	1930	LED	4 x LR 44 Alkaline	+	12	17	70	4.15	67	30	••
	2010	LED	3 x C-cell Alkaline	0	109	74	1359	43	206	380	••
	2130	LED	2 x L1154 Alkaline	+	4.7				44	10	•
6	2220	LED	2 x CR2032 Lithium	+	9	12	38	34	89	30	••
	2365	LED	2 x AA Alkaline		49	81	1644	7	557	260	•
	2370	LED	2 x AA Alkaline	+ Low)		52		41.25	163	180	•
	2410	LED	4 x AA Alkaline	(High)	106 126	158	684 2622	7.15	178	210	
	2460	LED	4 x AA NiMH		112	99	1583	4.15	178	220	
	2490	Recoil™ LED	Rechargeable 4 x AA Alkaline		51	88	1930	15	317	230	
	9410	LED	4 D Ni-MH	+ (Low)	300	249	15516	4.75	222	1400	
	9410	LED	4 D MI-WIII	(Low)	710	425	45260	1.5		1400	••
	1900N	Xenon	2 x AAA Alkaline	1	11	45	571	1.5	120	50	•••
5	2000N	Xenon	3 x C-cell Alkaline		53	158	6234	5	198	360	•••
	2400N	Xenon	4 x AA Alkaline	† \	45	125	3934	3.45	165	200	•••
	4300N	Xenon	8 x C-cell Alkaline	Z	276	143	5222	6	190	1040	•••
(Section)	2320	Xenon	2 x CR123 Lithium	+	82	145	5260	1.15	140	160	•
	3320	Xenon	2 x CR123 Lithium	+	81	131	4330	1.5	134	100	•
	8040	Xenon	4 x C-cell Alkaline		67	198	9820	5.15	286	520	•
	8050	Xenon	4 x C-cell NiCAD Rechargeable	10	137	234	13707	1.5	286	510	••
	2330	LED	2 x CR123 Lithium	+	100	93	2184	6	140	160	•
	2360	LED	2 x AA Alkaline	(Low) (High)	10 110	49 158	615 6242	40 2	155	130	•
	2390	LED	2 x CR123 Lithium	+	177	155	6002	2.5	135	160	••
	3330	LED	2 x CR123 Lithium	+	90	88	1959	4.45	134	100	•
	7060	LED	1 x Lithium-lon Rechargeable	10	160	254	16101	2	220	290	•
	8060	LED	4 x C-cell NiMH Rechargeable	10	179	279	19525	6.45	322	660	•

Product	Model No.	Light Source	Batteries		Key Features	lumens	metres	candelas	hours	Approvals Ex	Length (mm)	Weight with batteries (g)	Colours
	1900Z1	Xenon	2 x AAA Alkaline	+		11	45	571	1.5	Ex II 2G Ex e ib IIB T4 Ex II 2D Ex ibD 21 IP6X T100°C	120	50	••
9	1930Z0	LED	4 x LR 44 Alkaline	+		12	17	70	4.15	Ex II 1G Ex ia IIC T6/T4* (-40°C ≤Ta≤+60°C)	67	30	
	1965Z0	LED	2 x AAA Alkaline	+		21	51	756	4	Ex II 1GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C Da	139	60	••
	2000Z1	Xenon	3 x C-cell Alkaline		0	39	177	7852	6	Ex II 2G Ex e ib IIC T4 Ex II 2G Ex e ib IIC T150°C	198	360	••
4	2010Z0	LED	3 x C-cell Alkaline		0	109	144	5189	32	Ex II 1 G Ex ia IIC T4 Ga	206	380	••
<u> </u>	2220Z1	LED	2 x CR2032 Lithium	+		9	12	38	34	Ex II 2G Ex ib IIC T6	89	30	••
	2340Z1	Xenon	2 x AA Alkaline			6	34	285	6.45	Ex II 2G Ex e ib IIC T4 Tamb = -20°C to +40°C	159	100	•
	2400Z1	Xenon	4 x AA Alkaline		0	38	156	6194	4.5	Ex II 2G Ex e ib IIC T4	165	200	
	2410Z0	LED	4 x AA Alkaline			126	102	2622	7.15	Ex II 1G Ga Ex ia IIC T4 Ex II 1D Da Ex iaD 20 IP66 T83°C	178	210	••
200 A	2460Z1	LED	4 X AA NiMH Rechargeable	+	©	112	99	1583	4.15	Ex II 2G Ex ib IIC T4	178	220	••
0	3610 Z 0	LED	4 x AA Alkaline			126	102	2622	7.15	Ex II 1G Ga Ex ia IIC T4 Ex II 1D Da Ex iaD 20 IP66 T83°C	191	300	•
•	3660Z1	LED	4 X AA NiMH Rechargeable	+	0	112	99	1583	4.15	Ex II 2G Ex ib IIC T4	191	300	••
	3715Z0	LED	4 x AA Alkaline		(Low)	95	175	8051	8.30	Ex II 1G Ex ia IIC T4 Ga	136	410	•
	224272	150	0. 444 411 -11		(High)	174	278	19389	4.45	5 H 40 5 1: H0 T4 0:			
	2610Z0	LED	3 x AAA Alkaline	+	(Low) (High)	30	19 28	91 194	150 19	Ex II 1G Ex ia IIC T4 Ga	38	90	•
	2690Z0	LED	3 x AAA Alkaline	+		60	81	1664	10.5	Ex M1 Ex ia Ma 1 G Ex ia C T4 Ga 1 D Ex ia C T65°C Da P65	71	120	•
	2620	LED (Low)	3 x AAA Alkaline	•	(Low)	9	29	216	80		55	140	
		Xenon (High)		+	(High)	26	44	491	2.15				
	2640	LED (Low)	4 x AA Alkaline		(Low)	9	20	103	50		67	310	
		Halogen (High)		*	(High)	29	46	586	2.45				
	2680	Recoil LED	4 x AA Alkaline	+		69	123	3788	9.5		118	270	•
	2710	LED	2 x AAA Alkaline	+	(Low)	7	14	50	5		66	90	•
		. ==	0 444411 11		(High)	24	34	285	2			400	-
	2720	LED	3 x AAA Alkaline	+	(Low) (High)	5 80	15 56	60 790	175 8		63	130	•
					,				-				

ANSI/NEMA FL 1 STANDARDS

The American National Standards Institute (ANSI) with input from the light industry, have developed performance standards and symbols to effectively communicate a light's features and benefits. The organisation coordinates US standards with international standards so American products can be used globally.



Light Output

Light Output is the total luminous flux. It is the total quantity of emitted overall light energy as measured by integrating the entire angular output of the portable light source. Light output in this standard is expressed in units of lumens.



Run Time

Run Time is defined as the duration of time from the initial light output value – defined as 30 seconds after the point the device is first turned on – using fresh batteries, until the light output reaches 10% of the initial value.



Peak Beam Intensity


Peak Beam Intensity is the maximum luminous intensity typically along the central axis of a cone of light. The value is reported in candela and does not change with distance.



Beam Distance

Beam Distance is defined as the distance from the device at which the light beam is 0.25 lux (0.25 lux is approximately the equivalent of the light emitted from the full moon "on a clear night in an open field").















MITYLITE™ ZONE 1

Cat No. 1900Z1

- Compact, pocket torch
- Twist on/off lens shroud
- High performance Xenon lamp module
- Shirt clip
- 2 x AAA batteries (included)



L1 LED ZONE 0

Cat No. 1930Z0

- End switch for momentary "blink" or constant "on" modes
- Lanyard with breakaway safety feature
- Pocket clip for easy attachment
- 4 x LR 44 1.5 coin cells (included)



MITYLITE™ 2AAA LED ZONE O

Cat No. 1965Z0

- Compact LED pocket torch
- Corrosion-proof polymer body
- Clip for easy attachment
- Lightweight just 60g (inc. batteries)
- 2 x AAA batteries supplied



SABRELITE™ ZONE 1

Cat No. 2000Z1

- Beam pierces smoke & fog
- Twist on/off lens shroud
- Rugged body with a hi-impact polycarbonate lens
- Adjustable wrist lanyard
- Clip for easy attachment
- 3 x C-cells (not included)



SABRELITE™ ZONE 0 LED

Cat No. 2010Z0


- Powerful 109 lumen beam
- Twist on/off shroud
- Rugged lightweight resin body
- Adjustable lanyard
- 3 x C-cells (not included)



VB3™ LED ZONE 1

Cat No. 2220Z1

- Head flips up to activate LEDs
- Head tilts 180° to aim light where you need it
- Excellent battery efficiency
- 2 x CR2032 3v coin cells (included)



MITYLITE™ 2340 ZONE 1

Cat No. 2340Z1

- Push button on/off tail switch
- Xenon beam
- Compact, hand torch
- 2 x AA batteries (not included)





For use in hazardous areas – an area in which special precautions are required when using electrical equipment due to the presence or chance of explosive atmospheres.

All models in this range comply with the ATEX directives and are certified to ATEX Zone 0 (Category 1) or Zone 1 (Category 2).

Certain models are also certified for Dust Zones 20 and 21.

The wide choice includes hands-free, rechargeable and helmet mountable versions.





STEALTHLITE™ ZONE 1

- Cat No. 2400Z1
- One-handed safety switch
- Helmet mountable
- Adjustable wrist lanyard
- 4 x AA batteries (not included)



STEALTHLITE™ ZONE O LED

Cat No. 2410Z0

- Powerful LED
- One-handed safety switch
- Rugged body and polycarbonate lens
- Adjustable lanyard
- 4 x AA batteries (not included)



STEALTHLITE™ RECHARGEABLE

Cat No. 2460Z1

- One handed safety switch operation
- Rugged body with polycarbonate lens
- Smart Charger base with 240v charger and high-capacity industrial NiMh battery pack



LITTLE ED™ ZONE O LED

Cat No. 3610Z0

- LED produces 126 lumen beam
- One handed safety switch operation
- Rugged body with polycarbonate lens
- Powerful right-angled light
- Stainless steel clip for hands-free use
- 4 x AA batteries (not included)



LITTLE ED™RECHARGEABLE LED

Cat No. 3660Z1

- Powerful right-angled light
- Drop-in Smart Charger base with 240v charger hi-capacity NiMh battery pack
- One handed safety switch operation
- Rugged body with polycarbonate lens
- Stainless steel clip for hands-free use



ZONE O LED

Cat No. 3715Z0

- Secure clip allows hands-free use
- 4 light modes: High/Low/Downcast/Signaling
- Up to 8.5 hours of battery run time (low setting)
- Lightweight at 400g yet tough ABS body
- Up to 174 lumens of LED brightness
- 4 mode battery level indicator
- Locking wheel securely holds 4 x AA batteries (not included)



HEAD TORCHES

Peli[™] Heads Up Lites[™] offer high quality, lightweight head torches for hands-free light. The range includes LEDs and a combination of LEDs with either Xenon or Halogen lamps. All models include a cloth strap to wear directly on the head as well as a rubber strap for helmet/hard hat use.

HEADS UP LITE™

Cat No. 2620

- Multi angle pivoting head
- Dual mode beams:-
 - 3 LEDs (Low) or 1 Xenon lamp (High)
- Push button low/high or on/off switch
- Up to 80 hours of LED light
- 3 x AAA batteries (included)



HEADS UP LITE™

Cat No. 2640

- Dual mode beams:-
- 3 LEDs (Low) or 1 Halogen (High)
- High/Low side switch
- Up to 50 hours battery burn time
- · Pivoting head directs light
- 4 x AA batteries (included)





HEADS UP LITE™ ZONE O

Cat No. 2610Z0

- Dual mode LED headlight:-
- 1 LED (Low) or 3 LEDs (High)
- Push button switch
- Lightweight just 90 grams
- 3 x AAA batteries (included)



HEADS UP LITE™ ZONE 0

Cat No. 2690Z0

- Easy twist bezel switch for gloved hand operation
- 90° pivoting head directs the light where required
- Compact, lightweight LED headlamp
- Powerful 60 lumen beam
- 3 x AAA batteries (included)



HEADS UP LITE™

- Recoil LED™ Technology
- On/off side switch
- Rugged and Waterproof
- Powerful 69 lumen beam
- 4 x AA batteries (included)



LED HEADLIGHT

Cat No. 2710

- Main light high intensity LED
- 4 x optical magnification for wide penetrating beam
- Low level red or green light to preserve night vision
- Signaling red (SOS) and white beacon light
- 2 x AAA batteries (included)



LED HEADLIGHT

- Motion sensor activation
- Variable light output
- Low level red light that preserves night vision
- Signaling red (SOS) beacon light
- Optical 4 x magnification allows for wide penetrating beam
- 3 x AAA batteries (included)







ACCESSORIES

TRAFFIC WANDS

Traffic wands attach to torch head shroud.

- Small (available in Orange) fits the 2320 M6 and 3320 PM6 also the 2330 & 3330 LEDs.
- Medium fits the 7060 LED and is available in Yellow or Orange.
- Large fits the 8040 M10, 8050 M11, 8060 LED and the SabreLite[™] series and is available in Yellow or Orange.



HELMET TORCH CLIPS

Peli™ Helmet Clips are designed for the most popular helmet brands (contact us for details).

Tough polymer construction with brass inserts and stainless steel hardware.

Fits the following Peli™ Torches:

- M6 2320
 M6 2330 LED
- MityLite[™] 2340Z1
 M6 3W 2390 LED
- StealthLite™ 2400/2400Z1
- StealthLite[™] 2410/2410Z0 LED
- StealthLite[™] Rechargeable 2450
- StealthLite™ Rechargeable 2460/2460Z1 LED
- PM6 3320 PM6 3330 LED









0730 clip – attaches the **1930** L1 torch to various hard hats.

PELI™ UNIVERSAL HELMET CLIP

This durable clip fits the following Peli™ Torches:

- 1900/1900Z1 MityLte™
- 1965 MityLIte™ LED
- 1930/1930 Z0 L1 LED
- 2340 MityLite™
- 2400/2400Z1 Stealthlite[™]
- 2410/2410Z0 StealthLite™ LED
- 2450 StealthLite™ Rechargeable
- 2460/2460Z1 StealthLite[™] LED rechargeable models







CUSTOM LABELLING

We also offer custom labelling – please contact us for further details.



Full range of **Peli™ Protector Cases** and **Area Lighting Systems** are also available.

*Please contact us for more details.













Tel: +44 (0)191 490 1547

Fax: +44 (0)191 477 5371

Email: northernsales@thorneandderrick.co.uk

Website: www.cablejoints.co.uk

www.thorneanderrick.co.uk

© 2012 Peli Products (UK) Ltd All trademarks and logos displayed herein are registered and unregistered trademarks of Peli Products, S.L. and others.