



Plymouth Rubber Europa S.A

# 44 Neoprene Jacketing Tape

## For Permanent Cable Jacketing

- Self-amalgamating
- Excellent conformability
- Flame Resistant
- Resists acids and chemicals
- Resists oils, grease and hydrocarbons
- Protects against ozone, heat, moisture and sunlight
- Limited storage life (9 months)

**RECOMMENDED USES:** As a jacketing tape for use on neoprene jacketed cables and for corrosion protection on lead splicing sleeves.

### STANDARD SIZES:

- 3/4 in.x 30 ft.  
19mm x 9m
- 1 in. x 30 ft.  
25mm x 9m
- 1 1/2in. x 30 ft.  
38mm x 9m
- 2 in. x 30 ft.  
51mm x 9m

**DESCRIPTION:** 44 Neoprene is a self-amalgamating neoprene jacketing tape especially formulated for protecting cables against oil, grease and other hydrocarbons. It is chemical and weather resistant and readily conforms to to irregular contours forming a permanent and lasting protective outer sheath.

## SPECIFICATIONS:

Property	Value	Unit	Test Method
Physical			
Color	Black	---	---
Thickness	0,76	mm	ASTM D 4325
	0.030	inch	ASTM D 4325
Tensile Strength	450	psi	ASTM D 4325
	3,1	MPa	ASTM D 4325
Elongation	450	%	ASTM D 4325
Fusion	2 Max.	mm	ASTM D 4325
	5/64 Max.	inch	ASTM D 4325

Chemical			
Ozone Resistance	Pass	Visual	ASTM D 4325
Weathering	100	Hour	Mil R900A
Acid and Alkali	Pass	Visual	*BTM 814
Flammability	5 Max.	mm	UL44
	2 Max.	inch	UL44

Electrical			
Dielectric Strength	17,7	kV/mm	ASTM D 4325
	450	V/mil	ASTM D 4325
Dielectric Constant	5,8	---	ASTM D 4325
Dissipation Factor	0,01	---	ASTM D 4325
Volume Resistivity	$9,5 \times 10^{12}$	ohm · cm	ASTM D 4325

\*BTM - denotes Plymouth Test Method where no industry standard is applicable. Details available upon request. Data in table represent average test results and are not to be used for specifications. The product user should make his/her own tests to determine the product's suitability for the intended use.

Plymouth warrants that its Product will substantially conform to that products written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment. (Unless provided otherwise in the product data sheet). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products



**T&D THORNE & DERRICK UK**

Tel: +44 (0)191 490 1547  
Fax: +44 (0)191 477 5371  
Email: [northernsales@thorneandderrick.co.uk](mailto:northernsales@thorneandderrick.co.uk)  
Website: [www.cablejoints.co.uk](http://www.cablejoints.co.uk)  
[www.thorneandderrick.co.uk](http://www.thorneandderrick.co.uk)