

Electrical & Utility Products



Vinyl Tapes

Friction Tapes

Rubber Tapes

**Mastics Water
Seal**

**Special Purpose
Products**

**Splice &
Termination Kits**

Plymouth



Vinyl Electrical Tape

Plymouth



PREMIUM 111

A 7 mil (0,18mm) all weather, professional grade, pressure sensitive vinyl tape which gives excellent performance over a wide range of temperatures. Cold and weather resistant. Flame retardant. Premium 111 can be used as primary insulation for splices at not more than 600 Volts. Use as protective outer jacket over splices and all low temperature applications. UL 510, ASTM-D-3005, HH-I-595C. Lead-free.

PREMIUM 85 CW

An 8.5 mil (0,21mm) all weather, professional grade, pressure sensitive vinyl tape that provides heavier thickness for added mechanical and electrical protection. Cold and weather resistant. Flame retardant. Premium 85 CW can be used as primary insulation for splices at not more than 600 Volts. Excellent protective jacket over all types of splices. Excellent cold weather performance. UL 510, ASTM-D-3005, MIL-I-24391C.

PREMIUM 37 Color Coding

A 7 mil (0,18mm) all weather, professional grade, pressure sensitive vinyl tape that is available in nine colors for color coding and insulating. Cold and weather resistant. Flame Retardant. Use Premium 37 for quick identification of electrical circuits, containers, and conduit systems, as well as primary insulation for splices at not more than 600 volts. UL 510, ASTM-D-3005, HH-I-595C. Lead-free.

HD 2 (Heavy Duty Electrical Tape)

A 10 mil (0,25mm) heavy duty, general purpose, pressure sensitive vinyl tape for all types of mechanical and electrical applications. Additional thickness allows for quicker build-ups and added abrasion protection. HD 2 is flame retardant and can be used as primary insulation for splices at not more than 600 volts., ASTM-D-2301, MIL-I-7798A.

PLYWRAP® 11 (10 mil) Vinyl Pipewrap

A corrosion protection, pressure sensitive vinyl tape giving complete environmental, mechanical and electrical protection for all types of pipe-wrapping applications. UV, bacteria and fungus resistant, Plywrap 11 tape can be used for both overhead and direct burial applications. Fed. Spec. L-T-001512.

Vinyl Electrical Tape

PREMIUM 111

Cat.	Color	Dimensions	Packaging	Weight
4453	black	3/4" x .007" x 66'	100/case PC	24 lbs 11 kg
4452	black	3/4" x .007" x 66'	100/case C	24 lbs 11 kg

PREMIUM 85 CW

Cat.	Color	Dimensions	Packaging	Weight	
4240	black	3/4" x .0085" x 66'	19mm x 0,21mm x 20m	100/case PC	28 lbs 13 kg
4252	black	1 1/2" x .0085" x 66'	38mm x 0,21mm x 20m	100/case C	38 lbs 17 kg
4273	black	1 1/2" x .0085" x 108'	38mm x 0,21mm x 33m	50/case C	38 lbs 17 kg
4311	black	2" x .0085" x 66'	51mm x 0,21mm x 20m	40/case C	28 lbs 13 kg
4243	black	3/4" x .0085" x 66'	19mm x 0,21mm x 20m	100/case C	23 lbs 10 kg

PREMIUM 37 Color Coding (Plastic Can)

Cat.	Color	Dimensions	Packaging	Weight	
3702	green	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3703	yellow	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3704	red	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3705	blue	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3706	white	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3707	brown	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3708	orange	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3709	grey	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg
3711	violet	3/4" x .007" x 66'	19mm x 0,18mm x 20m	20/case PC	51 bs 2 kg

Premium 37 Color Coding (Cello+Label)

Cat.	Color	Dimensions	Packaging	Weight	
8756	green	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8754	yellow	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8751	red	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8753	blue	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8752	white	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8757	brown	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8759	orange	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8755	grey	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg
8758	violet	3/4" x .007" x 66'	19mm x 0,18mm x 20m	100 case C	21 lbs 10 kg

HD 2

Cat.	Color	Dimensions	Packaging	Weight	
8724	black	2" x .010" x 108'	50mm x 0,25mm x 33m	40/case C	46 lbs 21 kg

PLYWRAP® 11 (10 mil)

Cat.	Color	Dimensions	Packaging	Weight	
4610	black	1" x .010" x 100'	51mm x 0,25mm x 30m	48/case C	26 lbs 12 kg
4611	black	2" x .010" x 100'	50mm x 0,25mm x 30m	24/case C	26 lbs 12 kg

Friction and Duct Tapes



100 ASTM Friction Tape

A high quality cotton fabric coated on both sides with a black rubber adhesive compound which provides good adhesion to all types of surfaces. A 15 mil (0,38mm) general purpose tape that provides excellent protection against abrasion. ASTM-D-4514, Comm. Spec. 6747, HHT 101A.

170 BROWN Friction Tape

A high quality cotton fabric coated on both sides with a brown rubber adhesive compound which provides good adhesion to all types of surfaces. Distinctive natural rubber color, excellent tack. Provides excellent protection against abrasion for cable and splices.

PLYDUCT® 48 - Premium Grade Cloth Duct Tape

A premium duct tape that provides excellent adhesion to all types of surfaces. Laminated cloth construction provides superior mechanical strength and will conform to irregular surfaces. Use for sealing joints on all types of duct work. Excellent for heavy duty applications.

100 ASTM Friction Tape

Cat.	Color	Dimensions		Packaging	Weight
1004	black	3/4" x .015" x 30'	19mm x 0,38mm x 9m	200/case C	34 lbs 15 kg
1002	black	3/4" x .015" x 60'	19mm x 0,38mm x 18m	100/case C	29 lbs 13 kg
1038	black	1 1/2" x .015" x 60'	38mm x 0,38mm x 18m	50/case C	29 lbs 13 kg
1039	black	2" x .015" x 60'	51mm x 0,38mm x 18m	40/case C	31 lbs 15 kg
1012	black	3/4" x .015" x 82.5'	19mm x 0,38mm x 25m	100/case C	44 lbs 20 kg
1047	black	1 1/2" x .015" x 82.5'	38mm x 0,38mm x 25m	50/case C	36 lbs 19 kg

170 Brown Friction Tape

Cat.	Color	Dimensions		Packaging	Weight
1008	brown	3/4" x .0015" x 70'	19mm x 0,38mm x 21m	100/case C	36 lbs 16 kg
1057	brown	2" x .015" x 70'	51mm x 0,38mm x 21m	40/case C	40 lbs 18 kg
1077	brown	1" x .015" x 70'	25mm x 0,38mm x 21m	80/case C	40 lbs 19 kg

PLYDUCT® 48 - Premium Grade Cloth Duct Tape

Cat.	Color	Dimensions		Packaging	Weight
3150	grey	2" x 60 yds.	51mm x 55m	24/case C	39 lbs 17 kg

Low Voltage Rubber Tape



122 Rubber Tape - Splicing Compound

A 30 mil (0,76mm) UL listed, self-amalgamating, low voltage rubber tape which can be used as primary insulation for splices at not more than 600 volts when used in conjunction with a friction or vinyl jacketing tape. UL 510.

150 ASTM Rubber Tape

A 30 mil (0,76 mm) self-amalgamating, low voltage rubber tape that can be used for insulating cable splices through 2kV, in conjunction with a jacketing tape. Compatible with low and high density polyethylene and polypropylene PIC cables plus all rubber and PVC cable elements. 150 ASTM conforms easily and self-amalgamates into a homogenous, void-free mass to provide an effective moisture seal. ASTM-D-4388, Communications Industry Specification 6746.

125 Electrical Filler Tape

A 125 mil (3,2mm) self-amalgamating, low voltage insulating compound designed for quick, void-free insulation build-up. 125 can be easily molded by hand to conform to irregular shapes and can be used as primary insulation for splices through 5kV in conjunction with other insulating tapes. 125 is ideal for covering split bolts, padding bus bar edges and connections, and provides an excellent moisture seal. MIL-I-17695A.

PLYFILL Tape

Plyfill is a self-amalgamating low voltage insulating mastic, designed for quick void-free insulation build-up. Plyfill can be easily molded by hand to conform to irregular shapes and can be used as primary insulation for splices through 5 kV in conjunction with other insulating tapes. Plyfill provides an excellent moisture seal.

122 Rubber Tape - Splicing Compound

Cat.	Color	Dimensions		Packaging	Weight
2002	black	3/4" x .030" x 22'	19mm x 0,76mm x 6,7m	100/case C	34 lbs 15 kg
2020	black	2" x .030" x 22'	51mm x 0,76mm x 6,7m	40/case C	35 lbs 16 kg
2004	black	3/4" x .030" x 11'	19mm x 0,76mm x 3,3m	100/case C	18 lbs 9 kg

150 ASTM Rubber Tape

Cat.	Color	Dimensions		Packaging	Weight
2006	grey	3/4" x .030" x 30'	19mm x 0,76mm x 9m	100/case C	52 lbs 24 kg

125 Electrical Filler Tape

Cat.	Color	Dimensions		Packaging	Weight
2074	black	1 1/2" x .125" x 60"	38mm x 3,2mm x 1,5m	10/case B	7 lbs 3 kg

PLYFILL Tape

Cat.	Color	Dimensions		Packaging	Weight
2644	black	1 1/2" x 0,125" x 5'	38mm x 3,2mm x 1,5m	12/case B	4 lbs 2 kg

Insulating Mastics



10 PLYSEAL® Insulating Mastic

A self-amalgamating, insulating mastic for insulating and sealing all types of overhead and direct buried electrical connections up to 600 Volts. 10 Plyseal has superior adhesion to metals, cable insulations, and jackets with no adverse effect on polymeric conducting shields. For watersealing duct work, cable ends, and all types of splices.

4000 PLYSEAL®-V Vinyl Reinforced Insulating Mastic

Used for encapsulating and sealing sub-surface and overhead cases and auxiliary sleeves, ducts, and cable ends. Excellent for sheath and conduit repairs. Impervious to ozone, fresh water, salt water, and soil chemicals. Vinyl film backing provides mechanical strength and abrasion resistance. Plyseal-V is preferred for cold weather applications.

5000 BUS-SEAL EPR-Backed Insulating Mastic

A laminate of W963 Plysafe EPR high voltage tape and 10 Plyseal insulating mastic in a roll form. A one-pass application of this laminate provides high dielectric strength, instant adhesion and excellent conformability. For insulating and water-proofing high voltage bus connectors and conductors. Corrosion protection for junction boxes, bus-duct and cable tray joints. Outer jacket for direct buried high voltage splices. For primary insulation up to 2kV. For bus-bar applications, one half-lapped layer of 5000 Bus-Seal will provide short circuit protection up to 15kV and brush protection up to 25kV.

Rubber Mastic (RM) Tapes

A self-bonding mastic tape consisting of an ethylene propylene rubber (EPR) backing, bonded to a tacky, temperature stable, electrical grade mastic. Use for insulating and moisture sealing splices and terminations on solid dielectric cable. Can be wrapped, stretched or molded around irregular shapes for insulation build-up, water-sealing, and surface protection. Provides excellent electrical properties, superior adhesion, moisture and chemical resistance. For primary insulation up to 2kV.

Vinyl Mastic (VM) Tapes

A self-fusing mastic compound with an all-weather, premium vinyl backing that can be used for insulating and water-sealing electrical connections through 600 volts. Small roll sizes can be stretched and molded around irregular shapes, even in tight locations. Provides excellent electrical properties, superior adhesion, and moisture and chemical resistance. Vinyl backing adds UV protection. Use for insulating overhead and direct buried low voltage connections, motor lead connections, and cable and conduit repair.

WATERSEAL MASTIC

A self-amalgamating, mechanical grade mastic used for sealing and water-proofing. Excellent adhesion to metals, cable insulations, and jackets. Soft, malleable nature makes Waterseal ideal for molding and conforming to irregular shapes. Use in conjunction with Plymouth's premium tapes for optimum performance.

10 PLYSEAL® Insulating Mastic

Cat.	Form	Dimensions		Packaging	Weight
2626	roll	3 3/4" x .125" x 10'	95mm x 3,2mm x 3m	10/case B	31 lbs 14 kg
2627	pad	3 3/4" x .125" x 3 3/4"	95mm x 3,2mm x 95mm	10 pads/bx, 10 bxs/case	9 lbs 4 kg
2628	pad	3 3/4" x .125" x 6 1/2"	95mm x 3,2mm x 165mm	10 pads/bx, 80 bxs/case	17 lbs 8 kg

Insulating Mastics

4000 PLYSEAL®-V Vinyl Reinforced Insulating Mastic

Cat.	Form	Dimensions	Packaging	Weight
2620	roll	4" x .133" x 10' 102mm x 3,4mm x 3m	10/case B	34 lbs 15 kg
2621	pad	4" x .133" x 4" 102mm x 3,4mm x 102mm	10 pads/bx, 10 bxs/case	11 lbs 5 kg
2622	pad	4" x .133" x 6 1/2" 102mm x 3,4mm x 165mm	10 pads/bx, 10 bxs/case	17 lbs 8 kg

5000 BUS-SEAL EPR-Backed Insulating Mastic

Cat.	Form	Dimensions	Packaging	Weight
8371	roll	4" x .155" x 10' 102mm x 3,9mm x 3m	10/case B	36 lbs 16 kg

RUBBER MASTIC (RM) Tapes

Cat.	Form	Dimensions	Packaging	Weight
2619	roll	1 1/2" x .065" x 10' 38mm x 1,65mm x 3m	30/case IB	38 lbs 18 kg
2625	roll	2" x .065" x 10' 51mm x 1,65mm x 3m	30/case B	30 lbs 14 kg
2719	roll	1" x .065" x 10' 25,4mm x 1,65mm x 3m	10/case B	5 lbs 2 kg

VINYL MASTIC (VM) Tapes

Cat.	Form	Dimensions	Packaging	Weight
2617	roll	3/4" x .025" x 20' 19mm x 0,635mm x 6m	80/case B	29 lbs 13 kg
2618	roll	1 1/2" x .025" x 20' 38mm x 0,635mm x 6m	40/case C	26 lbs 11 kg
2609	roll	4" x .050" x 10' 100mm x 1,3mm x 3m	10/case B	13 lbs 6 kg

WATERSEAL MASTIC

Cat.	Form	Dimensions	Packaging	Weight
2856	pad	2 1/2" x .125" x 2' 64mm x 3,2mm x 610mm	40 pads/case IB	17 lbs 8 kg

Low Voltage Splice Kits



SPLICE WRAP™ One-Step Splice Kit

For insulating and water-proofing direct burial or overhead splices and terminations through 2000V. For cable jacket repair and restoration, and ground seal for shielded power cable. Suitable for straight and branch joints. Easy 1-step application. Connectors not included.

SPLICEWRAP One-Step Splice Kit

Cat.	Range	Packaging	Weight
8910	up to 500 kCMIL	20/case B	6 lbs. 3 kg

High Voltage Tape

Plymouth



L969 PLYVOLT™ Linerless High Voltage Insulating Tape

A 30 mil (0,76mm) EPR , self-bonding high voltage tape for insulating and jacketing splices through 69kV. L969 Plyvolt is linerless, and permits quicker application than a tape with liner. Yields a void-free build-up. Excellent corona, ozone, and chemical resistance. L969 Plyvolt can also be used for building stress-cones on power cable through 35kV. ASTM-D-4388, HH-I-553C.

W963 PLYSAFE® High Voltage Insulating Tape with Liner

A 30 mil (0,76mm) EPR, self-amalgamating high voltage tape for insulating and jacketing splices through 69kV. W963 Plysafe amalgamates quickly, yielding a void-free, electrically stable build-up and is ideal for water-proofing. ASTM-D-4388, HH-I-553C/Grade A, MIL-I-3825B.

3 BI-SEAL® High Voltage Insulating Tape with Liner

A polyethylene and ethylene propylene rubber based tape possessing superior electrical, chemical, mechanical and thermal properties. Fuses quickly, yielding a void-free, electrically stable build-up. For insulating and jacketing of splices on power cable from 600 volts through 69kV and for building stress cones and jacketing of terminations on power cable from 600 volts through 35kV. Available in 20 mil (0,51mm) or 30 mil (0,76mm) thickness. ASTM-D-4388, HH-I-553C.

W962 High Voltage Insulating Tape With Liner

20 mil (0,51mm) EPR based high voltage tape with superior electrical, chemical, mechanical, and thermal properties. For insulating and jacketing of splices on power cable from 600 volts through 138kV and for building stress cones and jacketing of terminations on power cable from 600 volts through 35kV. W962 is self-amalgamating. ASTM-D-4388.

PIB Medium Voltage Tape with Black Liner

A self-amalgamating, polyisobutylene-based medium voltage tape that maintains a tight insulation build-up for void-free electrical stability and permanent resistance to moisture penetration. For insulating and jacketing of splices on power cables from 600 volts through 46kV. Plymouth's PIB has excellent stretch capabilities that allow fast taping speeds and is compatible with all extruded dielectrical cable insulations.

17 PLYSHIELD® EPR Shielding Tape

A 30 mil (0,76mm) EPR self-amalgamating, conducting tape for shielding high voltage splices and terminations. Use for rebuilding strand shield and insulation shields on high voltage splices and for shielding all types of connections. ASTM-D-4388.

15 PLYBRAID Tinned Copper Shielding Tape

A tinned copper mesh-knit shielding with exceptional conformability for replacing metallic shield in shielded cable repair. The two-inch width allows for quicker application and a larger overlap for increased safety in flexible cables.

PLYSTRAP® Tinned Copper Ground Braid

A woven tinned copper braid used for grounding high voltage splices and terminations. Also used for shield continuation on splices. Plystrap has current carrying capacity of #9 AWG solid copper.

High Voltage Tape

L969 PLYVOLT™ Linerless High Voltage Insulating Tape

Cat.	Dimensions	Packaging	Weight
2211	3/4" x .030" x 30'	19mm x 0,76mm x 9m	100/case B 38 lbs 18 kg
2212	1" x .030" x 30'	25mm x 0,76mm x 9m	80/case B 41 lbs 19 kg
2213	1 1/2" x .030" x 30'	38mm x 0,76mm x 9m	50/case B 36 lbs 16 kg
2214	2" x .030" x 30'	51mm x 0,76mm x 9m	40/case C 37 lbs 17 kg

W963 PLYSAFE® High Voltage Insulating Tape with Liner

Cat.	Dimensions	Packaging	Weight
2117	3/4" x .030" x 30'	19mm x 0,76mm x 9m	100/case B 46 lbs 21 kg
2132	1" x .030" x 30'	25mm x 0,76mm x 9m	80/case B 47 lbs 22 kg
2134	1 1/2" x .030" x 30'	38mm x 0,76mm x 9m	50/case B 43 lbs 20 kg
2145	2" x .030" x 30'	51mm x 0,76mm x 9m	40/case C 44 lbs 20 kg

3 BI-SEAL® High Voltage Insulating Tape with Liner

Cat.	Dimensions	Packaging	Weight
8051	3/4" x .020" x 30'	19mm x 0,51mm x 9m	100/case B 44 lbs 20 kg
8052	1" x .020" x 30'	25mm x 0,51mm x 9m	80/case B 42 lbs 21 kg
8053	1 1/2" x .020" x 30'	38mm x 0,51mm x 9m	50/case B 40 lbs 18 kg
8054	2" x .020" x 30'	51mm x 0,51mm x 9m	40/case C 41 lbs 19 kg
8065	3/4" x .030" x 30'	19mm x 0,76mm x 9m	100/case B 53 lbs 24 kg
8066	1" x .030" x 30'	25mm x 0,76mm x 9m	80/case B 54 lbs 25 kg
8067	1 1/2" x .030" x 30'	38mm x 0,76mm x 9m	50/case B 52 lbs 24 kg
8068	2" x .030" x 30'	51mm x 0,76mm x 9m	40/case C 53 lbs 24 kg

W962 High Voltage Insulating Tape With Liner

Cat.	Dimensions	Packaging	Weight
8080	3/4" x .020" x 30'	19mm x 0,51mm x 9m	100/case B 44 lbs 20 kg
8081	1" x .020" x 30'	25mm x 0,51mm x 9m	80/case B 46 lbs 21 kg
8082	1 1/2" x .020" x 30'	38mm x 0,51mm x 9m	50/case B 41 lbs 19 kg

PIB Medium Voltage Tape with Black Liner

Cat.	Dimensions	Packaging	Weight
2038	3/4" x .020 x 33'	19mm x 0,51 x 10m	100/case C 21 lbs 10 kg
2039	1" x .020 x 33'	25mm x 0,51 x 10m	80/case C 50 lbs 23 kg

17 PLYSHIELD® EPR Shielding Tape

Cat.	Dimensions	Packaging	Weight
2104	3/4" x .030" x 15'	19mm x 0,76mm x 4,6m	50/case B 13 lbs 6 kg

15 PLYBRAID Tinned Copper Shielding Tape

Cat.	Dimensions	Packaging	Weight
2230	2" x 10'	50mm x 3m	40 rolls/case 8 lbs 4 kg
5415	1" x 15'	25mm x 4,6m	50/case B 7 lbs 3 kg
5416	1" x 100'	25mm x 30m	16/case B 9 lbs 4 kg

PLYSTRAP® Tinned Copper Ground Braid

Cat.	Dimensions	Packaging	Weight
2711	3/8" x 100'	9mm x 30m	1/case B 4 lbs 2 kg

Special Purpose Products

Plymouth



20 PLYSIL® Silicone Rubber Tape

A 20 mil (0,51mm) triangular cross-section, self-amalgamating, silicone rubber tape used for jacketing high voltage terminations on solid dielectric cable through 69kV. 20 PLYSIL is track and erosion resistant and can be used as primary insulation for high temperature (180°C) applications. ASTM-D-2148, MIL-I-46852A.



53 PLYARC® Arc and Fireproofing Tape

A 30 mil (0,76mm) elastomeric tape that provides excellent flame and arc protection for all types of cables. When exposed to flame, 53 PLYARC will generate a thermally insulating residue for cable protection. Use on cable conduit where added fire protection is required. Excellent flexibility and conformability for easy application. Available in grey or in fibre optic orange.



77 PLYGLAS® Pressure Sensitive Glass Cloth Tape

A 7 mil (0,18mm) woven glass fabric tape with a thermosetting rubber based, pressure sensitive adhesive used for insulating and protecting high temperature (130°C) connections, such as motor leads and transformer windings. 77 PLYGLAS has high tensile strength for splice reinforcement and provides excellent tear and abrasion resistance. Use 77 PLYGLAS to hold down 53 PLYARC arc- and fire-proofing tape. Comm. Spec. 7611, ASTM-D-2754, MIL-I-15126F/GFT.




61 and 61A Varnished Dacron-Glass Tape

61 and 61A Varnished Dacron-Glass Tapes are a fine weave of Dacron and fiber glass threads, impregnated with a fully cured polyester coating which provides excellent electrical and mechanical protection. The tapes are intended for use to 155°C and have good flexibility to allow tight taping of irregular shapes. Available without adhesive (61-7mils[18mm]) and with adhesive (61A - 8mils [20mm]).



44 NEOPRENE Jacketing Tape

A 30 mil (0,76mm) self-amalgamating neoprene tape specially formulated for permanent protection of cables exposed to oil, grease, and other hydrocarbons. 44 Neoprene is chemical, weather, and flame resistant. Use for corrosion protection on lead splicing sleeves.



PLYPREP™ Cable Preparation Kit

Plyprep is an effective and environmentally friendly cleaning kit for the proper preparation of both high and low voltage cables prior to splicing or terminating. Very effective for removing grease, oil, tar, and other contaminants from cables. Kits have everything necessary to prepare cables for a splice or termination. Each kit contains three sealed wipe sets and one 120 grit non-conducting abrasive cloth.



TERMINAL WRAP

Use for terminating three-core shielded cables for motor leads. Each kit contains three rolls of a specially formulated Stress-Wrap 1" (25mm) wide, coreless rolls. Stress-Wrap is a laminate of EPR High Voltage Insulating Tape and a special voltage gradient stress relieving compound. US Patent #4,187,389.

Special Purpose Products

Plymouth

20 PLYSIL® Silicone Rubber Tape

Cat.	Dimensions	Packaging	Weight
3455	1" x .020" x 30' 25mm x 0,51mm x 9m	50/case C	18 lbs 8 kg

53 PLYARC® Arc and Fireproofing Tape

Cat.	Color	Dimensions	Packaging	Weight
3817	Grey	1 1/2" x .030" x 20' 38mm x 0,76mm x 6m	20/case C	12 lbs 5 kg
3819	Grey	3" x .030" x 20' 76mm x 0,76mm x 6m	10/case C	12 lbs 5 kg

77 PLYGLAS® Pressure Sensitive Glass Cloth Tape

Cat.	Dimensions	Packaging	Weight
3451	1/2" x .007" x 66' 13mm x 0,18mm x 20m	50/case B	9 lbs 4 kg
3456	3/4" x .007" x 66' 19mm x 0,18mm x 20m	50/case B	12 lbs 5 kg
3459	1" x .007" x 108' 25mm x 0,18mm x 33m	20/case B	37 lbs 17 kg

61 and 61A Varnished Dacron Glass Tape

Cat.	Dimensions	Packaging	Weight
1101 (without adhesive)	3/4" x .007" x 60' 19mm x 0,18mm x 18m	40/case B	9 lbs 4 kg
1102 (without adhesive)	1" x .007" x 108' 25mm x 0,18mm x 33m	6/case	4 lbs 2 kg
1103 (without adhesive)	1 1/2" x .007" x 108' 38mm x 0,18mm x 33m	6/case B	16 lbs 7 kg
1121 (with adhesive)	3/4" x .008" x 60' 19mm x 0,20mm x 18,2m	40/case B	9 lbs 4 kg
1122 (with adhesive)	1" x .008" x 108' 25mm x 0,20mm x 33m	6/case	4 lbs 2 kg
1123 (with adhesive)	1 1/2" x .008" x 108' 38mm x 0,20mm x 33m	6/case B	16 lbs 7 kg

44 NEOPRENE Jacketing Tape

Cat.	Dimensions	Packaging	Weight
8261	3/4" x .030" x 30' 19mm x 0,76mm x 9m	100/case C	54 lbs 24 kg
8263	1 1/2" x .030" x 30' 38mm x 0,76mm x 9m	50/case C	55 lbs 25 kg
8264	2" x .030" x 30' 51mm x 0,76mm x 9m	40/case C	57 lbs 26 kg

PLYPREP™ Cable Preparation Kit

Cat.	Contents	Packaging	Weight
2684	1 kit/bag	20/case	4 lbs 2 kg

TERMINAL WRAP

Cat.	Range	Packaging	Weight
9012	2-25kV/.55"-.95" dia. 14,1-24,1mm dia.	20/case B	8 lbs 4 kg



Need to Arc and Fireproof Cables?

Plymouth Tape offers multiple solutions to arc and fireproofing, including 53 Plyarc® arc and fireproofing tape.

Termination Kits



COLDTERM™ Cold Shrink Cable Termination Kits - Outdoor/Indoor

An anti-tracking, skirted (outdoor only) silicone rubber termination for tape shielded, wire shielded, JCN and Unishield® cables. Universal kit design fits all extruded dielectric cables. Outdoor models feature unique pull-over tabs for fast and easy installation and superior insulating qualities. Design range covers 5-8kV (3/0 AWG to over 1000kCMIL), 15kV (2 AWG to 5000kCMIL), 25-28kV (2/0 AWG to 1250kCMIL) and 35 kV (1/0 AWG to 1000 KCMIL). Meets IEEE Standard No. 48, Class 1.

Note: kits do not include terminal lugs.

Cat.	Dimensions	Packaging	Weight
Outdoor			
2800	5-15kV, cable insulation o.d. range .637-1.12"	3 terminations/kit, 1 kit/case	3 lbs 1 kg
2801	5-28kV, cable insulation o.d. range .84-1.38"	3 terminations/kit, 1 kit/case	3 lbs 1 kg
2802	5-15kV, cable insulation o.d. range 1.3-2.1"	3 terminations/kit, 1 kit/case	3 lbs 1 kg
2806	5-35kV, cable insulation o.d. range .84-1.38"	3 terminations/kit, 1 kit/case	4 lbs 2 kg
2807	5-35kV, cable insulation o.d. range 1.3-2.1"	3 terminations/kit, 1 kit/case	4 lbs 2 kg
Indoor			
2803	5-15kV, cable insulation o.d. range .637-1.12"	3 terminations/kit, 1 kit/case	3 lbs 1 kg

Cat. No.	Cable Insulation O.D. Range	5 kV 100%	5 kV 133% 8 kV 100%	15 kV 100%	15 kV 133%	25/28 kV	35 kV 100%	35 kV 133%
OUTDOOR 2800	.637 - 1.12"	3/0 AWG to 600 kCMIL	1/0 AWG to 500 kCMIL	2 AWG to 350 kCMIL	4 AWG to 250 kCMIL	N/A	N/A	N/A
	1,62 - 2,84 cm	85 sq mm to 304 sq mm	53 sq mm to 253 sq mm	34 sq mm to 177 sq mm	21 sq mm to 127 sq mm			
2801	0.84 - 1.38"	350 kCMIL to 1000 kCMIL	250 kCMIL to 750 kCMIL	3/0 AWG to 600 kCMIL	1/0 AWG to 500 kCMIL	2 AWG to 400 kCMIL	N/A	N/A
	2,13 - 3,51 cm	177 sq mm to 507 sq mm	127 sq mm to 380 sq mm	85 sq mm to 304 sq mm	53 sq mm to 253 sq mm	34 sq mm to 203 sq mm		
2802	1.3 - 2.1"	Over 1000 kCMIL	750 kCMIL to 2000 kCMIL	600 kCMIL to 1500 kCMIL	500 kCMIL to 1500 kCMIL	400 kCMIL to 1250 kCMIL	N/A	N/A
	3,30 - 5,33 cm	Over 507 sq mm	380 sq mm to 1013 sq mm	304 sq mm to 760 sq mm	253 sq mm to 760 sq mm	203 sq mm to 633 sq mm		
2806	0.84 - 1.38"	350 kCMIL to 1000 kCMIL	250 kCMIL to 750 kCMIL	3/0 AWG to 600 kCMIL	1/0 AWG to 500 kCMIL	2 AWG to 400 kCMIL	1/0 AWG to 250 kCMIL	1/0 AWG to 2/0 AWG
	2,13 - 3,51 cm	177 sq mm - 507 sq mm	127 sq mm - 380 sq mm	85 sq mm to 304 sq mm	53 sq mm to 253 sq mm	34 sq mm to 203 sq mm	53 sq mm to 127 sq mm	53 sq mm to 67 sq mm
2807	1.32 - 2.1"	1000 kCMIL to 2500 kCMIL	750 kCMIL to 2000 kCMIL	600 kCMIL to 1500 kCMIL	500 kCMIL to 1500 kCMIL	400 kCMIL to 1250 kCMIL	250 kCMIL to 1000 kCMIL	2/0 AWG to 1000 kCMIL
	3,30 - 5,53 cm	507 sq mm - 1263 sq mm	380 sq mm to 760 sq mm	304 sq mm to 760 sq mm	253 sq mm to 760 sq mm	203 sq mm to 633 sq mm	127 sq mm to 507 sq mm	67 sq mm to 507 sq mm
INDOOR 2803	.637 - 1.12"	3/0 AWG to 600 kCMIL	1/0 AWG to 500 kCMIL	2 AWG to 350 kCMIL	4 AWG to 250 kCMIL	N/A	N/A	N/A
	1,62 - 2,84 cm	85 sq mm to 304 sq mm	53 sq mm to 253 sq mm	34 sq mm to 177 sq mm	21 sq mm to 127 sq mm			