

Mining Products Jacketing and Insulating Tapes

Plymouth

PLYTUFF® - F/R PVC Jacketing Tape

PVC tape specifically formulated for flame resistance and abrasion resistance. Use for repairing nicks and tears in all mining cables. Use this tape for primary insulation through 600V. Ideally suited for securing premolded and shrinkable sleeve ends to the cable jacket. Title 30-CFR 18.64, P-153-MSHA Acceptance.

GLF® Jacket Repair Wrap

Use as a jacket repair or conduit repair when severe conditions tear or puncture the original cable jacket or conduit. Extremely abrasion-resistant, with excellent moisture exclusion properties. Approved under 30 CFR 7.404, approval number P-7K-SK-153082-1-MSHA.

NEW GLF2® Jacket Repair Wrap

Is our newest laminate of a specially formulated Hypalon backing and 2 flame-retardant mastic layers possessing the superior abrasion and moisture resistance required for all types of cable jacket repair. The laminate is easy to apply and remains flexible at low temperatures. GLF 2 will adhere to all types of cable jackets yielding a positive moisture seal. GLF 2 with approval number P-7K-SK-153082-1-MSHA.

L969 Fire-Resistant Insulating Tape (Linerless Rubber)

Use to insulate around the connector area on splices from 600V-69kV. Also used to fill in irregularities and to smooth out the splice profile before applying jacketing tape.

Rubber Mastic (RM) Tapes

A self-bonding mastic tape consisting of an ethylene propylene rubber (EPR) backing, bonded to a tacky, temperature stable, electrical grade mastic. Use for insulating and moisture sealing splices and terminations on solid dielectric cable. Can be wrapped, stretched or molded around irregular shapes for insulation build-up, water-sealing, and surface protection. Provides excellent electrical properties, superior adhesion, moisture and chemical resistance. For primary insulation up to 2kV.

PLYTUFF® - F/R PVC Jacketing Tapes

| Cat. | Dimensions | Packaging | Weight |
|------|--|------------|--------------|
| 3880 | 3/4" x .007" x 66' 19mm x 0,18mm x 20m | 100/case C | 23 lbs 10 kg |
| 3881 | 1 1/2" x .007" x 66' 38mm x 0,18mm x 20m | 100/case C | 43 lbs 20 kg |
| 3897 | 1 1/2" x .007" x 44' 38mm x 0,18mm x 13m | 100/case C | 31 lbs 14 kg |

GLF® Jacket Repair Wrap

| Cat. | Dimensions | Packaging | Weight |
|------|---------------------------------------|-----------|-------------|
| 2563 | 2" x .075" x 6' 51mm x 1,3mm x 1,8m | 30/case C | 17 lbs 8 kg |
| 2564 | 2" x .075" x 8.5' 51mm x 1,3mm x 2,6m | 20/case C | 16 lbs 7 kg |

GLF2® Jacket Repair Wrap (With extra layer of adhesive)

| Cat. | Dimensions | Packaging | Weight |
|------|------------------------------|-----------|--------------|
| 2501 | 2 in x 7 ft. 51mm x 2,15 m | 30 / Case | 30 lbs 14 kg |
| 2502 | 2 in x 9.5 ft. 51mm x 2,90 m | 30 / Case | 30 lbs 14 kg |

L969 Fire Resistant Insulating Tape (Linerless Rubber)

| Cat. | Dimensions | Packaging | Weight |
|------|---|-----------|--------------|
| 2221 | 1 1/2" x .030" x 30' 38mm x 0,76mm x 9m | 50/case C | 31 lbs 14 kg |

RUBBER MASTIC (RM) Tapes

| Cat. | Form | Dimensions | Packaging | Weight |
|------|------|---|------------|--------------|
| 2625 | roll | 2" x .065" x 10' 51mm x 1,65mm x 3m | 30/case B | 30 lbs 14 kg |
| 2619 | roll | 1 1/2" x .065" x 10' 38mm x 1,65mm x 3m | 30/case IB | 38 lbs 18 kg |

T&D THORNE & DERRICK UK

Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk