



Plymouth Rubber Europa S.A

Rubber Mastic (RM)

**Self-Bonding
Mastic Tape**

Description

A self-bonding mastic tape consisting of an ethylene propylene rubber (EPR) backing, bonded to a tacky, temperature stable, electrical grade mastic. Use for insulating and moisture sealing splices and terminations on solid dielectric cable. Provides excellent electrical properties, superior adhesion, moisture and chemical resistance. For primary insulation up to 2kV. ASTM-D-4388.

Recommended Uses

Use for insulating and moisture-sealing splices and terminations on solid dielectric cable. Can be wrapped, stretched or molded around irregular shapes for insulation build-up, water-sealing, and surface protection. Ideal for Bus Bar insulation and corrosion protection.

Specifications

Property	Value	Unit	Reference
Physical			
Thickness	0.065	inch	ASTM-D-4388
	1.65	mm	
Dielectric Strength	400	V/mil	ASTM-D-4388
Water Absorption	0.10	%	ASTM-D-570
UV Resistance	Pass	Visual	ASTM-D-4388
Ozone Resistance	Pass	Visual	ASTM-D-4388
Operating Temperature			
Continuous	90	°C	
Emergency Overload	130	°C	

Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use.

Features

- Excellent electrical properties
- Superior adhesion
- UV resistant
- Moisture, corrosion, and chemical resistant
- Suitable for direct burial and overhead applications

Product Approvals

- ASTM-D-4388

Standard Sizes

- 1 1/2" x .065" x 10'
38mm x 1,65mm x 3m
- 2" x .065" x 10'
51mm x 1,65mm x 3m
- 1" x .065" x 10'
25,4mm x 1,65mm x 3m

Consult factory for other sizes



LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment, (Unless provided otherwise in product's data sheet). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (rev. 1/95)

**T&D THORNE &
DERRICK UK**

Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northersales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk