

PRODUCT DATASHEET

Prolab[®] Standard Laser Wrap-around Cable Labels



This is a multipage document, all pages must be read in conjunction with each other



The Silver Fox Prolab[®] Standard wrap-around cable labels are self-laminating and can be printed using a standard office laser printer.

The labels incorporate a highly opaque printable area ensuring excellent levels of clarity for your message whatever the colour of the cable.

The clear 'tail' on the label wraps around the cable and the printable area giving additional protection to the message printed.

Available in packs of 10 or 100 sheets.

TECHNICAL DATA

Printing Method	Standard Laser Printer
Material	Self-adhesive Matt Polyester
Thickness	25 microns
Sheet Size	A4
Standard Colours	See order information
RoHS (EU 2002/95/EC)	RoHS Compliant

PRODUCT TESTING

Test	Method
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4
High Temperature 1000 hours @ 85°C	MIL-STD-202G Method 108A
Hydrogen Sulphide	H ₂ S Sour Gas Exposure (2% H ₂ S)
UV Weathering 500 hours*	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

* Limited external applications generally away from direct sunlight. Labels generally for internal use such as data centres, banks, hotels, airports etc.

Please note that all tests were performed on white wrap-around label.

FEATURES & BENEFITS

- Print using a standard office laser printer
- Pre-cut for rapid removal from sheet
- Wide choice of sizes, fit cable
OD Ø 5mm - 20mm
- Self-laminating for additional protection
- To help you identify the label size you require, the maximum cable ODØ diameter and printable area are included in the order code

e.g.: P08/2512L

Cable ODØ = 8mm
Printable area = 25mm x 12mm



PRODUCT DATASHEET

Prolab[®] Standard Laser Wrap-around Cable Labels



This is a multipage document, all pages must be read in conjunction with each other



STORAGE INSTRUCTIONS


Storage Instructions	Store between 50° F (10° C) and 77° F (25° C)
Shelf Life	2 Years
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

ORDER INFORMATION

Product Code	Cable OD Ø (mm)	Printable Area (mm)	Labels per sheet	Sheets per Pack	Labels per Pack	Colour Options
P05/2508L*	5	25 x 8	80	10 / 100	800 / 8000	<input type="checkbox"/>
P08/1212L*	5 - 8	12 x 12	90	10 / 100	900 / 9000	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
P08/2512L*	5 - 8	25 x 12	48	10 / 100	480 / 4800	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
P08/5012L*	5 - 8	50 x 12	24	10 / 100	240 / 2400	<input type="checkbox"/>
P13/2520L*	5 - 13	25 x 20	32	10 / 100	320 / 3200	<input type="checkbox"/>
P13/5020L*	5 - 13	50 x 20	16	10 / 100	160 / 1600	<input type="checkbox"/>
P17/2525L*	8 - 17	25 x 25	24	10 / 100	240 / 2400	<input type="checkbox"/>
P20/2520L*	10 - 20	25 x 20	24	10 / 100	240 / 2400	<input type="checkbox"/>
P20/5020L*	10 - 20	50 x 20	12	10 / 100	120 / 1200	<input type="checkbox"/>

*Specify colour and pack size when ordering. Please Note: Colours shown are for indicative purposes only – shades may vary.

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE



T&D THORNE & DERRICK UK

Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northernsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk



Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.

Copyright © 2015 Silver Fox Limited

R5.5

Page 2 of 2