


FP600S

FIRE RESISTANT ARMoured POWER CABLE- BS 7846 F120 600/1000 V
ULTIMATE PROTECTION FOR ELECTRICAL EMERGENCY SYSTEMS



Certificate No 077n
Certificate No 517c/01



CABLE DESCRIPTION

Conductor

Plain annealed copper stranded conductor meets the requirements of: BS EN 60228 Class 2

Insulation

Mineral ceramic (Mica/Glass) fire resistant tape. 90°C cross - linked insulation.

Bedding

Extruded LSOH

Armour

Single layer of galvanised steel wires.

Sheath

Extruded LSOH

Key Applications

FP600S is the ultimate fire resistant armoured cable suitable for use in essential emergency systems to retain circuit integrity in the event of fire. Power and control for all life safety and fire fighting systems.

- > Smoke barriers, control dampers, smoke curtains
- > Smoke and heat exhaust ventilation systems
- > Fire fighting and evacuation lift supplies
- > Extinguishing systems - sprinkler pumps, water mist and powder.
- > Wet riser pumps.

British Standards

- > BS 8519 Category 1, 2 and 3 power and control cable
- > BS 8491 120 minutes
- > BS 7846 F120
- > London Underground 1.085 Approved Products Register (Section 12)
- > BASEC and LPCB approved

Core identification

HARMONISED CORE IDENTIFICATION: NON HARMONISED CORE IDENTIFICATION:

○ blue-brown-blue	○ red-black
○ brown-black-grey	○ red-yellow-blue
○ blue-brown-black-grey	○ black-red-yellow-blue

Non harmonised colours to special order.



Temperature Range
-25 to +90°C



Bending Radius
8D



Mechanical Impact
High



Flame Propagation
BS EN 60332-1-2
BS EN 60332-3-24



Flexibility
Rigid



Halogen Free
BS EN 60754-1



Low Smoke Emissions
BS EN 61034-2



Fire Resistance
BS 7846 F120
BS 8491 120 min

Nominal cross sectional area	Approximate overall diameter	Approximate diameter under armour	Nominal diameter of armour wires	Approximate cable weight	Maximum conductor resistance at 20°C	Short circuit rating (1sec) of conductor	Current rating		Volt drop Three phase AC	Recommended accessories	
							Three phase AC clipped direct	Three phase AC Free air or perforated tray			
mm²	mm	mm	mm	kg/km	ohms/km	kA	Amps	Amps	mV/A/m	Claw Cleat Ref No.	Brass Gland Ref No.
Three Core											
4	21	15	1.25	800	4.61	0.57	42	44	10	370CG04	LSF25CW
6	21	15	1.25	820	3.08	0.86	53	56	6.8	370CG04	LSF25CW
10	23	17	1.25	1050	1.83	1.4	73	78	4.0	370CG05	LSF25CW
16	24	19	1.25	1400	1.15	2.2	94	99	2.5	370CG05	LSF25CW
25	29	22	1.6	2000	0.727	3.6	124	131	1.65	370CG06	LSF32CW
35	31	24	1.6	2300	0.524	5.0	154	162	1.15	370CG06	LSF32CW
50	32	25	1.6	2800	0.387	7.1	187	197	0.87	370CG07	LSF32CW
70	36	29	1.6	3600	0.268	10	238	251	0.6	370CG07	LSF40CW
95	40	32	2.0	4500	0.193	13.6	289	304	0.45	370CG08	LSF50SCW
120	43	35	2.0	5400	0.153	17.2	335	353	0.37	370CG08	LSF50SCW
150	48	39	2.5	6900	0.124	21.4	386	406	0.30	370CG09	LSF50CW
185	52	43	2.5	8200	0.0991	26.5	441	463	0.26	370CG09	LSF63CW
240	57	47	2.5	10100	0.0754	34.3	520	456	0.21	370CG10	LSF63CW
300	62	52	2.5	12200	0.0601	42.9	599	628	0.185	370CG12	LSF63CW
400	69	58	2.5	15000	0.0470	57.2	673	728	0.165	370CG13	LSF75CW
Four Core											
4	21	15	1.25	800	4.61	0.57	42	44	10	370CG04	LSF25CW
6	23	17	1.25	950	3.08	0.86	53	56	6.8	370CG05	LSF25CW
10	24	19	1.25	1200	1.83	1.4	73	78	4.0	370CG05	LSF25CW
16	27	20	1.25	1600	1.15	2.2	94	99	2.5	370CG06	
25	32	24	1.6	2400	0.727	3.6	124	131	1.65	370CG07	LSF32CW
35	35	27	1.6	2800	0.524	5.0	154	162	1.15	370CG07	LSF40CW
50	36	29	1.6	3200	0.387	7.1	187	197	0.87	370CG07	LSF40CW
70	41	32	2.0	4500	0.268	10	238	251	0.6	370CG08	LSF50SCW
95	44	36	2.0	5700	0.193	13.6	289	304	0.45	370CG08	LSF50SCW
120	49	40	2.5	7300	0.153	17.2	335	353	0.37	370CG09	LSF50CW
150	55	44	2.5	8600	0.124	21.4	386	406	0.30	370CG10	LSF63CW
185	59	48	2.5	10500	0.0991	26.5	441	463	0.26	370CG11	LSF63CW
240	64	54	2.5	12900	0.0754	34.3	520	546	0.21	370CG12	LSF63CW
300	70	59	2.5	15500	0.0601	42.9	599	628	0.185	370CG14	LSF75CW
400	79	66	3.15	20100	0.0470	57.2	673	728	0.165	370CG15	LSH85CW
Five Core											
4	22	17	1.25	900	4.61	0.57	42	44	10	370CG05	LSF25CW
6	24	18	1.25	1070	3.08	0.86	53	56	6.8	370CG05	LSF25CW
10	27	21	1.25	1390	1.83	1.4	73	78	4.0	370CG06	
16	30	23	1.6	1900	1.15	2.2	94	99	2.5	370CG06	LSF32CW
25	34	26	1.6	2500	0.727	3.6	124	131	1.65	370CG07	LSF40CW
35	37	29	1.6	3100	0.524	5.0	154	162	1.15	370CG07	LSF40CW

No LPCB approval for 5 Core

Nominal cross sectional area	Approximate overall diameter	Approximate diameter under armour	Nominal diameter of armour wires	Approximate cable weight	Maximum conductor resistance at 20°C	Current rating DC or single phase AC clipped direct	Current Rating DC or single phase AC Free Air or perforated tray Amps	Voltage drop DC	Volt drop single phase AC	Recommended accessories	
mm ²	mm	mm	mm	kg/km	ohms/km	Amps	Amps	mV/A/m	mV/A/m	Claw Cleat Ref No.	Brass Gland Ref No.
Two Core											
4	21	15	1.25	800	4.61	49	52	12	12	370CG04	LSF25CW
6	21	15	1.25	800	3.08	62	66	7.9	7.9	370CG04	LSF25CW
10	22	16	1.25	800	1.83	85	90	4.7	4.7	370CG05	LSF25CW
16	23	17	1.25	1000	1.15	110	115	2.9	2.9	370CG05	LSF25CW
25	26	20	1.25	1300	0.727	146	152	1.85	1.90	370CG06	
35	30	23	1.6	1800	0.524	180	188	1.35	1.35	370CG06	LSF32CW
50	31	24	1.6	2200	0.387	219	228	0.98	1.0	370CG06	LSF32CW
70	33	26	1.6	2600	0.268	279	291	0.67	0.69	370CG07	LSF32CW
95	35	27	2.0	3400	0.193	338	354	0.49	0.52	370CG07	LSF40CW
120	39	30	2.0	4100	0.153	392	410	0.39	0.42	370CG08	LSF50CW
150	42	33	2.0	4700	0.124	451	472	0.31	0.35	370CG08	LSF50CW
185	46	36	2.5	6100	0.0911	515	539	0.25	0.29	370CG09	LSF50CW
240	51	41	2.5	7500	0.0754	607	636	0.195	0.24	370CG09	LSF50CW
300	56	45	2.5	9000	0.0601	698	732	0.155	0.21	370CG10	LSF63CW
400	61	50	2.5	11000	0.0470	787	847	0.120	0.19	370CG11	LSF63CW

Circular conductor 4.0- 35mm² .

Shaped conductor 50mm² and above.

Current ratings in accordance with BS 7671/IET Wiring Regulations.

The tabulated ratings are based upon a 30°C ambient temperature and 90°C operating temperature.

Installation

Minimum recommended installation temperature 0°C.

Suitable for indoor and outdoor installations. Should be installed in accordance with BS 7671/IET Wiring Regulations or any other appropriate national regulations. Suitable for direct burial, trough, tray, ladder or other installations requiring a robust armoured cable.



Should you have any concerns about unsafe, non-approved or counterfeit cable, please contact the ACI



Thorne & Derrick
+44 (0) 191 410 4292
www.cablejoints.co.uk