



## 384 Series

Heavy Duty Hook Cleat  
25-80mm Diameter



**BI** **con**™

### Application

Standard and LSOH Cables - 25 to 80 mm diameter.  
For normal industrial use Indoor and Outdoor.  
Fits most ladder and tray systems.  
Operating temperature -20°C to +90°C.  
Can be double stacked on one fixing.  
Not designed to secure cables in long vertical routes.  
All sizes secured with 10mm fixings.

### Features

Manufactured from glass-filled nylon & LSOH Materials.  
Two-piece, single fixing design.  
Can be installed in temporary open position to aid single person working.  
Tested in accordance with BS EN 50368



# Heavy Duty Hook Cleat

Cable Clear Selection				Cleat Details								
Design Number		Cable Diameter		Dimensions (mm)					Weight		SWL (FOS 2)	
Nylon	LSOH	A (mm)		B		C	D	E	Nylon	LSOH	Nylon	LSOH
		Min	Max	Min	Max				g	g	kgf	kgf
384AA01	384LSF01	25	35	36	46	76	40	18	63	52	80	48
384AA02	384LSF02	34	44	44	54	85	40	18	74	61	80	48
384AA03	384LSF03	43	53	56.5	66.5	96	40	18	105	88	98	59
384AA04	384LSF04	52	62	65.5	75.5	106	40	18	129	108	103	62
384AA05	384LSF05	61	71	78	88	119	44	20	175	146	165	99
384AA06	384LSF06	70	80	87	97	129	44	20	221	185	171	103

## Method of Fixing

In all applications the cleat should be mounted on suitable M10 fixings. There is no need for any channel adaptor when mounting directly on to 'C' section channel.

SWL = Safe Working Load

FOS 2 = Values include a Factor of Safety of 2

