

# FP200 Gold<sup>®</sup> Multicore

## BS7629-1:2008

# FIRE RESISTANT CABLES



Certificate No 077a  
Certificate No 077b



### Key Applications

- > Fire detection and fire alarm systems for buildings
- Voice alarm systems
- Emergency lighting
- Other essential service circuits

### Conductor

- > Plain annealed copper solid (1.0 - 1.5 mm<sup>2</sup>) or stranded (2.5 mm<sup>2</sup>) circular conductor complying with BS EN 60228 class 1 or class 2.

### Insulation

- > High Performance damage resistant Insudite™. British Standard Type E15.

### Core Identification

- > 7-12-19 cores white with printed number.

### Screen

- > Laminated aluminium tape screen bonded to sheath and in contact with tinned annealed copper 0.5mm<sup>2</sup> drain wire which provides automatic screen earthing.

### Sheath

- > Robust thermoplastic LSOH sheath
- Colour - White or Red. Other colours to special order
- For external exposure the use of a white sheath is recommended.



Temperature Range  
-20 to +70°C



Bending Radius  
Fixed r=6D



Mechanical Impact  
Medium



Fire Performance  
BS EN 60332-1-2  
BS EN 50266-2-4



Flexibility  
Rigid



Halogen Free  
BS EN 50267-2-1



Low Smoke Emissions  
BS EN 61034-2



Fire Resistance  
BS 6387 Category CWZ  
BS EN 50200 PH30  
BS EN 50200 Annex E

ef: FP200Gold\_Multi/01/09



WWW.CABLEJOINTS.CO.UK  
**THORNE & DERRICK UK**  
TEL 0044 191 490 1547 FAX 0044 477 5371  
TEL 0044 117 977 4647 FAX 0044 977 5582  
WWW.THORNEANDDERRICK.CO.UK



# Prysmian FP200 Gold<sup>®</sup> Multicore Cable

Nominal cross sectional area mm	Conceptual construction no./mm	Mean overall diameter mm	Approximate cable weight kg/km	Maximum conductor resistance at 20°C ohms/km	Current rating DC or single phase AC Enclosed Amps	Current rating DC or single phase AC Clipped direct Amps	Volt drop DC or single phase AC mV/A/m	Recommended accessories	
								<sup>1</sup> LSOH <sup>®</sup> Fixing Clips	<sup>2</sup> Nylon LSOH Gland
<b>Seven core</b>									
1.0	1/1.13	12.1	196	18.1	13*	15*	44	AP12	252
1.5	1/1.38	13.3	249	12.1	16.5*	19.5*	29	AP13	252
2.5	7/0.67	16.3	387	7.4	23*	27*	18	AP16	254
<b>Twelve core</b>									
1.5	1/1.38	17.5	399	12.1	16.5	19.5*	29	AP18	254
2.5	7/0.67	21.7	637	7.4	23*	27*	18	AP22	255
<b>Nineteen core</b>									
1.5	1/1.38	20.5	588	12.1	16.5	19.5*	29	AP20	255
2.5 <sup>3</sup>	7/0.67	25.6	949	7.4	23*	27*	18	AP25	-

## Notes to table

<sup>1</sup> Recommended clip spacing 300 mm and 400 mm vertical.

<sup>2</sup> Brass gland may be used as an alternative.

<sup>3</sup> This size is not included in the latest (2008) edition of BS7629-1 and is therefore manufactured to BS7629-1:1997

Installation methods for current rating in accordance with BS7671/IEE Wiring Regulations.

Minimum recommended installation temperature 0°C.

\*The tabulated rating is as a two core and may be used where its number of cores carrying current does not exceed the square root of the total number of cores.

The tabulated ratings are based upon a 30°C ambient temperature and 70°C operating temperature.

For other ambient temperatures or where cables are grouped together, the following rating factors should be applied.

## Temperature rating factors

Ambient Temperature °C	25	30	35	40	45	50	55	60
Rating factor	1.03	1.00	0.94	0.87	0.79	0.71	0.61	0.50

## Rating Factors for Grouping

Number of circuits	2	3	4	5	6	7	8	9
Rating factor	0.80	0.70	0.65	0.60	0.57	0.54	0.52	0.50