

Power

Tel: +44 (0)191 490 1547 Fax: +44 (0)191 477 5371

Email: northernsales@thorneandderrick.co.uk

Website: <u>www.cablejoints.co.uk</u> www.thorneanderrick.co.uk

Power - class 2

Complies with ENATS 12-24 Class 2, 450N at 50°C.

Complies with BS EN 61386-24 750N, normal duty impact.

Ridgiduct power

Ridgiduct is a twin wall system, specifically engineered to provide a light, yet robust, alternative to conventional cable protection. Ridgiduct is manufactured in HDPE and the resulting stiff, yet flexible, twin wall structure easily outperforms alternative products. Complementing the Ridgiduct range are a selection of twin wall long radius drawn bends, manufactured in HDPE. These are available in most sizes and a range of angles.



Ridg	iduct Power	ENATS 12-24	1 (Standard si	izes)
ID mm	OD mm	Length m	Code	Pack Qty
100	118	2	RB7100X2	85
100	118	3	RB7100X3	85
100	118	6	RB7100X6	85
125	148	2	RB125X2	46
125	148	3	RB125X3	46
125	148	6	RB125X6	46
150	178	2	RB150X2	36
150	178	3	RB150X3	36
150	178	6	RB150X6	36

Key Benefits

- Complies with ENATS
 12-24 Class 2 specification
- Complies with BS EN 61386-24
- A preferred choice of regional electricity companies
- Integral coupler
- Low weight, flexible, durable and high strength
- Good impact resistance, even at low temperatures
- Available in an alternative twin wall split duct form for easy installation around existing cables with minimal change in strength

	Ridgiduct Coupling				
Description	ID mm	Code	Pack Qty		
Black coupling	100	RBC100	10		
Black coupling	125	RBC125	10		
Black coupling	150	RBC150	10		

Note: Ridgiduct as a sealed system. If the system is required to be water tight, then couplers will be required from the Ridgidrain range.

Ridgiduct Bends								
Description	Radius m	Angle°	Code	Pack Qty				
PVCu Double Socket Bend 100mm	2.4	11.25	RBB100X11X2.4 ▲*	1				
	2.4	22.5	RBB100X22X2.4 ▲*	1				
	0.45	45	RBB100X45X0.45	1				
	0.45	90	RBB100X90X0.45	1				
PVCu Double Socket Bend 125mm	2.4	11.25	RBB125X11X2.4 ▲*	1				
	2.4	22.5	RBB125X22X2.4 ▲*	1				
	0.61	45	RBB125X45X0.61	1				
	0.61	90	RBB125X90X0.61	1				
PVCu Double Socket Bend 150mm	2.4	11.25	RBB150X11X2.4 ▲*	1				
	2.4	22.5	RBB150X22X2.4 ▲*	1				
	0.61	45	RBB150X45X0.61	1				
	0.61	90	RBB150X90X0.61	1				

Sealed Ridgiduct bends are available for 100 & 150mm duct.

- ▲ Made to order and subject to lead times.
- *Compliant with ENATS 12-24

Ridgiduct coupling



Ridgiduct bends







Tel: +44 (0)191 490 1547 Fax: +44 (0)191 477 5371

Email: northernsales@thorneandderrick.co.uk

Website: www.cablejoints.co.uk www.thorneanderrick.co.uk