

BANANA PEELER®

Adjustable Blade Semi-con Scoring Tool

- Scoring depth from 1 to 90 mils (.025 to 2.286 mm)
- For "strippable" semi-con UD cable shield
- One hand scoring of circumference and length
- Spring-loaded blade assembly assures consistent scoring depth
- Teflon coated cable guide
- Semi-con is cleanly removed with no damage to underlying insulation
- Metric versions available (see table below)
- Convertible to a fixed setting
- Made in the U.S.A.
- Replacement blade: Part No.: 34230
- Length: 9.4 in. (239 mm)
- Weight: 13 oz (369 g)



Removal of Semi-Con

Model	Semi-Con O.D. Range	Part No.
BP A	.38 - .75 in. (9.652 - 19.05 mm)	35250
BP 1A	.75 - 1.10 in. (19.05 - 27.94 mm)	34244
BP 1AH	1.10 - 1.30 in. (27.94 - 33.02 mm)	34190
BP 2A	1.25 - 1.75 in. (31.75 - 44.45 mm)	34245
BP 2AH	1.75 - 1.95 in. (44.45 - 49.53 mm)	34615
BP 2AK	1.95 - 2.00 in. (49.53 - 50.8 mm)	35330
BP 3A	2.00 - 2.63 in. (50.8 - 66.8 mm)	38445

Blade Depth Range is from 1 mil (.001") to 90 mils (.090")

Other sizes available special order.

Metric Banana Peelers - Removal of Semi-Con

Model	Semi-Con O.D. Range	Part No.
BP 1A-M	19.05 - 27.95 mm	42220
BP 1AH-M	27.95 - 33.00 mm	42335
BP2A-M	31.75 - 44.45 mm	42336

Blade Depth Range is from .0254 mm to 2.30 mm

Removal of Soft Rubber Jackets

Model	Cable O.D. Range	Part No.
BP AR	.38 - .75 in. (9.652 - 19.05 mm)	37760
BP 1AR	.75 - 1.10 in. (19.05 - 27.94 mm)	36401
BP 2AR	1.25 - 1.95 in. (31.75 - 49.53 mm)	36402

Blade Depth Range is from
 50 mils (.050 in.) to 140 mils (.140 in.)