

# WS 5 SERIES

## End Strippers

- For 600 volt to 35 KV cables
  - .260 to 1.265 in (6.60 to 32.13 mm) cable O.D.
  - Strips XLPE, polyethylene and EPR insulation\*
  - Precision stripping of insulation only or insulation and semicon simultaneously
  - Ideal for primary URD cable
  - Guarded cutting blade prevents injury
  - WS 5 and WS 5DA permit accurate preset stripping lengths of up to 4 in (101.60 mm). Bar removable for infinite stripping
  - Accepts SW 2 ratchet wrench for leverage
  - Stop bar with drill adapter can be purchased separately or comes with WS 5DA. Metric stop bar is also available
  - Bushing insert fits over cable
    - Bushing insert presets cutting blade depth
    - Bushings can be changed easily and quickly
  - Made in the U.S.A.
  - Model WS 5B available to strip from 3/4" up to 5-3/4" lengths (Part No.: 37710)
  - Length: 6 in (152 mm) • Weight: 1 lb (454 g)
- \* See instruction sheet for detailed information



WS 5



Stop bar with drill adapter

**Ordering Information:** Choose tool and bushing (below)

| Model   | Part No. | Insulation Materials | Insulation Thickness Max. (mils) | Replacement Blade | Rotating Stop Bar |
|---------|----------|----------------------|----------------------------------|-------------------|-------------------|
| WS 5    | 10327    | XLPE or EPR          | 400                              | CB 7-2            | 10346             |
| WS 5 DA | 10336    | XLPE or EPR          | 400                              | CB 7-2            | 10337             |

- CB 7-2 Replacement Blade Part No.: 10324

## Adjustable End Strippers

- Upgraded model of the WS 5
- Same basic function as the WS 5 Model plus:
  - New adjustable strip stop with rotary mechanism eliminates the need for hex wrench
  - New adjustment window, with inch and metric readings allows easy setting of stop for precise strip lengths
    - Strip lengths from 0.625 in (15.9 mm) up to 2.5 in maximum (63.5 mm)
    - For 600 volt to 35 KV cables
    - .260 to 1.265 in (6.60 to 32.13 mm) Cable O.D.
    - Strips XLPE, polyethylene, and EPR\* insulation up to 400 mils thick
- Precision stripping of insulation only or with semicon over insulation\*



WS 5A



WS 5A-DA

- Ideal for primary URD cable
- Guarded cutting blade prevents injury
- Accepts SW 2 ratchet wrench for leverage
- **WS 5A-DA comes with 3/8" drill adapter**
- *Drill adapter also available separately. Tools purchased prior to December 2005 require retrofit. Contact customer service or details* • Made in the U.S.A.
- Length: 8 in (203 mm) • Weight: 1.2 lb (544 g)
- Replacement Blade: CB 7-2 (Part No.: 10324)
- WS 5A Part No.: 37415 • WS 5A-DA Part No.: 38750

\* See instruction sheet for detailed information