

WS 5 SERIES

End Strippers

- For 600 volt to 35 KV cables
 - .260 to 1.265 in (6.60 to 32.13 mm) cable O.D.
 - Strips XLPE, polyethylene and EPR insulation*
 - Precision stripping of insulation only or insulation and semicon simultaneously
 - Ideal for primary URD cable
 - Guarded cutting blade prevents injury
 - WS 5 and WS 5DA permit accurate preset stripping lengths of up to 4 in (101.60 mm). Bar removable for infinite stripping
 - Accepts SW 2 ratchet wrench for leverage
 - Stop bar with drill adapter can be purchased separately or comes with WS 5DA. Metric stop bar is also available
 - Bushing insert fits over cable
 - Bushing insert presets cutting blade depth
 - Bushings can be changed easily and quickly
 - Made in the U.S.A.
 - Model WS 5B available to strip from 3/4" up to 5-3/4" lengths (Part No.: 37710)
 - Length: 6 in (152 mm) • Weight: 1 lb (454 g)
- * See instruction sheet for detailed information



WS 5

Stop bar with
drill adapter

Ordering Information: Choose tool and bushing (below)

Model	Part No.	Insulation Materials	Insulation Thickness Max. (mils)	Replacement Blade	Rotating Stop Bar
WS 5	10327	XLPE or EPR	400	CB 7-2	10346
WS 5 DA	10336	XLPE or EPR	400	CB 7-2	10337

- CB 7-2 Replacement Blade Part No.: 10324

Adjustable End Strippers

- Upgraded model of the WS 5
- Same basic function as the WS 5 Model plus:
 - New adjustable strip stop with rotary mechanism eliminates the need for hex wrench
 - New adjustment window, with inch and metric readings allows easy setting of stop for precise strip lengths
 - Strip lengths from 0.625 in (15.9 mm) up to 2.5 in maximum (63.5 mm)
 - For 600 volt to 35 KV cables
 - .260 to 1.265 in (6.60 to 32.13 mm) Cable O.D.
 - Strips XLPE, polyethylene, and EPR* insulation up to 400 mils thick
 - Precision stripping of insulation only or with semicon over insulation*



WS 5A-DA



WS 5A

- Ideal for primary URD cable
- Guarded cutting blade prevents injury
- Accepts SW 2 ratchet wrench for leverage
- **WS 5A-DA comes with 3/8" drill adapter**
- *Drill adapter also available separately. Tools purchased prior to December 2005 require retrofit. Contact customer service or details* • Made in the U.S.A.
- Length: 8 in (203 mm) • Weight: 1.2 lb (544 g)
- Replacement Blade: CB 7-2 (Part No.: 10324)
- WS 5A Part No.: 37415 • WS 5A-DA Part No.: 38750

* See instruction sheet for detailed information

SECONDARY DIST.

PRIMARY DIST. (OH)

PRIMARY DIST. (URD)

SPECIALTY DIST.

TRANSMISSION