

## WS 15

### Adjustable Semi-con Scoring Tool

- For "strippable" semi-con insulation shield for cable O.D.s up to 1.75 in (44.45 mm)
- Blade can be preset for any shield thickness
- Peelable in one continuous piece
- Scores in helical, spiral pattern approx. 1/2" (12.70 mm) wide
- Guarded cutting blade prevents injury
- Made in the U.S.A.
- Replacement blade: CB 16 (Part No.: 10817)
- Length: 4 in (101.6 mm)
- Weight: 9 oz (255 g)
- Part No.: 10800



| Model | Cable O.D. Range<br>(inch) | Cable O.D. Range<br>(mm) | Score Depth<br>(mils) | Score Depth<br>(mm) |
|-------|----------------------------|--------------------------|-----------------------|---------------------|
| WS 15 | .688 - 1.750               | 17.48 - 44.45            | 1 to 125              | .025 - 3.175        |

## WS 74

### Semi-con Removal Tool

- Shaves 15-35 KV cable with semi-con diameters from 12mm to 50mm (0.47 - 1.97")
- Accurate semi-con removal within 24mm (.945") of the jacket
- Precision ground blade provides a 20° chamfer cut finish at the semi-con end
- Precision blade adjustment in 0.1mm increments
- Thumb switch to allow easy transition from spiral shave to square cut finish without requiring an additional stop device
- Complete in plastic foam box with spare blade
- Easy blade replacement without the need for additional tools
- Length – 136mm (5.34 inches)
- Weight – 544g (1.2 lbs)
- Part No. 43140
- Replacement Blade – CB 277 (43144)



SECONDARY DIST.

PRIMARY DIST. (OH)

PRIMARY DIST. (URD)

SPECIALTY DIST.

TRANSMISSION