



The Ritherdon service/feeder pillar is designed with an integral root and body and a detachable door.

To ensure a long service life the complete unit is manufactured from 2.0mm thick stainless steel and is available either in the natural stainless steel finish or with a powder coated finish.

Access for cable ducting is provided through the lower front section of the pillar and duct apertures in the sides and back of the root. An earth cable is provided for bonding the door to the body, with two M6 studs complete with nuts and washers.

The base plate is designed to provide stability during installation and protrudes at both the front and sides. To permit installation close to a wall the rear edge of the base plate is welded flush with the rear panel of the pillar body. To ensure installation at the optimum depth a suggested ground level is marked on the outer faces of the pillar.



EX STOCK –

call us on 01254 819100
for stock availability

DELIVERY –

we have our own vans to
deliver when you need them

LOCK TYPE –

should the standard tri-key
cam lock not be suitable,
please specify your lock type for
Ritherdon to source and price

COLOUR –

choice of colours dark green,
light and dark grey, black and
anti-graffiti powder coating,
or can be left natural

Feeder Pillar Dimensions

Pillar Type	Width mm	Depth mm	Overall Height mm*	Base Plate (width x depth mm)	Plywood Backboard (width x depth mm)
ER150	150	150	900	175 x 130	130 x 600
R150	150	150	1060	230 x 190	130 x 600
R200 mini	200	100	750	280 x 140	180 x 330
R200	200	200	1060	280 x 240	180 x 600
R300	300	150	1060	380 x 190	280 x 600
R460	460	230	1060	540 x 270	440 x 600

* subtract ~350 mm for burial depth to give the installed height