



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.cablejoints.co.uk

Item Code: SM580

Item Description: Fine Ribbed Rubber Matting to 50,000v - Grey VDE0303 Grade

SM580 Fine Ribbed Rubber Matting to 50,000v - Grey Previously VDE0303 Grade is a high quality matting tested to 50,000 volts and in accordance to VDE0303 European specification with the regulation standard, stamped on the reverse of the roll at 1000mm intervals. Fully certified and tested to 50,000 volts with a recommended safety working voltage of 1,000v. It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse. A very commonly requested and approved Electrical Safety Matting specified by our customers in the UK and Europe

- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse
- Anti-slip finish
- Low maintenance

Cut lengths available to order. SM580 can also be supplied to order in colours and flame retardant, low smoke emission grades

Technical Information

Application	Electrical Safety, Health & Safety
Product	Anti Slip, Electrical Safety, EU VDE 0303, Safety Matting
Thickness	4.5mm
Resistance to	Please Call
Colour	Grey
Insert Req	No
Solid	Yes
Drainage Holes	No



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.cablejoints.co.uk



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.cablejoints.co.uk

metroseal Product Information Sheet

Item Code:

SM580

Other sizes and colours to special order.

Cut lengths to order.

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.



Stock Roll Sizes	Weight	Specifications	Values
[m x m x mm]	[kg/M2]	[compound]	[typical]
10m x 0.91m x 4.5mm	5.20	Colour:	Grey
10m x 1.0m x 4.5mm	5.20	Compound:	SBR/NR
10m x 1.2m x 4.5mm	5.20	Hardness [shore A]:	65°
		Density[SG]:	1.3
		Tensile Strength:	5 MPA
		Elongation[min]:	250%
		Abrasion Resistance:	180 mm ³
		Minimum Temperture	-20°C
		Maximum Temperture	+70°C



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.cablejoints.co.uk