

# RESCUE HOOK, STATIC DISCHARGE STICK



Tel: +44 (0)191 490 1547  
 Fax: +44 (0)191 477 5371  
 Email: [northernsales@thorneandderrick.co.uk](mailto:northernsales@thorneandderrick.co.uk)  
 Website: [www.cablejoints.co.uk](http://www.cablejoints.co.uk)  
[www.thorneandderrick.co.uk](http://www.thorneandderrick.co.uk)

**Salisbury Insulated Rescue Hook** is an invaluable tool for any workplace used to withdraw an injured worker out of a hazardous area. Confined spaces, in vaults, or just near electrical cabinets and switch gear are some of the places where this tool is a must. Featuring a foam filled, fiberglass reinforced handle for superior electrical insulation and a coated heat treated body hook with an 18” opening. The stick is available in the standard lengths of 6 and 8-foot lengths. Other lengths are available as a special order. Contact us with your requirements. Handle meets the requirements of ASTM F711.

**The Static Discharge Stick** is designed to safely remove the static charge after de-energizing. This tool is pre-assembled and includes a copper “U” hook, 3’6” closed cell foam filled tubular fiberglass stick and 6’ of copper grounding cable attached to a Salisbury 1814 bronze flat jaw serrated grade 3 clamp. Also available in a 1’ length stick.



**WARNING:** Discharge sticks are not grounding tools as described by OSHA 1910.269 and carry no fault duty rating.



Insulated Rescue Hook



Static Discharge Stick w/ Universal Attachment



Static Discharge Stick

Cat. No.	Dimensions		Weight ea.	
	in.	mm	lbs.	kgs
<b>INSULATED RESCUE HOOK</b>				
24400	Rescue Hook 3' (0.9 m) length		3.4	( 1.5 )
24401	Rescue Hook 6' (1.8 m) length		4.5	( 2 )
24403	Rescue Hook 8' (2.4 m) length		5.5	( 2.5 )
<b>STATIC DISCHARGE STICK</b>				
20817	Static Discharge Stick OAL 3'8" (1.08m) length		8	( 3.6 )
22629	Static Discharge Stick w/ Universal Attachment 1' (0.3m) length		.38	( 0.17 )