

# FRP CLAMPSTICKS



Tel: +44 (0)191 490 1547  
 Fax: +44 (0)191 477 5371  
 Email: [northersales@thorneandderrick.co.uk](mailto:northersales@thorneandderrick.co.uk)  
 Website: [www.cablejoints.co.uk](http://www.cablejoints.co.uk)  
[www.thorneandderrick.co.uk](http://www.thorneandderrick.co.uk)

*Tough Thermoplastic head ferrule.*  
*EZ Grip plastic hand grip.*  
*Wide opening 15/16" ( 23.8mm)*  
*stainless steel hook.*  
*Heavy duty rubber end cap.*

**External Rod Clampsticks** are constructed of closed cell foam-filled tubular fiberglass in accordance with ASTM standard F711. The hook's operating rod, made of solid 3/8" (9.5mm) dia. fiberglass, is mounted on the exterior of the tool so that it can be easily wiped down prior to use.

These Clampsticks meet ASTM F1825 Standards.



Side Opening Hook



9840 Splined Universal Head



External Rod Clampstick

Cat. No.	Length		Weight ea.	
	Feet	Meters	lbs.	kgs
<b>EXTERNAL ROD CLAMPSTICK</b>				
4007*	4' 8"	1.32	4.2	1.9
4008*	5' 8"	1.62	4.6	2.1
4009*	6' 8"	1.93	5.2	2.4
4010*	8' 8"	2.54	6.2	2.8
4011*	10' 8"	3.15	7.0	3.2
4012*	12' 8"	3.76	7.7	3.5
4013*	14' 8"	4.37	9.4	4.3
<b>EXTERNAL ROD CLAMPSTICK - PLAIN CAP</b>				
8106C	6' 6"	1.98	5	2.27

\*Add a "9864" suffix for a Switch Stick Head or a "9840" suffix for a Splined Universal Head. Clamp sticks may be ordered with these fittings attached to the end by adding the appropriate suffix to the catalog number.