

UNIVERSAL SWITCH STICKS



Tel: +44 (0)191 490 1547
 Fax: +44 (0)191 477 5371
 Email: northernsales@thorneandderrick.co.uk
 Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk

One, two, and three section hot sticks have a standard splined universal head. 1.25" dia. switch sticks are supplied with a #9971 Prong. A Heavy Duty Disconnect Prong #9969 is supplied on all others.



9969 Prong



9971 Prong

Cat. No.	Dimensions: Dia. x Length		Weight ea.	
			lbs.	kgs
ONE SECTION				
	in x ft.	mm x m		
4213	1.25 x 4	31.7 x 1.2	2.6	1.2
4214	1.25 x 6	31.7 x 1.8	3.4	1.5
4215	1.25 x 8	31.7 x 2.4	4.1	1.9
4216	1.25 x 10	31.7 x 3	4.9	2.2
4217	1.25 x 12	31.7 x 3.6	5.6	2.5
4218	1.25 x 14	31.7 x 4.3	6.4	2.9
4219	1.5 x 8	38.1 x 2.4	5.4	2.5
4220	1.5 x 10	38.1 x 3	6.5	3
4221	1.5 x 12	38.1 x 3.6	7.5	3.4
4222	1.5 x 14	38.1 x 4.3	8.6	3.9
4223	1.5 x 16	38.1 x 4.9	9.8	4.3
4225	1.5 x 20	38.1 x 6	11.7	5.3
TWO SECTIONS				
	OAL Length	Top	Bottom	lbs. kgs
	ft. m	in. x ft. mm x m	in. x ft. mm x m	
4036	8 2.4	1.25 x 4 31.7 x 1.2	1.25 x 4 31.7 x 1.2	4.2 1.9
4037	10 3	1.25 x 5 31.7 x 1.5	1.25 x 5 31.7 x 1.5	5.2 2.2
4038	12 3.6	1.25 x 6 31.7 x 1.8	1.5 x 6 38.1 x 1.8	6.9 3.1
4039	14 4.3	1.25 x 6 31.7 x 1.8	1.5 x 8 38.1 x 2.4	7.9 3.1
4040	16 4.9	1.25 x 8 31.7 x 2.4	1.5 x 8 38.1 x 2.4	8.6 3.9
4041	18 5.5	1.25 x 8 31.7 x 2.4	1.5 x 10 38.1 x 3	9.6 4.4
4042	20 6	1.25 x 10 31.7 x 3	1.5 x 10 38.1 x 3	10.4 4.7
THREE SECTION				
	OAL Length	Top	Middle / Bottom	lbs. kgs
	ft. m	in x ft. mm x m	in. x ft. mm x m	
4043	12 3.6	1.25 x 4 31.7 x 1.2	1.5 x 4 38.1 x 1.2	7.7 3.5
4044	15 4.6	1.25 x 5 31.7 x 1.5	1.5 x 5 38.1 x 1.5	9.1 4.1
4045	18 5.5	1.25 x 6 31.7 x 1.8	1.5 x 6 38.1 x 1.8	10.5 4.7
4046	20 6	1.25 x 8 31.7 x 2.4	1.5 x 6 38.1 x 1.8	16.5 7.5
HEAD ONLY				
9840		1.25 31.7	Universal Head	0.2 0.1
9841		1.5 38.1	Universal Head	0.3 0.1



Universal Switch Stick



FRP Splices with Button