



**PRO-HOOD® ARC FLASH PROTECTION HOODS ▶**

8 cal/cm<sup>2</sup> to 100 cal/cm<sup>2</sup>\* ATPV ratings  
 8 cal/cm<sup>2</sup> to 75 cal/cm<sup>2</sup>\* hoods are made from arc flash resistant material  
 100 cal/cm<sup>2</sup>\* hood is made from TuffWeld® and Q/9® material layers  
 Sewn with Nomex® thread  
 Arc rated 10" x 20" anti-fogging replaceable lens  
 Slotted bracket  
 Hook and pile tabs to attach Salisbury's PRO-AIR™ belt mounted compact air system  
 One size fits all.  
 Hard hat not included.

Meet current ASTM F2178 and NFPA 70E standards and the flammability requirements for ASTM F1506.

All PRO-HOODs are CE 0120 certified.

Orange color available by special order

**NEW Optional Universal Inner Anti-Fog Lens**

(see page 12 for more information)

**NEW Optional Integrated Air Flow Hood System**

(see page 17 for more information)

**IMPROVEMENTS:**

NEW Design and Cut on FH8BL, FH11BL & FH20BL

Clearer Lens available on FH8BL, FH11BL, FH20BL, FH31RB, FH40GY, FH40GYLT, and FH55GY

**IMPROVED**

**IMPROVED LENS CLARITY!**



FH40GY



FH31RB

**40 CAL/CM<sup>2</sup> & 100 CAL/CM<sup>2</sup>.  
 LIGHTER MATERIAL THAN EVER.**

Cat. No.	Description
FH8BL	IMPROVED 8 cal/cm <sup>2</sup> , navy blue
FH11BL	IMPROVED 12 cal/cm <sup>2</sup> , navy blue
FH20BL	IMPROVED 20 cal/cm <sup>2</sup> , navy blue
FH31RB	IMPROVED 31 cal/cm <sup>2</sup> , royal blue
FH40GY	IMPROVED 40 cal/cm <sup>2</sup> , gray
FH40GYLT	IMPROVED 40 cal/cm <sup>2</sup> , lighter weight, gray
FH55GY*	IMPROVED 55 cal/cm <sup>2</sup> , gray
FH75GY*	75 cal/cm <sup>2</sup> , gray
FH100TW*	100 cal/cm <sup>2</sup> , khaki, TuffWeld®

Add suffix "-C" to include integrated air flow hood system.

NOTE: Available in orange upon request. Contact your local Salisbury Representative.

**NEW**

**NEW AIR FLOW SYSTEM  
 OPTIONAL INTEGRATED  
 LIGHTWEIGHT AIR SYSTEM**



**NEW**

**NEW PRO-HOOD® CLEAR  
 IMPROVED FH8BL  
 -CLEAREST HOOD AVAILABLE  
 -LIGHTER WEIGHT  
 -MEETS NFPA 70E HRC2\* 2009**



FH8BL

**SALISBURY ADVANTAGE**

**NO OTHER OPTION COMES CLOSE!**



\*IMPORTANT: NFPA 70E does not have a Hazard Risk Category above 40 cal/cm<sup>2</sup>. Working on levels above 40 cal/cm<sup>2</sup> should be avoided because of the blast hazards caused by arc flash.