

HV Indicators

Portable, neon and digital potential indicators for confirming voltage on earthed neutral systems

The KD1E range of high voltage indicators confirm the presence of voltage on earthed neutral electrical systems. Conforming to the G9 recommended creepage and safety standards, each model features high-grade PVC tubing and incorporates encapsulated resistor chains. For additional safety and peace of mind, each unit is compatible for use with a PH3 proving unit for checking the voltage indicator before and after it is used.

Available with either digital readout or neon indication and the option of flat or domed contact electrodes.

The KD1E units are supplied as standard with a carry case and operating instructions. The KD1E/15D and KD1E/33D also include a battery charger and proving unit.

Key Features:

Digital Readout

- Use as a potential indicator to determine presence of voltage or as a voltmeter
- Robust display housing
- No switches
- Provides direct reading of voltage measurements
- Low battery indicator
- Supplied with battery charger
- Specifically designed carrying case for unit and accessories

Unit	System Voltage*	Features	Part No.
KD1E/15D	15KV max	Resolution-10V	109A910
KD1E/33D	33KV max	Resolution-100V	109A911

*Earthed neutral system

Neon Indication

- Duplicate neon indicators within shock resistant sleeves
- Permanently connected earth cable
- Hand guards on all elements
- Direct access to vertical or horizontal metal clad switch gear
- UK Electricity Council Approval list G9

Unit	System Voltage*	Features	Part No.
KD1E	1KV - 11.5KV		113A916
KD1E/KAD	1KV - 11.5KV	KAD Audio Alarm	113A915
KD1E/19	1.5KV - 19KV		113A914
KD1E/19S	1.5KV - 19KV	AC Voltage only	113A913
KD1E/22	3KV - 22KV		113A912
KD1E/33	3KV - 33KV		113A911

Find out more:



www.seaward.co.uk/hvindicators
 Tel: +44 (0) 191 587 8741

Neon Indication



Digital Readout

Technical Specification

TESTS

Indicator Type	Neon Indicator					Digital Reading	
Indicator Type	KD1E	KD1E/19	KD1E/19S	KD1E/22	KD1E/33	KD1E/15D	KD1E/33D
Maximum System Voltage	11kV	19kV	19kV	22kV	33kV	15kV	33kV
Maximum Voltage to Earth	6.6kV	11kV	11kV	12.5kV	19kV	8.6kV	19kV
Threshold Voltage	300V	300V	300V	300V	300V		
Measuring Range						0.00kV-8.6kV	0.00kV-19.0kV
Resolution						10V	100V
Sensitivity	AC/DC	AC/DC	AC Only	AC/DC	AC/DC	AC/DC	AC/DC
Circuit Current (IEC 61234-2)	2.3mA nominal @ 6.6kV	0.7mA nominal @ 11kV	0.9mA nominal @ 11kV	3.5mA nominal @ 12.5kV	1.1mA nominal @ 19kV	0.5mA nominal @ 8.6kV	1.1mA nominal @ 19kV
Dielectric Leakage Current (IEC 61234-2)	7µA nominal @ 13.8kV	11µA nominal @ 22.8kV	12µA nominal @ 22.8kV	12µA nominal @ 26.4kV	17µA nominal @ 40kV	9µA nominal @ 18kV	17µA nominal @ 40kV
Length (mm)	330	330	330	665	670	600	600
Diameter (mm)	25	25	25	25	25	25	25
Handle Length (mm)	105	105	105	90	250	235	235
Hand Guard Height (mm)	23.5	23.5	23.5	23.5	23.5	23.5	23.5
Contact Electrode Type	Domed	Flat	Flat	Domed	Flat	Domed	Domed

Extension Rods	1.5m Straight	90°	120°
Maximum System Voltage	33kV	15kV	33kV
Dielectric Leakage Current	140µA nominal @ 40kV	50µA nominal @ 18kV	130µA nominal @ 40kV
Length	150cm	78cm	78cm
Diameter	2.5cm	2.5cm	2.5cm
Contact Electrode Type	"V" form	Domed	Domed

ACCESSORIES

Unit	Features	Part No.
PH3	■ Proving unit for proof testing high voltage indicators ■ High voltage output 1200V -1500DC ■ Self test facility ■ Avoids use of known supply points or bulky test equipment	112A913 (domed) 112A921 (flat nose)
Bent End Adaptors	■ 90° or 120° ■ Suitable for use on vertical type switchgear	141A900 – 90° 141A912 – 120°
Extension Rod	■ 1.5m extension rod for use on overhead lines ■ Suitable for use with KDIE/15D, KDIE/33D, PR15D and PR33D	141A901