

PRODUCT DATASHEET

Legend™ 2-Part Labelling System - Thermal Labels



One Software
One Printer
One Ribbon



This is a multipage document, all pages must be read in conjunction with each other



A really easy and fast way of producing wire markers using our Silver Fox DTP-1/300 thermal printer.

With our 2-part labelling system you can make changes in seconds with no need to cut and re-terminate the wire. Simply remove the label from the tubing and pull through a new label.

TECHNICAL DATA

Printing Method	Silver Fox DTP-1 Thermal Printer
Thermal Ribbon	Silver Fox TSR3
Material	Polypropylene
Standard Colours	White
RoHS (EU 2002/95/EC)	RoHS Compliant

PRODUCT TESTING

Test	Method
Moisture Resistance	MIL-STD-202G Method 106G
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4
High Temperature 500 hours @ 70°C	MIL-STD-202G Method 108A
Hydrogen Sulphide	H ₂ S Sour Gas Exposure (2% H ₂ S)
UV Weathering 500 hours*	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

* Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for internal use such as, control rooms, power stations, substations etc.

FEATURES & BENEFITS

- Replace ident, no need to cut and re-terminate wire
- Choice of 3 lengths; 20mm, 30mm, 50mm

ASSOCIATED PRODUCTS

- 2-Part Labelling System clear tubing

Print using our DTP – 1/300 Thermal Printer.



T&D THORNE & DERRICK UK

Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northernsales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk

PRODUCT DATASHEET

Legend™ 2-Part Labelling System - Thermal Labels



**One Software
One Printer
One Ribbon**

This is a multipage document, all pages must be read in conjunction with each other



STORAGE INSTRUCTIONS

Storage Instructions	Store between 50° F (10° C) and 77° F (25° C)
Shelf Life	2 Years
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

HOW IT WORKS

STEP 1



Slide the tubing onto the cable/wire

STEP 2



Pull the printed label through the tubing

STEP 3




Tear/cut off tail

ORDER INFORMATION

Product Code	Label Dims (mm)	Labels / Roll	Rolls / Pack	Labels / Pack	Colour Options
L6/20T	20 x 5	5000	1 Roll	5000	<input type="checkbox"/>
L6/30T	30 x 5	5000	1 Roll	5000	<input type="checkbox"/>
L6/50T	50 x 5	5000	1 Roll	5000	<input type="checkbox"/>

Use with Silver Fox Labacus Innovator Advanced or Professional software.
Print in conjunction with our Fox-in-a-Box Plug'N'Play thermal printer using the same ribbon as all our other

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE

