

PRODUCT DATASHEET

Legend™ LHZ2 Low-smoke Zero-halogen Heatshrink



One Software
One Printer
One Ribbon



This is a multipage document, all pages must be read in conjunction with each other



The Silver Fox Legend™ LHZ2 zero-halogen heatshrink tubing is flexible, flame-retardant and has a low smoke index.

Supplied on rolls you can select the length of marker required with our Silver Fox Labacus Innovator Advanced or Professional software.

Print in conjunction with our DTP-1/300 Plug'N'Play thermal printer with the same ribbon as all our other thermal labels.

TECHNICAL DATA

Printing Method	Silver Fox DTP-1 Thermal Printer
Thermal Ribbon	Silver Fox TSR3
Material	Polyolefin
Shrink Ratio	2:1
Min. Shrink Temperature	115°C (full recovery)
Operating Temperature	-40°C up to 105°
Dielectric Strength	≥ 20 kV/mm
Standard Colours	Yellow
RoHS (EU 2002/95/EC)	RoHS Compliant

FEATURES & BENEFITS

- Easy to use and apply
- Use with a standard heat gun
- Print 2 rolls at a time
- Choice of 6 sizes

Print using our DTP – 1/300 Thermal Printer.



PRODUCT TESTING

Test	Method
Low Temperature 72 hours @ -40°C Followed by manipulation test*	MIL-STD-810F Method 502.4
High Temperature 2000 hours @ 70°C to 100°C**	MIL-STD-202G Method 108A
Hydrogen Sulphide	H ₂ S Sour Gas Exposure (2% H ₂ S)
UV Weathering 3000 hours***	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

* Manipulation of the labels were performed at -40°C at completion of the low temperature test. This took the form of attempting to bend the labels in half using bare hand force only.

** Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C

*** Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for internal use such as, control rooms, power stations, substations etc.



PRODUCT DATASHEET

Legend™ LHZ2 Low-smoke Zero-halogen Heatshrink



One Software
One Printer
One Ribbon



This is a multipage document, all pages must be read in conjunction with each other



STORAGE INSTRUCTIONS


Storage Instructions	Store between 50° F (10° C) and 77° F (25° C)
Shelf Life	2 Years
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

ORDER INFORMATION


Product Code	Cable ID Ø Expanded (mm)	Cable ID Ø Recovered (mm)	Roll Length (m)	Rolls / Pack	Total Pack Length (m)	Colour Options
LHZ2/R/2.4-1.2TY(PF)	2.4	1.2	22	8 Rolls	176	<input checked="" type="checkbox"/>
LHZ2/R/3.2-1.6TY(PF)	3.2	1.6	22	8 Rolls	176	<input checked="" type="checkbox"/> <input type="checkbox"/>
LHZ2/R/4.8-2.4TY(PF)	4.8	2.4	18	6 Rolls	108	<input checked="" type="checkbox"/> <input type="checkbox"/>
LHZ2/R/6.4-3.2TY(PF)	6.4	3.2	18	6 Rolls	108	<input checked="" type="checkbox"/> <input type="checkbox"/>
LHZ2/R/9.5-4.8TY(PF)	9.5	4.8	18	4 Rolls	72	<input checked="" type="checkbox"/> <input type="checkbox"/>
LHZ2/R/12.7-6.4TY(PF)	12.7	6.4	18	4 Rolls	72	<input checked="" type="checkbox"/> <input type="checkbox"/>

Use with Silver Fox Labacus Innovator Advanced or Professional software.
Print in conjunction with our Fox-in-a-Box Plug'N'Play thermal printer using the same ribbon as all our other thermal labels.

SILVER FOX CATALOGUE



TIP - TIME INTO PROFIT BROCHURE



T&D THORNE & DERRICK UK

Tel: +44 (0)191 490 1547
Fax: +44 (0)191 477 5371
Email: northersales@thorneandderrick.co.uk
Website: www.cablejoints.co.uk
www.thorneandderrick.co.uk



Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice.