

# PRODUCT DATASHEET

## Legend™ Thermal Tie-On Cable Labels

This is a multipage document, all pages must be read in conjunction with each other

### FEATURES & BENEFITS

- Easy to use and apply
- Pre-perforated for rapid removal from roll
- Apply to any cable from OD Ø 10mm - unlimited

### APPROVALS

- Authorised for use by London Underground Registration No. 1105

### PRINTING METHOD



Silver Fox DTP-1 Thermal Printer

### SUPPORTED CONSUMABLES

- TSR3/300/110 Thermal Ribbon

### LABACUS INNOVATOR SOFTWARE

- Advanced
- Professional

Our low cost Legend™ polyester thermally printed tie-on cable labels offer a simple way of printing either low volumes in ones or twos or in higher volumes in conjunction with our DTP-1/300 thermal printer.

Print 100 tie-on cable labels in 100 seconds!

It has been independently tested for salt mist spray, high/low temperature, H<sub>2</sub>S, humidity - so can be used where a thermal solution is preferred and there is no requirement for LS0H or UV resistance.

Authorised for use for London Underground Limited projects.



### TECHNICAL DATA

Printing Method	Silver Fox DTP-1 Thermal Printer
Thermal Ribbon	Silver Fox TSR3
Material	Polyester
Thickness	175 microns
Standard Colours	Yellow
Standard Sizes	90mm x 13mm
RoHS (EU 2002/95/EC)	RoHS Compliant

### PRODUCT TESTING

Test	Method
Moisture Resistance	MIL-STD-202G Method 106G
Low Temperature 72 hours @ -40°C	MIL-STD-810F Method 502.4
High Temperature 2000 hours @ 70°C to 100°C*	MIL-STD-202G Method 108A
Hydrogen Sulphide	H <sub>2</sub> S Sour Gas Exposure (2% H <sub>2</sub> S)
UV Weathering 500 hours**	ISO 4982 Part 3 Method A Cycle 1
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

\*Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C

\*\*Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for use internally such as: data centres, control rooms, sub-stations, power stations etc. Other applications may include banks, hotels airports etc




# PRODUCT DATASHEET

## Legend™ Thermal Tie-On Cable Labels


This is a multipage document, all pages must be read in conjunction with each other

### ORDER INFORMATION

Product Code	Label Dims (mm)	Labels / Roll	Rolls / Pack	Labels / Pack	Colour Options
<b>LM9013TY</b>	90 x 13	3000	1 Roll	3000	


### HOW TO REMOVE LABELS

STEP 1



After printing, fold the label along the perforations

STEP 2



Firmly crease along the fold

STEP 3



Tear along the crease to remove the label

### SILVER FOX CATALOGUE



### TIP - TIME INTO PROFIT BROCHURE



Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted.

This datasheet supersedes any previous information/datasheet released and is subject to change without notice.



**THORNE &  
DERRICK UK**

Tel: +44 (0)191 490 1547  
Fax: +44 (0)191 477 5371  
Email: [northernsales@thorneandderrick.co.uk](mailto:northernsales@thorneandderrick.co.uk)  
Website: [www.cablejoints.co.uk](http://www.cablejoints.co.uk)  
[www.thorneandderrick.co.uk](http://www.thorneandderrick.co.uk)