



Pillar References	FP310	FP315	FP320	FP325	FP330
Height	950	1007	1010	1155	1173
Width	451	506	606	666	772
Depth	205	258	288	276	348
Internal Working Depth	175	230	260	245	315
Root	300	300	300	300	400
Backboard Height	830	890	890	900	1000
Backboard Width	400	425	525	570	750
Weight (Kgs)	66	62	72	100	140
Louvres	Yes	Yes	Yes	Yes	Yes

(Dimensions in mm)

Specifications

- ◆ Fabricated from 3mm mild steel sheet.
- ◆ Standard finish is hot dipped galvanised to BS EN 1461.
- ◆ 18mm thick exterior grade ply backboard, treated with a clear water repellent.
- ◆ Pillar door hinged using internal plated brass hinges.
- ◆ Earth lug fitted to both pillar and door.
- ◆ Fitted with triangular headed locks.
- ◆ Door aperture fully gasketed.
- ◆ Pillar ventilated via louvres on each side.
- ◆ Fitted with a detachable root section, open on all sides for easy cable entry.
- ◆ Designed to IP54.

Optional Extras

- ◆ Can be manufactured from stainless steel.
- ◆ Can be supplied painted leatherette black, grey or other colours on request.
- ◆ Pillar can be supplied for surface mounting.
- ◆ Can be supplied with a bitumen coated root.
- ◆ Anti-graffiti / fly poster textured finish.
- ◆ Vandal resistant padlock bar (VRB).
- ◆ Other sizes available on request.
- ◆ Cut-outs and Isolators pre-fitted to your specifications.
- ◆ All pillars can be pre-wired.

Order Reference



Ref.	Pillar Size (mm)	Ref.	Material Type	Ref.	VRB Option	Ref.	Material Thickness
310	H=950 W=451 D=205	HDG	Hot Dip Galvanised	V	Vandal Resistant Padlock Bar (VRB)	3	3mm Thick
315	H=1007 W=506 D=258	HDP	Hot Dip Galvanised and Painted (Grey as standard)	N	No VRB		
320	H=1010 W=606 D=288	STP	Stainless Steel and Painted (Grey as standard)				
325	H=1155 W=666 D=276						
330	H=1173 W=772 D=348						



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582