

**TOKSTRIP**

DESCRIPTION A cold applied preformed sealing strip based on bitumen for sealing joints between precast concrete units used for manholes, box culverts, pipes and tunnel segments.

TYPICAL PROPERTIES	DATA
Colour	Black
Non-volatile content	100%
Specific Gravity	1.37
Specific Volume	730 cm ³ /kg
Softening Point	>100°C
Flexibility	Excellent
Extensibility	>600%
Adhesion to concrete	Excellent
Watertightness	Withstands >0.5 bar
Resistance to Acids, Alkalis and Salts	Excellent
Resistance to Microbiological attack	Excellent
Root resistance	Contains additive to prevent penetration
Temperature Range For Application For Service	-5°C to +40°C -15°C to +40°C

RECOMMENDED PRIMER	Tokstrip Primer
---------------------------	-----------------

PACKING	Supplied in reels with a range of section sizes to suit particular joint designs.
----------------	-----------------------------------------------------------------------------------

APPLICATION	Instructions for use are supplied in every carton.
--------------------	----------------------------------------------------

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

